Erratum to: Bevel Gear

© Springer-Verlag Berlin Heidelberg 2016 J. Klingelnberg (ed.), *Bevel Gear*, DOI 10.1007/978-3-662-43893-0

DOI 10.1007/978-3-662-43893-0 DOI 10.1007/978-3-662-43893-0_2 DOI 10.1007/978-3-662-43893-0_3 DOI 10.1007/978-3-662-43893-0_4

Frontmatter

Page VII, line 9 from the bottom B was replaced by b

Page VII, line 11 from the bottom b_M was changed B_M

Page XXVI Garching was replaced by Eching-Dietersheim

The updated original online version for this book can be found at DOI 10.1007/978-3-662-43893-0 DOI 10.1007/978-3-662-43893-0_2 DOI 10.1007/978-3-662-43893-0_3 DOI 10.1007/978-3-662-43893-0_4

© Springer-Verlag Berlin Heidelberg 2016 J. Klingelnberg (ed.), *Bevel Gear*, DOI 10.1007/978-3-662-43893-0_9

Chapter 2

Page 19, Table 2.1 (last column) "Radius difference" was replaced by "Cutter tilt" 4 times

Page 36, Table 2.7 σ was replaced by Σ in the whole table

Page 42, Table 2.12, equ. 2.79 D was replaced by C

Page 45, Table 2.16 "the face hobbed pinion" was replaced by "all pinions"

Chapter 3 Page 67, Figure caption 3.6 " γ " was moved to the next line

Chapter 4

Page 128, Table 4.16 Equation 4.115 was changed to:

Lengthwise curvature factor	$K_{F0} = 0.211 \left(\frac{r_{c0}}{R_{m2}}\right)^q + 0.789$	For spiral bevel gears (face milled)	(4.115)
-----------------------------	---	--------------------------------------	---------

Page 128, Table 4.18, Equation 4.122 Y_{ϵ} was replaced by Y_{LS}

Page 184

Sentence "where: $\xi_V^* = \xi_V / m_{mn}$ and $\xi_R^* = \xi_R / m_{mn}$ (see Fig. 4.35)" was moved to right

Page 189 Layout of equation 4.349 was changed

E2