



Correction to: Influence of dry and solid lubricant-assisted MQL cooling conditions on the machinability of Inconel 718 alloy with textured tool

Chetan Darshan¹ · Sumit Jain² · Manu Dogra³ · Munish Kumar Gupta⁴ · Mozammel Mia⁵ · Raisul Haque⁵

© Springer-Verlag London Ltd., part of Springer Nature 2019 / Published online: 7 November 2019

Correction to: The International Journal of Advanced Manufacturing Technology
<https://doi.org/10.1007/s00170-019-04221-z>

The original version of this article contained a mistake.

In the original manuscript, the source of Figure 10 and 11 was missing. Figure 10 and 11 have been adopted from [28].

Publisher's note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

The online version of the original article can be found at <https://doi.org/10.1007/s00170-019-04221-z>

✉ Mozammel Mia
mozammelmiaipe@gmail.com

Chetan Darshan
chetandarshan@gmail.com

Sumit Jain
sumit281@rediffmail.com

Manu Dogra
mdogra7@gmail.com

Munish Kumar Gupta
munishguptanit@gmail.com

Raisul Haque
raisulshaque@gmail.com

¹ I.K.Gujral Punjab Technical University, Jalandhar, Punjab, India

² Mechanical Engineering Department, CT Institute of Engineering Management & Technology, Shahpur, Jalandhar, Punjab, India

³ Mechanical Engineering Department, SSG Regional Center, UIET Panjab University, Hoshiarpur, Punjab, India

⁴ Key Laboratory of High Efficiency and Clean Mechanical Manufacture, School of Mechanical Engineering, Shandong University, Jingshi Road, Jinan 250061, China

⁵ Mechanical and Production Engineering, Ahsanullah University of Science and Technology, Dhaka 1208, Bangladesh