

## Correction to: Design Optimization of Hybrid FRP/RC Bridge

Vasileios S. Papapetrou<sup>1</sup> · Ali Y. Tamijani<sup>1</sup> ·  
Jeff Brown<sup>2</sup> · Daewon Kim<sup>1</sup>

Published online: 31 May 2018  
© Springer Science+Business Media B.V., part of Springer Nature 2018

**Correction to: Appl Compos Mater**  
<https://doi.org/10.1007/s10443-018-9691-3>

The original version of this article unfortunately contained an error.

There was an error regarding the captions of Figures 11 and 12, which are mistakenly interchanged. Although the cross-references for these figures are accurately described in the text, the correct figure captions should be:

**Fig. 11** FE Model of the composite beam with the steel tubes

**Fig. 12** Deformation pattern of the girder under static loading, units in mm

---

The online version of the original article can be found at <https://doi.org/10.1007/s10443-018-9691-3>

✉ Vasileios S. Papapetrou  
papapetv@my.erau.edu

Ali Y. Tamijani  
tamijana@erau.edu

Jeff Brown  
jeff.brown1@erau.edu

Daewon Kim  
daewon.kim@erau.edu

<sup>1</sup> Aerospace Engineering Department, Embry-Riddle Aeronautical University, Daytona Beach, FL 32114, USA

<sup>2</sup> Civil Engineering Department, Embry-Riddle Aeronautical University, Daytona Beach, FL 32114, USA