

Index

A

- Ab initio molecular dynamics (AIMD), 169
- Acoustic phase velocity
 - change in, 263, 285
 - perturbations affecting, 263
- Acoustic wave, 261
 - advantages of, 266–267
 - devices, 261–296, 319
 - propagation modes for, 265
 - role of, 261–262
 - types of, 262
 - usage of, 262
 - in elastic media, 263–265
 - parameters effects, 263
 - sensors, properties of, 266
- Adsorption band, 165
- Adsorption enthalpy, 251
- Air pollution, 181
- Air quality assessment, 182
- Air/fuel sensor, 182
- AlN nanowires, modelling of, 171
- Amorphous fraction, 123
- Amperometric sensors, 198–199
- Anisotropic etching, 251
- Anisotropic silicon etching techniques, 6, 8
- APCVD *see* Atmospheric pressure chemical vapor deposition (APCVD)
- Aromatic hydrocarbons, 241
- Artificial neural network (ANN), 259
- Artificial olfaction systems, 257
 - See also* Electronic noses
- Atmospheric pressure chemical vapor deposition (APCVD), 77
- Atomistic model, for semiconductors, 53
- Attenuated total reflection (ATR), 215

B

- Band model, for semiconductors, 53
- Barium carbonate, 163

- BAW *see* Bulk acoustic wave (BAW)
- Benzene, 241
- Bimaterial cantilever, 316
- Bombyx mori*, 305
- Bragg grating, 277
- Bromocresol purple (BCP), 219
- Bromothymol blue (BTB), 221
- Brunauer' classification, 110
- Bulk acoustic wave (BAW), 262, 267
- Burning *see* Combustion
- Butterworth-Van Dyke (BVD), 270–271

C

- Cadmium arachidate (CdA), 281
- Calorimetric sensors, 251
- Cantilever in cantilever (CIC) structures, 321
- Cantilever-based gas sensors, 307–308
 - applications of
 - chemical vapor detection, 318–319
 - explosive detection, 319–320
 - gas pressure and flow sensing, 321–322
 - gas sensing, 316–318
 - electronic nose application, 314–316
- Capacitance-type sensors, 138
- Capillary condensation, 141
- Carbon filters, 247
- Carbon nanotubes (CNT), 317
- Catalysis, 239–240
- Catalytic combustion, 254
- Catalytic gas sensors, 6
 - See also* Pellistors
- Catalytic sensing, 241–242
- Catalytic surface reactions, 19
- Catalytic-gate field-effect gas sensors, 19
- Catalytic-gate MOS gas sensors, 4
- Catalyzers in metal oxide, usages of, 90–91
- Cathodic polarization, 187
- Cavity ringdown spectroscopy (CRS), 209

- Cavity-enhanced spectroscopy (CES), 209
 CdA *see* Cadmium arachidate (CdA)
 CdGeON oxygen sensor, 163
 Cellulose acetate, 123
 Cellulose–water system, 113
 Charge Transfer Model (CTM), 66
 Chemical gas sensor, 153
 detection mechanism of, 161
 Chemical sensitization, 69
 Chemical vapor deposition (CVD), 71, 77–79
 Chemical vapor detection, 318–319
 Chemisorption, of gas, 65–67
 Chemo-optical transducer, 222
 CMOS chemical microsensor, 318
 Co-tetra-phenyl-porphyrin (Co-TTP), 280
 Combustible gases, detection of, 238
 Combustion, 238–239
 thermal considerations during, 238–239
 Compressive surface stress, formation
 of, 307
 Conducting polymers, 225
 sensors, 323
 Conductometric sensor fabrication, 84–92
 Conventional SAW gas sensors, 285–286
 See also Surface acoustic wave (SAW)
 fabrication of, 143–144
 improvements using MEMS technology,
 145–147
 long-term stability of, 145
 performance of, 143–145
 Cross-linked PMMA-based sensor
 characteristics of
 durability against acetone vapor,
 134–135
 long-term stability, 135
 performances, 133–134
 temperature dependence, 134
 Crosslinked polymers
 polar nature of, 124
 prepared by polymerizing monomers, 127
 CTM *see* Charge Transfer Model (CTM)
 CVD *see* Chemical vapor deposition (CVD)
- D**
 Dangling bonds, of semiconductors, 52–53
 Density functional theory (DFT), 165
 Desorption process, 66
 Diamond, 171
 Dielectric passivation layers, 6
 Dielectric relaxation, 125
 Dielectric-membrane-type heaters, 12
 Dielectric-membrane-type
 micro-heaters, 12
- Diisopropylmethylphosphonate
 (DIMP), 318
 Dimethyl-methyl-phosphonate (DMMP), 225
 Dipole–dipole interaction, 113
 Direct absorption (DA), 210
 Direct current (DC) sputtering, 74
 Distortion polarization
 caused by intermolecular interaction,
 112–113
 degree of, 122
 Distributed feedback (DFB) laser
 diodes, 210
 Divinyl benzene (DVB), 133
 Donor defect level, in surface states, 53
 Dopants in metal oxide, usages of, 90
 DRIFT spectroscopy
 atmospheric pressure, for, 157
 in situ studies of adsorbates, for, 163–168
- E**
 EBE *see* Electron beam evaporation (EBE)
 Electrical capacitance, 141–142
 Electrical sensitization, 69
 Electron beam evaporation (EBE), 74
 Electronic detectors, for nerve agents, 306
 Electronic noses, 257–259, 314–316
 Ellipsometric gas sensor, 214
 Ellipsometry, 213–216
 Evanescent-wave sensors, 221–222
 Exhaust gas sensors, 181
 Exhausts emission, regulations for, 182
 Exothermic chemical reactions, 237
 Explosive mixtures, 240–241
 procedure for safe detection of, 244–245
- F**
 Fermi level, 97, 98
 Fermi–Dirac statistic, 50
 FET devices
 detection mechanism of, 154–157
 nanoparticles as sensing layers in,
 171–173
 FET gas sensors, 154
 atomistic modelling of chemical reactions
 on, 168–171
 FET sensing layers, nanostructure of, 160
 FET surface reactions, UHV studies of,
 157–159
 Fiber Bragg gratings, 226
 Fiber cladding, 223–224
 Fiber optics, 220
 sensors, 224
 Fiber-optic SPR (FO-SPR) sensors, 222–224

- Field-effect transistor (FET) sensors, 324
Field-effect gas sensors, 11, 19–21
Filters in metal oxide, usages of, 91–92
Fire detectors, 34
Flame arrestor, 244
Flammable gases, catalytic combustion of, 241, 251
Flash point, 241
Flexural-plate-wave (FPW), 262, 323
Flory–Huggins isotherm, 110
Flory–Huggins statistics, 110
Flory–Huggins theory, 110
FPW *see* Flexural-plate-wave (FPW)
Free surface, of semiconductor, 52
Frequency modulation (FM) spectroscopy, 210
Frustrated total internal reflection (FTIR), 218
- G**
- Gas and vapor sensitivity, in SAW
 acoustoelectric perturbations, 288–291
 mechanical perturbations, 287–288
Gas sensors
 development of, 3–4
 light activation in, 99
 polymer-based, *see* Polymer-based gas sensors
 silicon, *see* Silicon, sensors
 thermal microstructures, 6–11
 thermal sensors and actuators, 4–6
Gas-phase decomposition, 193
Gas-sensing microsystems, 3
 air quality monitoring and leak detection, for, 27–33
 conventional and microstructured fibers for, 224–228
 guided-wave configurations for, 220–222
 industrial applications, 34
 low false-alarm-rate fire detection, for, 23–27
Gold nanoparticles, 173
Green-house effect, 191
Guided-wave sensors, advantages of, 220
- H**
- Hall effect position sensors, 251
Hartree-Fock method, 169
Hazardous gases, 191
He/Ne laser, 322
Heat conductivity sensors, 11–15, 257
Henry' law, 110
 See also Flory–Huggins isotherm
Heterogenous catalysis, 241, 242
Hetero-junction, NiO–Au–YSZ interface, 194
High-temperature bias (HTB), 19
Hollow-core photonic band-gap fibers, 228
Humidity sensors
 applications of, 109
 categories of, 109
 characteristics of, 141
 development of, 109
Hybrid suspended gate field-effect (HSGFET) devices, 158
Hydrocarbon gases, 19
Hydrogen bonding, 123
Hydrogen-bond basicity, determination of, 117
Hydrogenated fluorocarbon gases, 27
Hydrophilic cross-linking agent, 127
Hydrophilic polymers, sorption isotherms of, 110
Hydrophilic/hydrophobic ligands, 311
Hydrophobic polymer, 128
 cross-linked, 131
 thin films, 130–131
Hygroscopic polymers, 109
- I**
- I–V characteristics, 21
IDTs, *see* Interdigital transducers (IDTs)
Impedance
 analysis, 271
 measurement, 94
Impedance-metric sensors, 197, 200–201
 environmental monitoring of C₃H₆, for, 201–203
 sensing of various gases, for, 200
Independent component analysis (ICA), 319
Indium-tin-oxide (ITO), 272
Inductively coupled plasma (ICP) etching, 147
Infrared gas-sensing microsystems, 5
Inkjet-spotting technique, 313
Integrated calorimetric sensors, 256–257
Integrated optical SPR sensors, 222
Integrated optics (IO), 220
Interdigital microelectrodes, 146
Interdigital transducers (IDTs), 262
Interference fringes, 210
Intermodal coupling, 223
Intermolecular interactions, 115
IO, *see* Integrated optics (IO)

- Ionosorption, definition of, 67
 IR filter, narrow-band, 27
 ITO, *see* Indium-tin-oxide (ITO)
- K**
 Katharometers, *see* Thermal conductivity (TC) gas detectors
 Kelvin probe measurements, 163
 Kretschmann configuration, 217
 Kretschmann sensors, 222
 Kurosaki's equation, 128
- L**
 Lambert-Beer law, 209
 Langmuir-Blodgett (LB), 273, 281
 film, 221
 Large and medium enterprise (LME), 36
 Laser ablation process, 76, 77
 Laser chemical vapor deposition (LCVD), 77
 LB, *see* Langmuir-Blodgett (LB)
 LCVD, *see* Laser chemical vapor deposition (LCVD)
 Leaky surface acoustic wave (LSAW), 284
 LEDs, *see* Light emitting diodes (LEDs)
 Lennard-Jones representation of gas
 adsorption, 65–67
 Light detector, 24, 25
 Light emitting diodes (LEDs), 99
 Light impinging, 215
 Love wave/mode, 284, 292
 Low pressure chemical vapor deposition (LPCVD), 77
 Low wavelength modulation (LWM), 210
 Low-index guiding fibers, 227
 Lower explosive limits (LEL), 14, 240
 LPCVD, *see* Low pressure chemical vapor deposition (LPCVD)
 LSAW, *see* Leaky surface acoustic wave (LSAW)
- M**
 Mach-Zehnder Interferometers (MZI), 221
 Mass flow controllers, 314
 Mass sensitivity, of SAW mode, 287
 Materials fabrication processes, 48
 Mechanical sensing
 approaches to, 305–307
 deflection measurement for, 307–310
 functionalization, 312–313
 modes of operation for
 dynamic mode, 311
 static mode, 310–311
- Mercury vapor-sensing applications,
 274–276
 Metal oxide (MOX) gas sensors, 15–18
 thin-film, 17
 use of, 2
 Metal oxide gas sensors, 322
 Metal oxide semiconductor (MOS)
 devices, 156
 Metal oxide semiconductor gas sensor, 49–50
 absorption over surface
 catalysts and promoters, 69
 physical and chemical adsorption,
 65–67
 surface reactions, 67–69
 conduction models of, 58–60
 mono-crystalline metal oxides, 63–65
 polycrystalline devices, 60–62
 conductometric sensor fabrication, 84–92
 dopings, catalysts and filters, 90–92
 electrical contacts, 88
 substrate and heater, 84–88
 thermal treatments, 89–90
 deposition techniques of
 one-dimensional materials, 80–84
 three-dimensional
 nanostructures, 70–71
 two-dimensional
 nanostructures, 71–80
 electrical properties of surface
 dipole, 57–58
 semiconductor statistics, 50–52
 space charge region, 54–57
 states of, 52–53
 geometric structures of surface, 49–50
 principles and novel devices
 AC impedance, 94
 DC resistance, 92–94
 response photoactivation, 95–99
 surface electronic structures of, 50
 Metal oxide semiconductor, light effect
 on, 95
 Metal shield electrode, 148
 Metal-dielectric interface, 220
 Metal-organic chemical vapor deposition (MOCVD), 77
 Michelson interferometer, 322
 Micro-electro-mechanical systems (MEMS)
 and silicon components, 251–252
 batch fabrication technologies, 2
 foundry, 38
 gas-sensing devices, 12
 hydrogen sensor, 317
 micro-miniaturization technologies, 34

- Micro-fabricated cantilevers, 306
 - Micro-fabricated detectors, 319
 - Micro-gas-sensors, 6
 - Micro-heaters, 6, 16
 - Micro-hot-plate sensor, 251
 - Micro-machined gas sensors, 26
 - Micro-total analytical systems (Micro-TAS), 251
 - Microcalorimeters, 242, 248–249
 - Microcantilever arrays, measurement setup for, 313
 - Microcantilever deflections, 309
 - Microcantilever-based sensing, 305
 - Microfluidic systems, 248
 - Micromachining, 251
 - Microstructured optical fiber (MOF), 228
 - MIPs, *see* Molecular imprinted polymers (MIPs)
 - Mixed-potential-type gas sensors, 185
 - sensing performances for
 - high-temperature-type NO_x sensors, 185–189
 - hydrocarbon (C₃H₆ or CH₄) sensors, 191–192
 - improvement in NO₂ sensitivity by additives, 189–190
 - nano-sized Au thin-layer for sensing electrode, 196–198
 - MOCVD, *see* Metal-organic chemical vapor deposition (MOCVD)
 - Molecular absorption, 210–211
 - Molecular imprinted polymers (MIPs), 273
 - Molecular packing, 124
 - Molecular recognition phases (MRP), 319
 - Mono-crystalline silicon, 3
 - Monocrystalline gas sensors, 59, 63–65
 - Multi-layered SAW-based gas sensors, 286
 - See also* Surface acoustic wave (SAW)
 - Multi-walled carbon nanotube (MWCNT), 274
 - See also* Carbon nanotubes (CNT)
 - Multichannel sensing devices, 223
 - Multipass absorption spectroscopy (MPAS), 210
- N**
- Nanocomposite systems, effects of, 91
 - Nanocrystals, surface properties of, 220
 - Nanogold, surface of, 195
 - Nanoparticles
 - as sensing layers in FET devices, 171–173
 - gold, of, 173
 - Nanostructures, 192–195
 - Nanowires, 230
 - NDIR gas-sensing systems, 22
 - NiO–YSZ interface, 187
 - Non-dispersive infrared (NDIR)
 - absorption, 27
 - Non-dispersive infrared (NDIR) gas-sensing systems, *see* NDIR gas-sensing systems
- O**
- Oligonucleotides, 313
 - On-board diagnosis (OBD) system, 181
 - Optical beam deflection, 309
 - Optical communications, 211
 - Optical filter, narrow band, 27
 - Optical gas sensors, 230
 - Optical noise, 211
 - See also* Shot-noise
 - Optical sensors
 - advantages of, 209
 - spectroscopic detection, for, 210–213
 - Optical spectroscopy, 210
 - Optical wave, 220
 - Optical waveguide, 219
 - properties of, 223
 - systems, 218
 - Otto arrangement, 218
- P**
- PAA *see* Poly acrylic acid (PAA)
 - Parallel resonant frequency, 271
 - PCVD *see* Photochemical vapor deposition (PCVD)
 - PECVD *see* Plasma enhanced chemical vapor deposition (PECVD)
 - Pellistors, 6, 8, 242–244
 - calibration of, 245
 - limitations for using, 247–248
 - multisensor array of, 256
 - Perturbation theory, 288
 - Phase-lock loop (PLL), 268
 - Photo-acoustic (PA) gas detection, 28
 - Photo-acoustic spectroscopy (PAS), 210
 - Photochemical smog, 191
 - Photochemical vapor deposition (PCVD), 77
 - Photoconductivity curves, shape of, 95
 - Photoelectric fire detectors, 23
 - Photoexcitation and polycrystalline material, 96
 - Photolithography, 147
 - Photonic bandgap (PBG), 228
 - Photonic crystal fiber (PCF), 228, 230
 - Physical vapor deposition (PVD), 71–72

- Physisorption of gas, 65–66
 Piezo-driven ejection system, 312
 Piezocrystals, 308
 Piezoelectric effect, 308
 Piezoelectric material and acoustic wave devices, 262
 Piezoelectricity, characteristics of, 263
 Piezoresistive microcantilevers, 308, 309
 Piezoresistors, 305, 308
 Plane-polarized light, 216
 Plasma enhanced chemical vapor deposition (PECVD), 77
 PLD *see* Pulsed laser deposition (PLD)
 PLL *see* Phase-lock loop (PLL)
 PMMA *see* Poly methy methacrylate (PMMA)
 Poisson equation, 54
 Polarization current, 197
 Poly acrylic acid (PAA), 274
 Poly methy methacrylate (PMMA), 279
 Poly vinyl alcohol (PVA), 274
 Poly (etherurethane) (PEUT), 318
 Poly-methylmethacrylate (PMMA)-based humidity sensor
 dielectric relaxation of, 132
 electrical capacitance of, 131
 long-term stability, 132–133
 performances of, 131
 temperature dependence of, 131–132
 Polycrystalline gas sensors, 59–63
 Polyelectrolyte, 109
 Polyethylene glycol (PEG), 318
 Polyethylene oxide (PEO), 317
 Polyimide-based sensor, acetylene-terminated, 138–141
 Polymer-based gas sensors, 24
 Polymer–solvent interaction, 110
 Polymers
 characterization of
 capacitance changes with water sorption, 120–123
 FT–IR measurement, 115–116
 solvatochromism, 117–119
 sorption isotherms, 113–115
 chemical structure of, 114
 coating, 318
 cross-linked, *see* Crosslinked polymers
 high-molecular-weight, 111
 hydrogen-bonding ability, 111
 molecular structures of, 124–125
 sensing layers, 311
 sensor array, 259
 sorbed water effects on dielectric properties of, 111–113
 sorption isotherms of, 110
 thin films, 109, 126
 water sorption behavior of, 111–113
 Polypyrrole, 226
 Polysulfone-based sensor
 long-term stability, 137–138
 performances, 136–137
 Polyvinyl chloride (PVC), 241
 Porous silicon (PS), 216, 254
 Position-sensitive detector (PSD), 309
 Pre-polymerized monomer, 125
 Preferential oxidation (PROX), 90–91
 Principal component analysis (PCA), 258, 315
 Printed circuit board (PCB), 30
 Prism-coupled total reflection systems, 218
 PROX, *see* Preferential oxidation (PROX)
 Pseudo surface acoustic wave (PSAW), 284
 Pt/air reference electrode, 204
 Pulsed laser deposition (PLD), 76, 77
 PVA, *see* Poly vinyl alcohol (PVA)
 PVD, *see* Physical vapor deposition (PVD)
 Pyroelectric crystal, 255
 Pyroelectric sensor, 255
- Q**
- QCM, *see* Quartz crystal microbalance (QCM)
 QCR, *see* Quartz crystal resonators (QCR)
 Quadrant cell photodetector, 217
 Quantum cascade lasers (QCL), 212–213, 230
 Quartz crystal microbalance (QCM), 111, 262, 267, 323
 based gas sensors, 268–269
 gas and vapor sensitivity, 269–271
 performance, 272–276
 Quartz crystal resonators (QCR), 268
 Quartz crystal, AT-cut and BT-cut in, 265
- R**
- Radio frequency (RF) sputtering, 75
 Rayleigh hypothesis, 270
 Rayleigh mode, 284
 Rayleigh waves, 324
 Reetz sacrificial anode electrolysis, 172
 Reference-electrode (RE), 204
 Refractive index, 215
 Refractive index units (RIUs), 224

- Resonant frequency, 270–272
 Rheotaxial growth and thermal oxidation (RGTO) technique, 89–90
- S**
- Saturated hydrocarbons, 197
 Sauerbrey equation, 269–270
 Sauerbrey-Lotsis approximation, 278
 SAW, *see* Surface acoustic wave (SAW)
 Scanning light pulse technology (SLPT), 162
 Schottky diodes, 154
 Schrödinger equation, 168
 SCR, *see* Space charge region (SCR)
 Screen-printing technique, 196
 Seebeck effect, 254, 259
 Selective sublimation process (SSP), 89
 Semiconductors
 - bulk conductivity of, 52
 - composition, radiation effect on, 96–97
 - gas sensor, 223
 Sensing-electrode (SE), 182
 Sensitivity curve, 93
 λ Sensor, *see* Air/fuel sensor
 Sensor
 - arrays, 257–259
 - fabrication using thin Au-SEs, 196
 - method for preparing, 146–147
 - networks, bus-connected, 16
 - response curve, 93
 - sensing characteristics of, 147–149
 - thermal conductivity, 249–250
 - thermal consideration for development of, 252–254
 Shear horizontal acoustic plate mode (SH-APM), 262
 Shear horizontal surface acoustic wave (SH-SAW), 284
 Shot-noise, limit for, 211
 Silicon
 - membrane microcalorimeter, 248
 - microsensors, 251
 - monocrystalline, 3
 - sensors, 3
 Silicon carbide devices, 21
 Silicon dioxide (SiO₂), 264
 Silicon-MOS (SiMOS) capacitors, 19
 - C-V characteristics of, 19
 Silicon-on-insulator (SOI) techniques, 8
 Single mode fiber, 224
 Single nanowire transistor (SNT), 64
 Single-mode IO waveguides, 223
 Single-walled carbon nanotube (SWCNT), 274
 Sintered flame arrestor, 247
 SiO₂:Si interface, 19
 SLPT, *see* Scanning light pulse technology (SLPT)
 SLS, *see* Solution liquid-solid (SLS)
 Small and medium enterprises (SME), 35–36
 SMRs, *see* Solidly mounted resonators (SMRs)
 Snell's law, 214
 SnO₂
 - nanobelt gas sensors, 171
 - nanoparticles, 171
 SNT, *see* Single nanowire transistor (SNT)
 Sol-gel process, 79–80
 Solid electrolytes, 182
 Solid state gas sensors, 241
 Solid-electrolyte amperometric sensors, 198
 Solid-state gas sensors, 47, 157
 - for monitoring of pollutant gases, 182
 - mechanistic studies of, 160
 Solid-state reference electrode, 204–205
 Solidly mounted resonators (SMRs), 276
 - structures of, 276–278
 Solution liquid-solid (SLS), 83
 Solvatochromic band, 117
 Sorption isotherm, 110, 113–115
 - various cellulose thin films, of, 120
 Source-to-waveguide light coupling, 221
 Space charge region (SCR), 65
 Spectrophotometer, 224
 SPR gas sensors, 220
 Sputtering plant, 74
 SSBW, *see* Surface-skimming bulk wave (SSBW)
 SSP, *see* Selective sublimation process (SSP)
 STW, *see* Surface transverse wave (STW)
 Surface acoustic sensors, 323
 Surface acoustic wave (SAW), 262
 - based gas sensors, 282–285
 - conventional, 28
 - gas and vapor sensitivity, 286–291
 - multi-layered, 286
 - performance, 291–295
 Surface dipoles, 57–58
 Surface electromagnetic waves, 216
 Surface plasmon metal interface, 224
 Surface plasmon polaritons, *see* Surface plasmons
 Surface plasmon resonance (SPR), 209, 216–221
 Surface plasmon waves, 223

- Surface plasmons, 216
 Surface space charge region, 54–57
 Surface transverse wave (STW), 284
 Surface-localized states, formation of, 53
 Surface-relief gratings, 222
 Surface-skimming bulk wave (SSBW), 284
 SWCNT, *see* Single-walled carbon nanotube (SWCNT)
 Swelling, 131
- T**
- Telecommunication fibers, 227
 Temperature coefficient of resistivity (TCR), 7
 Temperature programmed desorption (TPD), 165
 Tetrafluoroethane (CF₃CH₂F), 27
 TFBAR, *see* Thin-film bulk acoustic resonator (TFBAR)
 TFRs, *see* Thin-film resonators (TFRs)
 TFT, *see* Thin-film transistors (TFT)
 Thermal activation, 16
 Thermal annealing, 39
 Thermal capacitance, 244
 Thermal conductivity (TC) gas detectors, 249
 Thermal infrared emitters, 11, 21–22
 Thermal insulation, degree of, 6
 Thermal mass flow sensors, 6
 Thermal microstructures, 6
 architectures of, 6–7
 kinds of, 27
 use of, 4–5, 12
 Thermal resistor model, 11
 Thermometric gas sensing, 251–252
 categories of, 237
 Thermopiles, 31
 Thick-film
 gas sensors, 26, 36
 technology, 71
 Thickness shear mode (TSM)-based gas sensors, 267–268
 QCM-based sensors, 268–269
 gas and vapor sensitivity, 269–272
 performance, 272–276
 TFR-based sensors, 276–285
 Thickness-shear mode sensors (TSM), 323
 Thin films, 140
 Thin-film alloys, 7
 Thin-film bulk acoustic resonator (TFBAR), 262
 structure of, 276
 Thin-film resonators (TFRs), 262, 267
 advantages and disadvantages of, 278–279
 BVD equivalent circuit of, 270
 gas sensors performance, 279–282
 Thin-film transistors (TFT), 64
 Three-way catalyst (TWC), 181
 Ti:LiNbO₃ channel waveguide, 222
 Tiersten boundary condition, 287
 Total internal reflection (TIR), 216, 219, 228
 Tunable diode-laser absorption spectroscopy (TDLAS), 210
 Tunable diode-laser spectroscopy (TDLS), 212
 Tunable infrared laser differential absorption spectroscopy (TILDAS), 210
- U**
- Ultrahigh-resolution detection system, 220
 Ultraviolet photoemission spectroscopy (UPS), 50
 Upper Explosive Limit (UEL), 240
- V**
- Vacuum pressure sensors, 15
 van der Waals volume, 124
 Vapor liquid-solid (VLS), 83–84
 Vapor-solid (VS), 83
 Vertical-cavity surface emitting lasers (VCSELs), 313
 Vibrational-rotational energy, 29
 VLS, *see* Vapor liquid-solid (VLS)
 VM, *see* Volkenstein Model (VM)
 Volatile organic compounds (VOC), 248, 267, 311, 318, 322–323
 Volkenstein Model (VM), 67
 VS, *see* Vapor-solid (VS)
- W**
- Water affinity parameter (WAP), 116
 Water binding energies, 113
 Water sorption, 120–123
 by forming crosslinked structure, 130
 isotherms, 121
 Water surface adsorption, 147
 Weight percent oxygen (WPO), 127
 Wide-band-gap semiconductors, 16
 WO₃ nanocrystalline powders, 165

Y

Yttria-stabilized zirconia (YSZ)-based gas sensors, 182, 185
grain-boundaries of, 196

Z

Zeolite-coated QCMs, 273
Zeolites, 317
Zirconia-based oxygen sensor, 204