

Subject Index

A

Actel, 2–3, 12, 26–27, 29–34, 163, 165, 180, 182–184, 198–203, 208, 210–211, 214–215

Algorithm, 2–3, 30, 56, 75, 79, 89, 94, 129, 141–148, 153, 156–159, 163, 165–167, 182, 187, 189–192, 195–197, 201–203

Alpha particle, 38–39, 42

Amorphous silicon, 118–120

Analysis, 37–81, 88, 92, 96, 131–132, 149, 152, 159, 163–165, 187, 189–195, 197, 199–201, 203, 205, 208–210, 213

Antenna, 60–61, 134–135, 137

Antifuse, 7, 13, 18, 113, 118–120, 211

Application, 1–3, 7, 30–31, 33–34, 37–38, 48–49, 51, 62–64, 68–70, 74–75, 78, 85–86, 88–99, 106, 112–113, 117–118, 121, 124, 137–138, 143, 148–149, 158–159, 179–186, 205–206, 209–215

Area, 22, 40–41, 48, 50, 67, 87, 92–94, 104–105, 109–110, 114, 116, 119, 122–123, 128–129, 139, 145, 152, 156–157, 159–161, 164, 187–191, 193–194, 203

Arithmetic function, 1, 180

ASIC, 1, 85, 137, 159–160, 184

Atmel, 3, 180, 184–186, 208, 210

B

Benchmark, 129, 187–191, 195–197, 201–202

BESOI, 99–100, 102

BISER, 109–110

Body effect, 105

Bridge, 60–61, 134–137, 141

C

C-element, 109–110, 123

Charge accumulation, 44–45, 49

CLB, 8–9, 15–16, 19, 24–25, 29, 58, 60–61, 134–135, 149–150, 152–157, 180, 194

Cluster, 29, 71, 79–80, 149, 153, 156–157, 195

Coarse-grain, 15–16

Commercial off the Shelf (COTS), 97, 149, 179, 214–215

Configuration memory, 3, 7, 13–15, 18–22, 51–52, 54–58, 60–66, 69, 71–81, 86–88, 95–96, 106, 113, 120–121, 126–128, 131, 133–134, 136, 148–154, 157, 167–168, 180–183, 185–189, 191–197, 208–211

Conflict, 59–60, 134–137, 141

Constraint, 14, 16, 37, 79, 88, 92–95, 129–132, 138–139, 143–146, 157, 159, 190, 195, 201, 205

Cosmic Ray, 38–39, 43, 110–111

Cost, 1–2, 7, 33, 66, 86, 88, 97–98, 100, 104, 110, 126, 129, 143–145, 147, 157, 159, 165–166, 179, 190, 215

CRIL, 110–111

Cross-section, 62–63, 66

D

Decoupling resistor, 113–115

Delayed clock, 112–113

Dependability, 7, 37, 71, 74–75, 77–79, 195

Design

- designer, 26, 51, 68, 74, 86–89, 91–92, 94, 96, 103, 122, 129, 179, 181–182
- flow, 3, 63, 87, 89, 141
- process, 85–89, 91–97

Device, 1–3, 7, 13–15, 17–18, 21–27, 29–34, 37–68, 72–75, 85–88, 91–94, 96–98, 100, 102–105, 113, 118–120, 122, 129–130, 132, 141, 148–149, 152, 156, 160–161, 163, 167–168, 179–184, 186, 187–199, 205

DICE, 107–110, 113

Dielectric, 49, 100, 118–120
 Direct ionization, 42, 48
 Displacement effect, 44
 DSP, 24, 30–31, 51, 180
 Duplication with comparison (DWC),
 128, 211

E
 EDAC, 121, 210–211
 Edgeless transistor, 104–105
 EDIF, 90–92
 Embedded memory, 1, 185, 210
 Emulation, 64, 71–72, 74
 Energy loss, 41–43, 158

F
 Failure mode, 3, 37–81
 FAMOS, 12, 18
 Fault
 injection, 64, 68–74, 89, 92, 125, 192,
 201–203
 model, 3, 44–45, 50–52, 69, 71, 89, 92,
 96, 109
 tolerance, 37, 87
 Feedback, 47–48, 106–109, 111, 113, 116,
 127, 130, 132
 Field programmable gate array, 1, 7–34, 37–81,
 85–168
 Filtering, 31, 114, 159–160
 Fine-grain, 14–15
 Finite state machine (FSM), 22, 25, 52, 188
 Flash, 33, 49, 51, 113, 116–118, 182, 184, 211
 Flash-based FPGA, 51, 117–118, 158, 165,
 182, 198–203, 211
 Flip-flop, 16, 21, 24–27, 29, 50–52, 57–58,
 91–92, 106, 109–110, 112, 124, 127,
 137–138, 141, 152, 159–160, 181–183,
 185–188, 191, 195, 198, 202, 208–211
 Floating gate, 12–13, 18, 49, 116–118, 180,
 182, 184
 Floorplan, 129, 192
 Fluence, 40, 60, 102, 195, 198, 200
 Flux, 40, 49, 64, 66, 205–208
 FPGA, 1–3, 7–15, 17–34, 37, 48, 50–58,
 62–66, 68–69, 71–72, 74–76, 78–81,
 85–89, 91–168, 179–187, 189–195,
 197, 199, 201–202, 205
 Frame, 22, 80, 149, 152, 153, 167–168, 181,
 194–195
 Funneling, 43–45

G
 Granularity, 14, 150
 Ground radiation, 39

Guard-gate, 123–125
 Guard-rings, 102–103

H

Hardening technique, 79, 85–86, 88–89,
 91–92, 104, 111, 148–150, 191, 195
 Heavy-ion, 39, 42–43, 48–49, 67, 78, 125,
 148–149, 158, 161, 181–183, 185–186,
 197, 206, 208–211

I

Indirect ionization, 42, 48
 Input/output, 1, 12, 19, 21, 75, 87, 97,
 124–125, 180
 Interconnection, 7–9, 12, 14, 16–19, 21, 23–24,
 26–30, 33, 51–52, 58, 77, 80–81,
 86–87, 89, 94, 126, 128, 130, 134, 139,
 142, 147, 152, 154–155, 158–159, 163,
 165–166, 197–199
 IOB, 80–81, 149, 180, 191
 Ionizing radiation, 2–3, 49, 62–63, 68–69, 101,
 103, 122, 149, 179, 181, 183,
 205–206, 214

L

Latch, 15–16, 21, 25–26, 45, 47, 66, 92, 96,
 100, 103–104, 106–113, 122–124, 130,
 133, 159–160, 210, 215
 Layout, 78–80, 85, 87–88, 90, 96–97, 104,
 109, 122, 130, 152–153, 156–160, 165,
 185, 194–195, 197, 199
 Linear energy transfer (LET), 42, 45, 49, 66,
 134, 161, 181–183, 186, 205–210

Logic
 cell, 1, 159–160
 function, 1, 7, 12, 15–17, 24, 31, 54, 56–57,
 61, 78, 133, 141–143, 145–146,
 150, 165
 resource, 9, 24–27, 29, 31–32, 34, 54,
 57–58, 61, 78, 81, 87, 91, 93, 96, 124,
 129–130, 134, 138, 153, 165, 182–183,
 189, 199
 Logic placement graph (LPG), 153–154,
 156–157
 LUT, 7–8, 22, 24–25, 29, 57, 61, 77, 92, 128,
 134, 138, 152–153, 157, 187, 191, 194

M

Manufacturer, 1, 3, 7, 15, 24, 27, 31, 33–34,
 54, 63, 85, 96–125, 179, 182, 205, 214
 Mapping, 86–87, 92, 94, 130–132, 142, 152,
 154, 164, 192–193, 209
 Mission-critical, 2, 37–38, 85, 95, 112, 118,
 121, 179–186, 214

- Mitigation, 2–3, 50, 72, 75, 78, 85–89, 91–92, 94, 96–97, 104–106, 113–124, 126–168, 179–181, 183, 186–203, 205, 210–212, 214–215
- Mitigation technique, 2–3, 50, 72, 75, 78, 85, 87, 91–92, 94, 96–168, 178, 181, 183, 187–203, 205, 210–211, 214–215
- Multiple cell upset (MCU), 45, 47–48, 51–58, 70, 72, 74, 78–81, 98, 132–133, 137, 148–157, 159, 192–198
- Multiplexer, 13–15, 18–20, 26, 52–53, 57–58, 61, 152
- N**
- Netlist, 86, 89–92, 130, 165–166, 190
- O**
- Open, 14, 26, 58–59, 77–78, 80–81, 134–137, 141, 155–156, 182
- Oxide-Nitride-Oxide (ONO), 116–119
- P**
- Performance, 1, 24, 27, 29–31, 44, 49, 52, 68, 71, 87–88, 92, 94–95, 102, 104–105, 113, 121, 123, 129, 148–149, 154, 187, 190–192
- PHAM, 153, 156, 197–198
- Physical effects, 41–44, 96
- PIP, 18–20, 22, 53–56, 58–61, 75–78, 119, 141, 150, 153, 156, 194
- PIPB, 124
- Placement, 29–30, 44–45, 49, 86, 88, 92–94, 129, 141–145, 153–157, 159–160, 165–167, 189–190, 198–199, 201–202, 213
- ProASIC, 3, 26, 165, 180, 182–184, 198–203, 208–211, 215
- Processor, 7, 24, 31–34, 48, 51–52, 65, 71, 188, 197
- Programmability, 12, 49, 52, 113, 182
- R**
- Rad-hard, 78–79, 88, 97, 195
- Radiation
 - effect, 3, 39, 42–43, 50, 86–87, 89, 94, 96–97, 110–111, 113, 179–181, 205–206, 209, 214–215
 - experiment, 133
 - testing, 64, 66–68, 78, 125, 149
- Radiation hardened by design (RHBD), 87, 97, 104, 110, 122, 179–180, 182–185, 210
- Reconfigurable, 1–3, 7–34, 37–81, 85–168, 179–181, 183, 211, 213–215
- Reconfiguration, 1–2, 48, 51, 72, 87, 93–96, 113, 118, 126, 129, 148, 167–168, 211
- Redundancy, 79, 87, 106–107, 112–113, 121–123, 126, 128, 130, 137–141, 148–150, 158–160, 185, 195, 210–211
- Reliability, 85, 87, 92, 94–97, 104–105, 120–122, 141–144, 146, 196
- Resource, 1, 3, 9, 12, 16, 19, 21–34, 50, 51–58, 61–63, 65–66, 69, 74–75, 77–81, 86–88, 91–97, 121–122, 124, 126–127, 129–130, 132–136, 138–139, 141, 143–144, 149–153, 155, 160, 165, 180–183, 186, 188–190, 194–196, 199, 209, 212, 214–215
- Reverse-body bias (RBB), 104–106
- Robust, 3, 87–88, 94, 96, 103, 105–107, 113, 121, 142, 186–189, 197, 210–211
- RoRA, 141–148
- Routing
 - graph, 77, 78, 142–143, 145–148
 - resource, 12, 19, 21, 52, 54, 58, 61–62, 94, 126–127, 129, 133–136, 138, 143–144, 149, 151, 155, 160, 182–183, 190
- S**
- Scrubbing, 72, 121, 130, 167–168, 210–211
- S/DH latch, 111–113
- Short, 14, 24, 48, 65, 66, 77–78, 80–81, 114, 122, 124–125, 143, 146–147, 152, 155–156, 166, 168, 199–201
- Silicon, 1, 39, 42, 62–63, 67–68, 98–102, 105, 111, 114, 116–120, 152, 161, 179–180, 182, 185, 194, 215
- Silicon on insulator (SOI), 98–104, 116
- SIMOX, 99–102
- Simulation, 44, 63–64, 68, 71–72, 74, 88–89, 92, 125, 136, 199
- Single event effect (SEE), 45, 47, 49, 63, 87, 96, 106, 118, 124, 129, 192, 194, 205–206
- Single event functional interrupt (SEFI), 45, 48, 66, 70, 72, 133–135, 181–182, 211
- Single event latch-up (SEL), 45, 48, 52, 66, 97–104, 130, 133, 180–181, 183, 186
- Single event transient (SET), 45, 66, 157–167, 198–201
- Single event upset (SEU), 45, 47, 49–, 62, 65–67, 69, 71–72, 74–78, 80, 95, 106–107, 109–113, 116–117, 121–122, 126–128, 130–134, 136–137, 141–149, 158, 167–168, 180–183, 185–192, 195–197, 209–210
- Slice, 24–25, 29
- Space radiation, 38–39

- Speed, 1, 24–25, 30, 34, 38–39, 64, 123, 148, 214–215
- SRAM, 7, 12–15, 18, 47, 51, 80, 107, 113–118, 121, 149, 167, 184, 193
- SRAM-based FPGA, 14, 63–64, 72, 74–76, 78, 126, 128–131, 141, 148–149, 152, 167–168, 182, 184, 187, 189, 190, 194–195, 197, 211
- STAR, 74–76, 78–81, 187, 210
- Static analysis, 88, 92, 149, 189, 191–192
- Stopping power, 41–42
- Switch-block, 9–10, 17–18, 52–56, 136–137, 141
- Switch-matrix, 24, 28–29, 77, 95, 149, 152, 155
- Synthesis, 16, 73, 76, 86, 89–92, 126–132, 180
- T**
- Technology, 3, 7–8, 12–14, 18, 39, 43–44, 51, 62–66, 68, 85–89, 96–99, 104, 109, 113–120, 122, 141–142, 149, 157–158, 160–161, 179, 185, 205–206, 213–214
- Testing
 - accelerated, 64, 66–68, 78, 149, 186, 207
 - life, 64–66
 - radiation, 64, 66–68, 78, 125, 149
- TMR, 75–76, 78, 81, 91, 106–107, 113, 124–128, 130–132, 137–143, 148–151, 153, 159, 185, 187–192, 195–198, 210
- domain, 153–157
- Total ionizing dose (TID), 45, 49–50, 66, 104, 133–134, 183
- Transistor, 12–14, 18–19, 21, 27, 43–45, 47–50, 52, 87–88, 97–99, 101–106, 108–114, 116–117, 122, 158, 160, 182–184
- Trench isolation, 102–103
- U**
- User, 1, 3, 31, 33–34, 38, 44, 51–52, 64, 66, 69, 72–73, 75, 85–86, 88, 91, 96–97, 106, 126–168, 181, 183–186, 205, 208–209
- V**
- Van Hallen Belts, 39
- VersaTile, 26, 29–30, 182–183
- Virtex, 1, 3, 24–27, 30, 32–33, 65, 75, 78, 80, 133, 149, 152–153, 156, 168, 180–182, 187–198, 208–211, 215
- Voter, 126–128, 130–132, 138, 142, 150–151, 153–157, 188, 190–191, 198
- X**
- Xilinx, 1, 3, 15–16, 24–34, 54, 64–65, 72, 75, 78, 80, 91, 129, 149, 152–153, 156–157, 168, 180, 182, 187–198, 208, 211, 214–215