

Index

A

Aerial work platform, 23, 28, 49

B

Building material(s), 1–3, 23–24, 47, 53, 65

C

Compliance, 7
Conceptual design, 23
Constrained case, 7
Construction industry, 1–2
Construction robot(s), 1–3, 5, 23–27, 29, 37, 47–48, 52–53, 55, 58, 62, 64–67
Curtain wall(s), 1, 3–4, 65

D

Deck, 53–55
Denavit-hartenberg notation, 31

F

Falling accident(s), 23–24
Field test, 47
Force augmentation ratio, 7
Force/torque sensor, 31
Functional requirement(s), 23–24, 26

G

Glazed ceiling panel(s), 23–24, 26–27, 48, 53

H

Human–robot cooperative manipulation, 1
Human robot interface, 23, 52

I

Impedance parameter(s), 7–8, 10–11, 15, 19, 21, 39, 43

L

Labor shortage, 1
Lagrange formulation, 31, 34

M

Manual construction process, 47
Mobile platform, 31, 34–35
Module T&H-bar, 23–24
Multi-DOF manipulator, 23
Musculo-skeletal disorder(s), 23–24, 47, 53

O

Outrigger, 31, 50

P

Panel construction, 1
Press fit, 7

R

Remote-controlled construction robot, 1
Robotized construction process, 47

S

Soffit, [24](#), [47](#)
Stiffness parameter, [7](#)

T

Target dynamics, [7](#)
Telescopic boom, [47](#)

U

Unconstrained case, [7](#)

V

Vacuum pad(s), [23](#), [27–28](#), [37](#),
[40–41](#), [53](#), [55](#)
Vacuum suction device, [53](#), [55](#)
Vehicle rollover(s), [23–24](#)
Virtual-work theory, [31](#)

W

Wired/wireless control, [31](#)
Work-related musculo-skeletal
disorder(s), [47](#), [53](#)