

Index

■ A

- Accelerometers, 74
- Actionable device, 81, 97
- Adafruit's wireless
 - garden tutorial, 15
- Adafruit WiFi Shield, 57–58
- Adafruit XBee Adapter Kit, 62
- Aggregating data
 - calculations, 139–140
 - get_data() method, 138
 - interval driven data, 136–139
 - sensor-driven data, 134–136
 - XBee modules, 137
- Analog sensors, 73–74, 104, 303
- Annotating data
 - Arduino, 107–108
 - data aggregators/data nodes, 106
 - data interpretations
 - code implementation, 131–132
 - database considerations, 132–134
 - data type transformations
 - arithmetic, 117
 - casting, 119
 - database considerations, 122–123
 - floating-point data types, 117–118
 - reading and
 - storing integers, 120–121
 - derived/calculated data
 - code implementation, 123–126
 - database considerations, 126–127
 - INSERT statement, 129–130
 - SELECT statement, 128–129
 - trigger, 127–128
 - unit of measure, 123
 - enumerations, 110
 - Python, 109
 - RTC (*see* Real-time clock (RTC))
- Arduino, data storage
 - nonvolatile memory, 86
 - real-time clock (RTC) modules, 87
 - SD card, 86–88
- Arduino Due
 - advantages, 34
 - Arduino Mega 2560, 35
 - Atmel SAM3X8E ARM Cortex-M3 processor, 34
 - mega footprint factor, 34
- Arduino Ethernet Shield, 53, 55, 236, 241
- Arduino hybrids
 - Intel Galileo Gen 2, 65–66
 - onboard Arduino-compatible processor, 63
 - pcDuino3B, 63–64
- Arduino IDE
 - choosing Arduino board, 46–47
 - description, 45
 - editor and buttons, 45–46
 - serial port, 47–48
- Arduino Leonardo, 33–34
- Arduino Mega 2560
 - ATmega2560 processor, 35
 - RAMPS, 36
 - representation, 35–36
- Arduino. *See also* Arduino IDE; Clones, Arduino boards
 - Adafruit WiFi Shield, 57–58
 - Arduino Ethernet Shield, 53
 - Arduino WiFi Shield, 55
 - Arduino WiFi Shield 101, 54–55
 - complex robotic functions, 30
 - “Hello, World!” project
 - circuit wiring, 48–49
 - compiling and uploading, 51
 - writing sketch, 50–51
 - host, 30
 - jumpers, 31
 - learning resources, 45
 - models
 - Arduino Due, 34–35
 - Arduino Leonardo, 33–34
 - Arduino Mega 2560, 35–36
 - Arduino Yún, 32–33
 - Arduino Zero, 31–32
 - processors and memory configurations, 31

- Arduino (*cont.*)
 - open source hardware prototyping platform, 30
 - project testing, 51–52
 - shields, 31
 - sketches, 30
 - Sparkfun CryptoShield, 58–59
 - Sparkfun MicroSD Shield, 60
 - Sparkfun WiFi Shield: ESP8266, 56–57
 - XBee Modules, 60–62
- Arduino WiFi Shield, 55
- Arduino WiFi Shield 101, 54–55
- Arduino Yún
 - processors, 32
 - Python script, 33
 - representation, 33
 - WiFi and Ethernet networking, 33
- Arduino Zero
 - added memory, 32
 - description, 31
 - memory, 32
 - representation, 32
- Atheros AR9331 processor, 32
- Atmel ATmega32U4 processor, 32
- Atmel SAM3X8E ARM Cortex-M3 processor, 34
- Audio sensors, 75

■ **B**

- Backup/recovery reliability
 - with Binary Log, 262–263
 - database export and import, 260–261
 - data operations, 256
 - Enterprise Backup, 261–262
 - mysqldump client, 257–260
 - MySQL options, 257
 - MySQL Utilities, 260–261
 - Physical File Copy, 262
- Barcode readers, 75
- BeagleBone Black
 - capex, 67
 - hard drive configuration, 226
 - MySQL installation, 226
 - port scanner, 225
 - power connector, 67
 - startup guide, 67
 - USB ports, 225
- Binary log file, 276, 283
- Biometric sensors, 75

■ **C**

- Capacitive sensors, 75
- Clones, Arduino boards
 - description, 36
 - Sparkfun ESP8266 WiFi Module, 42–44
 - Sparkfun Redboard, 36–37

- Spikenzie Labs Prototino, 41–42
- Spikenzie Labs Sippino, 39–41
- TinyDuino, 37–39
- Coin sensors, 75
- Compute Module Development Kit, 198–199
- Computer boards
 - BeagleBone Black board, 67–68
 - characteristics, 66
 - GPIO pins, 66
 - Intel Edison board, 70–72
 - IOT development platforms, 66
 - Raspberry Pi 2 Model B, 68–69
 - Raspberry Pi B model, 69–70
- Computer Module Development Kit, 198–199
- Computer systems, 77, 197
- Connector. *See also* Connector/Arduino database; Connector/Python database
 - programming module, 230
- Connector/Arduino database
 - database-enabled sketch, 234
 - description, 231
 - GPLv2 license, 231
 - include files, 235
 - installation, 232–233
 - intermediate computer/web-based service, 230
 - Library Manager dialog, 232
 - MySQL server, connection, 236–237
 - Preferences dialog, 232–233
 - preliminary setup, 235–236
 - run the query, 237
 - standard Ethernet library, 231
 - test database creation, 234–235
 - testing the sketch, 237–242
- Connector/Python database
 - connect() method, 245
 - Connector/Python online reference manual, 249
 - desktop/laptop platforms installation, 243–244
 - download page, 243–244
 - executing queries and retrieving rows, 246
 - features, 242
 - insertion, data, 247
 - installation check, 245
 - low-cost platforms installation, 244–245
 - MySQL database-enabled applications, 242
 - MySQL-enabled Python script, 247
 - sample data, 248
 - scripts, 242
- Current sensors, 75

■ **D**

- Data aggregator
 - advantages, 91
 - connector, 92
 - local-storage, 92
 - XBee, 91

- Data collectors
 - data nodes, 81
 - node placement, 97
 - with storage, 81
- Data definition language (DDL), 142–143
- Data manipulation
 - language (DML), 142–143
- Data retention policy, 24
- Data sheet, 104, 131
- Data storage, IOT
 - aggregator
 - advantages, 91
 - connector, 92
 - local-storage, 92
 - XBee, 91
 - database server
 - benefits, 93–94
 - code development, 94
 - database design, 95
 - maintenance, data, 96
 - MySQL database, 95
 - physical storage, 95
 - SQL statements, 94
 - timestamp field, 95
 - data flow chart, 98
 - distributed IOT
 - actionable device, 81
 - data aggregators, 81
 - database server node, 82
 - data collectors, 80–81
 - description, 80
 - network nodes, 80
 - local on-device storage
 - Arduino, 85–90
 - Raspberry Pi, 83–85
 - node placement, 96–97
 - presentation, 99
 - sensor data, 97
- Data transformation
 - aggregation (*see* Aggregating data)
 - annotation (*see* Annotating data)
 - Arduino/Python scripts, 101
 - larger-scale operations, 101
 - observation data
 - accuracy, 105
 - filters, 102
 - interpretations, 104
 - lifetime, 105–106
 - record, 103
 - sensor, producing, 104
 - sensor data, 101
 - social media applications, 101
- DDL. *See* Data definition language (DDL)
- Digital sensors, 73–74, 77
- DIY home automation, 10–11
- DML. *See* Data manipulation language (DML)

■ E

- ECDSA. *See* Elliptic Curve Digital Signature Algorithm (ECDSA)
- Elliptic Curve Digital Signature Algorithm (ECDSA), 59
- Encryption functions, 23
- Enumerations, 110, 123, 130

■ F

- Fault tolerance, IOT nodes, 270–271
- Fault-tolerant data collector
 - coding, 302–308
 - design, 301
 - hardware, 301–302
 - testing, 309
- Flex/force sensors, 75

■ G

- Gas sensors, 76
- General-purpose input/output (GPIO) header, 201
- Global transaction identifiers (GTIDs), 276–277
- GPIO. *See* General-purpose input/output (GPIO) header
- GTIDs. *See* Global transaction identifiers (GTIDs)

■ H

- Hardware platforms, IOT, 6
- Highavailability. *See also* Replication
 - backup/recovery reliability (*see* Backup/recovery reliability)
 - engineering principles, 252
 - fault tolerance, 255–256
 - goals for IOT solutions, 252
 - recovery, 253–254
 - redundancy, 254–255
 - scaling, 255
 - synonymous with reliability, 251
 - uptime representation, 251
- High availability IOT nodes
 - fault-tolerant data collector
 - Arduino mega, Ethernet shield, 301
 - coding, 302–308
 - data collector node, 300
 - debug statements, 309
 - design, 301
 - hardware, 301–302
 - moisture sensor, 301
 - requirements, 310
 - RTC module, 302
 - testing sketch, 309

- High availability IOT nodes (*cont.*)
 - redundant data collectors
 - coding, 294–295
 - condition compilation, 294
 - debugging output, 299
 - design, 291–292
 - with failover, 296–298
 - hardware, 292–294
 - setup() code, 294
 - testing sketch, 298–300
 - wire.begin(), 294
- Home Depot solution, 10

■ I, J, K

- Instructable, 11
- Intel Edison board, 70–72
- Intel Galileo
 - hard drive configuration, 229
 - Intel Einstein platform, 227
 - MySQL installation, 228–229
- Intel Galileo Gen 2, 65–66
- Internet of Things (IOT)
 - addressing IOT devices, 16
 - and big data, 19–20
 - Arduino and Raspberry Pi support, 18
 - chirps, 18
 - connected to Internet, 3–5
 - database design and MySQL server
 - coherent names, 192
 - binary data storage, 192
 - data back up, 193
 - data type, 191
 - database design, 193
 - database normalization, 193
 - database server, 192
 - documentation, 193
 - indexes, 191
 - lookup tables, 192
 - primary keys, master tables, 192
 - raw data, 192
 - queries preparation, 192
 - redundant data, 191
 - SELECT, 192
 - wide tables, 192
 - description, 1
 - devices, 2
 - fleet management, 8–9
 - home automation, 10–11
 - IP address, 16
 - IPv6 addresses, 16
 - layered solution, 18
 - lower-resource communication protocols, 17
 - machine-to-machine data exchange, 15
 - MySQL database server, 19
 - plant monitoring, Arduino, 12

- plant soil monitoring, 12–13
- security
 - actionable device, 26–27
 - Arduino-based sensor platform, 21
 - biometric signature (fingerprint), 21
 - communication protocols, 23–24
 - data aggregator, 26–27
 - database server, 26–27
 - data collector, 26–27
 - password policies, 21, 24, 28
 - physical security, 25
 - privacy policies, 24
 - remote maintenance, 24
 - RFID badge, 21
 - services, 26
 - software and firmware, 25
 - the United States Office of Personnel Management, 21
 - sensor networks, 1, 7–8
 - services, 6–7
 - simple plant-monitor, 12
 - soil-monitoring, 13–14
 - XBee modules, 15
- Iris smart hub, 10

■ L

- Light sensors, 12, 75–76
- Liquid-flow sensors, 76
- Liquid-level sensors, 76
- Location sensors, 76
- Lowe's solution, 10
- Low-powered computing platforms
 - Arduino hybrids
 - (*see* Arduino hybrids)
 - computer boards
 - (*see* Computer boards)
 - description, 62
 - Linux operating system, 63

■ M

- Machine-to-machine (M2M) services, 6
- Magnetic-stripe readers, 76
- Magnetometers, 76
- Microcontrollers. *See also* Arduino, microcontroller platform
 - integrated circuit (IC) chips, 29
 - memory and command features, 30
- MySQL commands
 - data addition, 169–170
 - databases and tables, 165–166
 - data changing, 170
 - data removal, 171
 - result set/rows, 166–169
 - SELECT statements, 166–167

- mysqldump client application
 - back up table, 257–258
 - client utility, 259–260
- MySQL replication techniques
 - database maintenance
 - errant transactions, 282
 - slave errors, 282–284
 - starting replication,
 - existing data, 284–285
 - GTIDs, 276–277
 - failover, 280–282
 - switchover, 279–280
 - scaling applications
 - cloud service, 285
 - design, 286
 - get_next_server(), 287
 - LOCK TABLES, 286
 - read scaling server selector, 287–290
 - SHOW SLAVE HOSTS, 286
 - testing sketch, 290
 - transaction processing, 274–276
- MySQL server
 - accounts and roles page, 152–153
 - advanced options panel, 154–155
 - Archive storage engine, 161
 - check requirements page, 147–148
 - commands, 164
 - configuration file, 162–163
 - configuring examples, 156–157
 - COUNT, AVG functions, 175
 - “CREATE PROCEDURE and CREATE FUNCTION Syntax”, 175
 - CSV storage engine, 161
 - data location, 161–162
 - indexes, 171–172
 - installation preparation, 148–149
 - license agreement, 146
 - Linux and Unix systems, 143
 - mysql, client application, 142–143
 - packages installation, 149–150
 - product configuration, 150–151
 - routines, 175
 - server configuration
 - execution, 155–156
 - setup type, 147
 - simple joins, 173–175
 - SQL, DDL and DML, 142
 - start, stop and restart, 163
 - storage engine, 158–160
 - Sun Microsystems, 141
 - triggers, 172–173
 - type and networking page, 151–152
 - Ubuntu Linux, download page, 145
 - users and access, 163–164
 - views, 172

- Windows Installer,
 - download page, 145–146
- Windows Service page, 153–154

N

- New Out Of the Box Software (NOOBS)
 - interfaces, 210
 - localisation, 210
 - network installer and
 - base image, 207
 - performance, 210
 - Raspbian configuration dialog, 210
 - SDFormatter 4.0, 208
 - startup screen, 209
 - system, 210

O

- Operating system
 - boot image installation
 - Linux, 212
 - Mac OS X, 211
 - Windows, 211
 - images, 206–207
 - methods, installation, 207
 - NOOBS (*see* New Out Of the Box Software (NOOBS))
 - occidentals, 207

P, Q

- pcDuino, 226–227
- pcDuino3B board, 63–64
- Plant-monitoring system
 - AUTO_INCREMENT
 - data type, 179
 - data, 177
 - database design, 177–180
 - DATE() and CURRENT_DATE()
 - functions, 181
 - EXPLAIN command, 179
 - ID, soil_status, 189–191
 - queries/questions, 181–185
 - sample data, 185–186
 - schema, 177–178
 - SELECT statement, 183, 184
 - view, 183
 - WHERE clause, 182
- Position replication, 276
- Proximity sensors, 76
- Pulse-width modulation (PWM)
 - output, 33–35, 40–41, 64
- PWM. *See* Pulse-width modulation (PWM) output

R

- Radiation sensors, 76
- Radio frequency identification (RFID), 21, 70, 75
- RAMPS. *See* RepRap Arduino Mega Pololu Shield (RAMPS)
- RaspberryPi. *See also* Operating system
 - Raspberrypi.org organization, 196
 - automatic drive mounting, 218–220
 - boot sequence, 212–213
 - catalog entry, 203
 - Compute Module Development Kit, 198–199
 - configuration menu, 213
 - data storage
 - Python, 83
 - writing data to files, 83–84
 - ext4 file system, 218
 - GPIO header, 201
 - hard disk partitioning, 216–217
 - HDMI port, 200
 - Linux operating systems, 196
 - loss of knowledge and skillsets, 197
 - main page, 196
 - menu items, 214
 - menus, 196
 - microUSB connector, 200
 - MySQL server installation
 - connecting to, 222–223
 - data directory to external drive, 223–225
 - Ethernet port/wireless networking device, 220
 - package manager package headers, 220
 - Raspberry Pi 1 Model B+, 198
 - Raspberry Pi 2 Model B, 198
 - Raspberry Pi 7" Touch Display, 200–201
 - Raspberry Pi Model A+, 198–199
 - recommended accessories, 202–203
 - required accessories, 201–202
 - solid-state drive (SSD), 215
- Raspberry Pi 1 Model B+, 198
- Raspberry Pi 2 Model B, 68–69, 198
- Raspberry Pi B model, 69–70
- Raspberry Pi Model A+, 198–199
- RDBMS. *See* Relational database management system (RDBMS)
- Real-time clock (RTC)
 - code implementation, 112, 114
 - database considerations, 115–116
 - DS1307 chip, 111
 - I2C interface, 111
 - library, 112
 - module, 58
- Redundant data collectors
 - coding, 294–296
 - design, 291

- failover, 296–297
- hardware, 292
- testing, 298–300
- Relational database management system (RDBMS), 144
- Replication
 - binary log and events, 264
 - master preparation, 265–266
 - relay log, 264
 - servers, 264
 - slave, 266–270
- RepRap Arduino Mega Pololu Shield (RAMPS), 36
- Rethinking the Internet of Things*, 17
- RFID. *See* Radio frequency identification (RFID)
- RFID sensors, 75

S

- Sensors
 - accelerometers, 74
 - analog, 73
 - audio sensors, 75
 - barcode readers, 75
 - biometric, 75
 - capacitive, 75
 - coin, 75
 - current, 75
 - description, 72
 - digital, 73–74
 - flex/force, 75
 - gas, 76
 - light, 76
 - liquid-flow, 76
 - liquid-level, 76
 - location, 76
 - magnetic-stripe readers, 76
 - magnetometers, 76
 - proximity, 76
 - radiation, 76
 - RFID sensors, 75
 - speed, 77
 - storage of, 74
 - switches and pushbuttons, 77
 - tilt switches, 77
 - touch, 77
 - video, 77
 - weather, 77
- Smart home, 10, 22
- Smart refrigerator, 3
- Sparkfun CryptoShield, 58–59
- Sparkfun ESP8266 WiFi Module
 - board, 43
 - features, 42
 - WiFi capabilities, 44

Sparkfun MicroSD Shield, 60
 Sparkfun Redboard
 Arduino Uno version, 36
 programming and building circuits, 37
 representation, 36–37
 Sparkfun’s soil moisture tutorial, 14
 Sparkfun WiFi Shield: ESP8266, 56–57
 Sparkfun XBee Explorer USB, 62
 Sparkfun XBee Explorer USB Dongle, 62
 Speed sensors, 77
 Spikenzie Labs
 Prototino
 ATmega328 processor, 41
 board, 42
 permanent installations, 41
 solder pads, 42
 Sippino
 with breadboard headers, 40
 sensor networks, 41
 shield dock, 39–41
 solder-less breadboard, 39
 SQL. *See* Structured Query Language (SQL)
 Structured Query Language (SQL), 142

■ **T, U**

Telematics, 8
 Tilt switches, 77
 TinyDuino

boards/core modules, 38
 main board, 37–38
 modules, 39
 terminal board, 38–39
 Touch sensors, 77
 TPM. *See* Trusted platform module (TPM)
 Transaction processing, 274
 Trusted platform module (TPM), 58

■ **V**

Video sensors, 77

■ **W**

Weather sensors, 77
 Weather Station Network, 8
 Wink app, 10

■ **X, Y, Z**

XBee modules, 91, 137
 and various host boards, 61
 low-cost, low-power
 communication, 60
 sensor nodes, 60
 types, 62