

# Index

## A

Abatement potential, 488  
Abrasion index, 85  
ACARP (Sustainable Technology Australia), 100  
Activated carbons (AcC), 395, 396  
Activated coke method, 121, 122  
Adsorption-enhanced reforming (AER), 540  
Aeration tank, 45  
Agglomerating agents, 315  
Air emissions, 115  
Air separation unit (ASU), 536  
Air travel distance, 526  
Aligned policies, 23  
Alkali-activated fly ash, 314  
Alkaline-binding systems, 313  
Anaerobic degradation, 46  
Anthracite/petroleum coke, 148  
AOPs, 46  
ArcelorMittal plant, 124  
ArcSave stirring, 347–349  
Ash, 311  
Ash-based geopolymer systems, 314  
Atmospheric emissions, 115  
Automotive grade steels, 317  
Auxiliary reducing agents (ARA), 437

## B

Basic oxygen furnace (BOF), 7, 20, 179, 222, 275, 512  
    bottom gas stirring (*see* Bottom gas stirring)  
    by-products reuse, 287  
    capacities, 275

    composition variation  
        melt, 278  
        slag, 277, 278  
    contour censoring, 294, 295  
dust recovery  
    dedusting load, 287  
    electrostatic precipitators, 287  
    RecoDust plant, 288, 289  
    types, 288  
energy consumption, 288  
energy input (*see* Metallized iron usage)  
energy issues, 287–291  
energy saving potential, 289–291  
environmental issues, 279  
exhaust gas analysis, 293  
functions, 275, 276  
gas blowing process, 288  
gas dry dedusting technique, 290, 291  
heat and gas recovery (*see* Energy recovery)  
in-furnace post-combustion, 296, 297  
ladle preheating, 295, 296  
materials flow and emission, 279, 280  
melt composition variation, 277  
off-gas composition, 279  
reactions, 275–277  
route, 14  
slag (*see* BOF slags)  
    steel/slag composition monitoring, 294  
Basic oxygen steelmaking (BOS)  
    process, 277–279  
Baur-Glaessner type diagram, 469  
Bessemer Thomas converter, 275  
Best available techniques, 6  
BF-BOF route, 426, 427  
BF-MIDREX-EAF process, 426

- Biochar, 156–158
- Biological treatment method, 45
- Biomass, 31, 32
  - coke making, 99–103
  - combustion
    - BF injection, 225
    - biofuel production technologies, 227
    - bioreducers, 223, 231
    - Brazilian plants, 226
    - charcoal chemistry, 223
    - CO<sub>2</sub> emissions, 223
    - coke and coal, 223
    - emission taxes, 230
    - flame temperature, 229
    - hard carbons, 227
    - HTC, 226
    - isotropic disordered material, 230
    - lignin, 226
    - morphology, 230
    - optimized carbonization, 231
    - price, 229
    - pulverized coal, 223
    - pyrolysis concept, 230
    - steelmaking process, 227
    - TP and WP, 228
    - tuyeres constant, 229
    - wood-based biomass, 224
    - wood-based materials, 225
  - in sintering
    - activated carbon/lignite, 158
    - biochar, 156–158
    - cellulignin coal, 155
    - characterization techniques, 154
    - clean energy, 153
    - coke breeze fuel, 158
    - combustion efficiency, 154
    - corus, 153
    - CSIRO, 155, 156
    - environment impacts, 158, 159
    - ESP, 158
    - flame front speed, 155, 156
    - gas flow simulations, 155
    - hydrocarbons, 154
    - material types, 154
    - metallurgical properties, 156
    - micropores, 154
    - operation data, 158
    - reaction surfaces, 155
    - silica, 154
    - small-scale sinter pot experiments, 154
    - solid fuels properties, 153
    - SOx emission, 154
    - Tumble index, 155, 156
- Bioreducers, 223
- Blast furnace gas (BFG), 146–148, 155, 461, 503, 505, 534
- Blast furnaces (BFs), 7, 14, 27, 39, 52, 53, 55, 57, 61, 64, 66, 84, 86, 87, 89, 95, 99–101, 111, 499
  - air flow, 167
  - air moisture, 173
  - BF-BOF steelmaking system, 179
  - burden and reduction reaction, 191
  - carbon, 171
  - carbon dioxide emission, 173
  - CFD-DEM model, 199
  - CO<sub>2</sub>
    - abatement, 170
    - emissions, 170, 178
    - intensity, 169
    - potential reduction, 169
  - COG, 178
  - coke
    - and iron-bearing materials, 179
    - reduction, 181
  - concepts, 172
  - conceptual system, 168
  - conventional blast furnace, 178
  - EMF, 194
  - energy consumer, 167
  - energy-efficient technologies, 168
  - equilibrium reduction reactions, 174
  - gas-phase equilibrium composition, 175
  - gas recycling, 170, 172
  - gas scrubbing, 168
  - GHG, 168
  - H<sub>2</sub> and CO, 173
  - hematite, 175
  - hot waste gases, 167
  - hydrogen, 175
  - industrial process, 175
  - instrumentation, 194
  - iron ore, 167
  - iron oxides, 167
  - legal requirements, 199
  - mathematical simulation, 173
  - online tools, 199
  - optimized scheduling, 201
  - oxygen blast furnace, 172
  - oxygen enrichment, 178
  - oxygen gas volume, 170
  - parameters, 194
  - PCI, 173
  - performances, 179, 181
  - process control, 194
  - pulverized coal, 172

- reactor, 196
  - reduction, 173
  - secondary emissions, 200
  - size, 169
  - small-scale steel production, 169
  - steel production, 176
  - techniques, 194
  - temperature curves, 174
  - tuyeres level, 197
  - WTCR, 191
  - wüstite reduction, 176
  - Blast furnace with CCS (BF-CCS), 463
  - BLUE scenario, 24, 25
  - BOF slags
    - applications, 286, 287
    - cement clinker manufacturing process, 286
    - CRW, 286
    - CW-EDI, 286
    - holding time, 291
    - magnetic spinel phases, 291
    - oxidation behavior, 291
    - properties, 285
    - sensible heat recovery, 284, 285
  - BOF steelmaking, 311
  - Bottom gas stirring
    - bottom-blowing intensity, 293
    - dephosphorization mechanism, 292
    - differential flow, 293
    - inert gas injection, 292
    - mass transfer, 293
    - nitrogen, 291
    - oxidation volume, 293
    - phosphorous removal, 293
  - Bottom stirring
    - carbon content, 349
    - characteristics, 350
    - in EAF, 346
    - efficiency, 350
    - electromagnetic force, 350
    - EMS stirring, 347
    - gas, 291
    - inert gas, 346
    - new EAF process development, 347
    - practice, 346
    - reduced electrode current swings, 347
  - Bottom-up energy system models, 462
  - Breakthrough technologies, 22, 28, 29, 31, 32
  - Briquettes, 101
  - Burning waste plastic, 499
  - Burn-through point (BTP), 133
  - Business model, 17
- C**
- Ca-based sorbents, 545
  - Ca-based WFGD system, 60
  - Calcium-enriched system, 313
  - Calorific value (CV), 58, 281
  - Capture processes, 536
  - Carbon, 28, 307
  - Carbonation, 316
  - Carbon capture and sequestration, 533
  - Carbon capture and storage (CCS), 22, 23, 25, 27, 31, 432, 462, 479, 488–491
    - BF-BOF process, 498
    - biomass, 493
    - blast furnaces, 499, 501
    - and CCU, 490
    - chemical composition, 497
    - in China, 487
    - CO<sub>2</sub>
      - capture, 488, 495
      - emissions, 486–488, 490
    - Dutch greenhouse, 493
    - energy efficiency potential, 496
    - EOR, 493
    - in Europe, 497
    - gas treatment, 489
    - global emissions, 486
    - IEA statistics, 496
    - iron and steel industry, 497
    - manufacturing plants, 485
    - methanation, 492
    - mini steel mills, 491
    - mitigation options, 490
    - natural gas, 501
    - and oxygen atoms, 491
    - recycling, 501
    - RUREH, 486
    - sintering process, 499
  - Carbon capture and usage (CCU), 5
  - Carbon capture technologies, 491
  - Carbon capture use and storage (CCUS), 6
  - Carbon dioxide (CO<sub>2</sub>) emissions, 309, 310
  - Carbon direct avoidance (CDA), 5
  - Carbonization
    - air contactor, 524
    - BF, 521
    - chemical loops, 523
    - coking industry, 531
    - COREX process, 521
    - designers, 526
    - emission sources ranges, 532
    - iron and steel mill, 532
    - liquid distribution, 526
    - outdoor contractor, 526

- Carbonization (*cont.*)
  - prototype module, 526
  - storage capacity, 521
  - TGRBF, 533
- Carbon membranes, 516
- Cellulignin coal, 155
- Chamber walls, 82
- Charcoal, 99, 100, 422
  - markets, 183
  - in sintering
    - application, 151
    - biomass fuel, 149
    - characteristics, JSM sinter blend, 152
    - charred plant carbon structures, 149
    - CO and CO<sub>2</sub> concentrations, 149, 150
    - coke breeze, 148
    - combustion behavior, 149
    - emission mechanisms, 153
    - energy-efficient and nonpolluting, 148
    - experimental results, 151
    - fuel rate, 152
    - gaseous fuel injection technology, 152
    - green granules, 152
    - higher volatile matter content, 151
    - iron ore, 149
    - JFE Steel Corporation, 152
    - lower fixed carbon content, 151
    - matching, 148
    - PCDD/Fs, 148–151
    - POPs, 148
    - portion replacement, 152
    - properties, 149
    - replacement of coke, 150
    - SO<sub>2</sub> emissions reduction effect, 149
    - temperature zone, 152
    - toxic organic pollutants, 150
- Charging carbon composite agglomerates (CCA)
  - BF production, 233
  - biomass-iron oxide composites, 237
  - FeO-Fe, 232
  - fine iron ores, 232
  - gas generation rate, 235
  - gas utilization ratio, 239
  - HCMB, 233
  - hot briquetting process, 233
  - ICHB, 240
  - nonvolatile carbon, 237
  - reaction model/ratios, 234
  - wüstite and metallic iron, 234
- Chemical-looping combustion (CLC), 78
- Chemical-looping cycles
  - advantage, 538
  - CaCO<sub>3</sub>, 538
  - CaL, 539, 543
  - carbonator, 539, 541
  - CO<sub>2</sub>-lean gas, 541
  - CO<sub>2</sub>/oxygen, 538
  - coal consumption, 543
  - decarbonization concept, 545
  - DFB biomass, 540
  - investment costs, 544
  - O<sub>2</sub>/CO<sub>2</sub> atmosphere, 540
  - parameters, 541
  - regenerator, 539, 540
  - steam production, 541, 543
  - steel production, 544
  - VPSA, 543, 544
- Chemical-looping hydrogen (CLH), 538
- Chemical/physical adsorption
  - blast furnace gas, 504
  - carbon monoxide, 508
  - CoMo catalyst, 504
  - crude syngas, 508
  - equilibrium, 505
  - MEA scrubber system, 504
  - NH<sub>3</sub> and CO<sub>2</sub>, 505
  - power plant and ironmaking plant, 505
  - Rich MEA stream, 504
  - sodium and potassium carbonates, 505
  - solvents, 503
  - temperature and pressure, 503
  - urea synthesis, 508
- Circofer®, 494
- CIRCORED, 452, 453
- Circular economy, 6, 7
- Circulating fluidized bed (CFB), 452
- Cleaner technology, 117
- Climate change, 4, 13
- Clinker-like agglomerate, 115
- CO<sub>2</sub>
  - BFs, 100
  - chemical-looping hydrogen process, 66
  - coal gasification process, 68
  - emissions, 39, 55, 80, 99, 104
  - hydration reaction, 517
  - mitigation and H/C ratio, 67
  - price set, 22
  - reforming, 65, 70
  - utilization, 77
- Coal-based DR processes, 422
- Coal-based HYL technology, 432
- Coal cake, 83
- Coal-direct chemical-looping process (CDCL), 538
- Coal fly ash, 315

- Coal gasification, 378, 402
- Coal gas production, 357
- Coal market of Europe, 39, 41
- Coal moisture control process (CMCP), 87, 88, 103
- Coal stamp charging battery (CSCB)
  - accommodation, particles, 82
  - blend quality and process control, 85
  - bulk density, 86
  - CDQ facility, 86
  - coal
    - blends, 84
    - cake, 83
    - making, 84
    - production, 83
    - quality, 82, 84, 86
  - compressive strength, 85
  - densification, 82
  - density, 84, 86
  - dimensions, 83
  - dry bulk density, 86
  - elastic-plastic deformation, 83, 84
  - heat recovery ovens, 83
  - heat recovery stamp-charged coke making technology, 85
  - mechanical properties, 82, 84
  - mechanical strength, 84
  - operational efficiency, 85
  - parameters, 86
  - pre-carbonization technologies, 83
  - preparation, 82, 83
  - temperature, crude COG, 85
  - wet agglomerate, 84
  - wet bulk density, 86
- Coal-tar pitch, 101
- CO<sub>2</sub> capture by slag carbonization (CCSC), 56
- CO<sub>2</sub> emissions, 117
  - Chinese iron and steel industry, 13
  - economic measures, 28
  - vs. energy consumption, 12
  - engaging, 16
  - factor, 20
  - global warming, 21, 22
  - levels, 20
  - steel, 13
  - steel mill, 16, 18
- COG chemical-looping hydrogen- assisted
  - COG-to-natural gas (CGCLH-CGtNG), 66
- Coherent, 309
- Coke breeze, 112, 114, 140
- Coke consumption, 499, 527
- Coke cooler, 52
- Coke dry quenching (CDQ), 498
  - advantages, 52, 55
  - application, 55
  - ash content, 54
  - carbon flow analyses, 56
  - CO<sub>2</sub> emissions, 55
  - coke cooler, 52
  - coke losses, 53, 54
  - communication tool, 52
  - cooled coke temperature, 56
  - CSQ, 55
  - CWQ, 50, 51
  - DDQ, 57
  - development of designs, 54
  - dry-quenching unit (*see* Dry-quenching unit)
  - dust emissions, 52, 55
  - energy/exergy analysis, 50, 51
  - energy recoveries, 50, 57, 58
  - energy-saving technology, 53
  - gas emissions, 54
  - gas volume, 57
  - heat exchange, 52
  - injection, 52
  - lower moisture content, 52
  - operating conditions, 54
  - plant, 52, 53
  - pollutant emissions, 53
  - prechamber flare, 54
  - quality indexes, 55, 56
  - reduce air pollution, 50
  - SDQ, 57
  - single-chamber, 55
  - SO<sub>2</sub> emissions, 55
  - steam generation, 56
  - in steelmaking industry, 52
  - strength and size distribution, 50
  - temperature, 50
  - thermal energy, 51, 53
  - thermodynamic analysis, 51, 52
  - uniform quenching, 57
  - usable exergy, 51
- Coke making, 311
  - biomass, 99–103
  - carbon porous material, 39
  - CDQ (*see* Coke dry quenching (CDQ))
  - CMCP, 87, 88
  - coal market of Europe, 39, 41
  - COG (*see* Coke oven gas (COG))
  - control systems, 79–82
  - CSCB (*see* Coal stamp charging battery (CSCB))
  - CSQ, 95, 96

- Coke making (*cont.*)
- dust and SO<sub>2</sub> emissions, 39
  - emissions reduction and energy efficiency, 104
  - environmental pressure, 39
  - GHG and CO<sub>2</sub> emissions, 39
  - heating time, 39
  - HPALA, 87
  - materials flow and emission sources, 40, 42
  - non-recovery coke ovens (*see* Non-recovery coke ovens)
  - SCOPE21, 97–99
  - SCS, 96, 97
  - temperature monitoring, 80, 81
  - thermal and physical role, 39
  - waste materials, 99–103
  - wastewater treatment (*see* Wastewater treatment)
  - world production, 39, 40
- Coke oven gas (COG), 178, 426, 461, 527
- activated carbon and Ni/Al<sub>2</sub>O<sub>3</sub> catalysts, 71
  - advantages, 61, 68, 70, 72
  - application, 72
  - BCFNO membranes, 73
  - BF, 202
  - and blast furnace, 57, 205
  - by-product, coal carbonization, 57
  - caloric value, 60
  - catalysts, 61
  - catalytic method, 72
  - CGtNG, 66
  - chemical reagents, 60
  - in China's coke industry, 76
  - CLC, 78
  - CO<sub>2</sub>
    - adsorption technology, 79
    - emissions, 207
    - MES system, emissions reduction, 79, 80
  - coal char catalyst, 65
  - coal gasification reactions, 68
  - cohesive zone and permeability, 205
  - COI12 case, 205
  - coke powder, 207
  - composition, 58, 59
  - and CTM processes, 76, 77
  - CWHS, 74
    - carbon balance, 74, 75
    - energy balance, 74, 76
  - CWOHS
    - carbon balance, 74, 75
    - energy balance, 74, 76
  - deactivation rate of catalyst, 64
  - desulfurized, 68
  - direct and indirect emissions, 77
  - disadvantages, 64, 68, 70
  - DMR, 68, 74
  - dry reforming, 69–71
  - electricity emission factor, 78
  - elevated cost, 73
  - energy
    - balance, 58, 59
    - consumption, 204
    - saving in steelmaking, 58
    - utilization, 206
  - EUD methodology, 79
  - exothermic process, 72
  - FT synthesis, 71
  - GaCTO, 67–69
  - gasification processes, 79
  - gas injection, 202
  - gas-phase oxidizers, 60
  - gas recycling optimization
    - operations, 204
  - gas utilization, 204
  - GHG generation, 77
  - global sensitivity analysis, 77
  - greenhouse gases, 70
  - H<sub>2</sub>/CO ratio, 71
  - H<sub>2</sub>S, 71
  - HECA facility process, 77, 78
  - hierarchical attribution management, 77
  - hot COG, 60
  - hydrogen separation, 68, 69
  - IGAR, 207
  - inner furnace status, 205
  - integrated COG-DRI plant, 66
  - IR, 64
  - iron-molybdenum hydrodesulfurization
    - technology, 74
  - isothermal reduction, 203
  - LTIR, 204
  - mechanism, NO<sub>x</sub> removal, 60
  - membrane reactors, 73
  - methanol production, 65, 66
  - methanol steam, 74
  - MPO, 74
  - multifunctional energy system, 79
  - nitrogen-free blast furnace, 206
  - non-catalytic method, 72
  - O<sub>2</sub>/CH<sub>4</sub> ratio, 73
  - onsite use/separate sale, 64, 65
  - optimal utilization, 79
  - oxygen carrier, 78
  - ozone generation, 60
  - partial oxidation of methane, 71, 72

- performances, different CTM processes, 74, 77
- production ratios
  - annual H<sub>2</sub> production, 64, 65
  - COG vs. coke, 64, 65
  - coke vs. coal, 64, 65
  - H<sub>2</sub> vs. COG, 64, 65
- properties, 58
- proposed MES system, 79
- PSA, 64, 65
- pseudo-catalyst, 73
- quantitative conversions, 73
- reforming processes, 69
- RWGS, 71
- RWGS+SR pathway, 71
- SCR, 58
- sensitivity analysis, 66
- sinter, 202
- SMR, 74
- space velocity, 73
- SPARG, 71
- SR, 63
- steam reforming
  - hot COG, 64
  - methane, 63, 64
- superiorities, 60
- synergetic effect, 71
- syngas production, 69
- synthesis gas (syngas), 63
- technologies, 58, 68, 70
- TI and SI, 205
- top gas recycling, 207
- TRM, 75
- types of catalysts, 71, 72
- utilization, 61–63
- valorization, 73
- VSD compressors, 95
- WFGD, 58, 60
- Coke oven gas (COG)-to-natural gas (CGtNG), 66
- Coke quality, 497, 498
- Coke stabilization quenching (CSQ), 55, 95, 96
- Coke strength after reaction (CSR), 86, 90, 92, 94, 101, 102
- Coke wastewater (CWW) treatment plant, 49
- Coke wet quenching (CWQ), 50, 51
- Cold DRI, 433, 434
- Cold rolling wastewater (CRW), 286
- Combined cycle power plant (CCPP), 56
- Combustion gases, 115
- Combustion/non-combustion processes, 282
- Commonwealth of Independent States (CIS), 446
- Composite burnout potential (CBP), 182
- Computer control technologies, 159
- Concentrated water from electro-deionization (CW-EDI), 286
- Consteel, 306, 329, 330, 344
- Contiarc furnace, 360, 366
- Convection, 307
- Convective heat transfer, 307
- Conventional BF ironmaking system, 400
- Conventional burners, 134
- Conventional ignition system, 145–147
- Cooled coke temperature, 56
- Cooling and extra reduction reactor, 468
- Copper, 322
- Corex, 381, 383, 398, 421, 533
  - AcC, 395, 396
  - adsorbent and desulfurizer, 396
  - Bauer-Glaessner diagram, 383, 384
  - chemical reactions, 397
  - CO<sub>2</sub> direct emission analysis, 389
  - coal consumption, 388
  - coal gas, 394
  - coke oven, BF and COREX gases, 400
  - conventional BF process, 398
  - COREX<sup>®</sup> shaft furnace export gas, 392
  - degree of metallization, 388
  - description, 381
  - desulfurizers, 398, 399
  - downstream CO<sub>2</sub> emission, 389
  - dry desulfurization, 399
  - EAFs and BOFs, 386
  - exergy analysis, 388
  - gas, 510
  - generator gas composition, 388, 390
  - hydrogen reduction, 383
  - material consumption and CO<sub>2</sub> emissions, 400, 401
  - melter-gasifier, 381, 384–387
  - metal and slag composition, 388, 390
  - metallization degree, 394
  - and Midrex, 393
  - oxidation, 397
  - oxygen, 386
  - phthalocyanine metal complexes, 395
  - proportion of H<sub>2</sub>, 393
  - reactions, 382
  - shaft furnace, 385
  - Si and P contents, 392
  - thermodynamic model, 388, 389
  - top gas composition, 388, 390
  - two-stage direct smelting process, 381

- Corus, 153
- Costs
- coke, 56
  - collection and treatment of material, 100
  - excessive energy, 81
  - investment, 74
  - low, 48
  - maintenance, 87
  - methanol production, 66
  - NOx control, 60
  - plant, 90, 98
- COURSE 50, 240, 241, 243
- CRI, 90, 101, 102
- Cryogenics separation
- CO<sub>2</sub> capture, 520
  - concept, 518
  - experimental setup, 520
  - flue gases, 518
  - gas-liquid separation, 518
  - high temperature, 518
  - LNG, 521
  - refrigerator, 520
- CSIRO, 155, 156
- CTM processes, 76, 77
- Curtain flame burner, 134
- Curtain flame ignition system, 145–147
- CWHS, 74–76
- CWOHS, 74–76
- D**
- Decarbonization technologies, 548
- Deflector plate type feeder, 139
- Dephosphorization mechanism, 292
- Desulfurizer, 395, 396, 399
- Diffusion-controlled mechanism, 456
- Diffusion melting, 307
- Digital control system, 133
- Dioxins, 115–117, 121, 124, 125, 127, 130, 136, 137, 142, 144, 146, 148, 153, 158
- Direct current (DC) arc furnace, 351
- Direct emissions reduction, 24, 25
- Direct reduced iron (DRI), 27, 28
- agglomerates, 420
  - annual production scale, 420
  - BF, 424
  - charcoal, 422
  - CIRCORED, 452, 453
  - classification, 422, 424
  - vs. coal-based system, 422, 423
  - coal volatile matter, 422
  - CO<sub>2</sub> emissions, 422
  - density and shape, 419
  - EAF, 15, 419
  - energy consumption, 420, 424
  - FASTMELT, 440, 441
  - FASTMET, 440, 441
  - feedstocks, reactors and agents, 419
  - FINMET process, 450
  - gasified coal, 419
  - global warming, 422
  - greenhouse emissions and energy consumption, 419
  - Hyl-energiron process (*see* Hyl-energiron process)
  - iron carbide process, 450–452
  - and iron ore resources, 420, 421
  - ITmk3<sup>®</sup> process, 441, 442
  - metallization, 317
  - Midrex<sup>®</sup> process (*see* Midrex<sup>®</sup> process)
  - MXCOAL<sup>™</sup> process (*see* MXCOAL<sup>™</sup> process)
  - on natural gas, 419, 421, 422
  - plants, 419
  - porosity, 419
  - processing conditions, 422, 423
  - production, 422
  - Redsmelt, 452, 454, 455
  - rotary hearth processes, 421
  - scrap, 419
  - shaft furnace, 420
  - SL/RN process, 448, 449
  - smelting reduction processes, 421
  - types, 420, 421
  - volume capacity, 420
  - waste heat recovery, 449
- Dissolving, 307
- Dolomite, 159
- Double dry quenching (DDQ), 57
- Drop tube furnace (DTF) data, 182
- Dry bulk density, 86
- Dry granulation, 285, 335
- Dry methane reforming (DMR), 67, 68, 74
- Dry-quenching unit
- blast fan, 53
  - CO emissions, 53
  - coke losses, 54
  - design and operation, 53
  - excess gases emitted, 54
  - gas channel, 54
  - gas emissions, 54
  - operational efficiency, 54
  - utilization, 54
- Dry slag granulation (DSG), 260



- Dry-type top gas cleaning and recovery (DTCR), 191
- Dust, 311
  - emission, 117
  - recovery and recycling, 287
- Dynamic hydrogen electrode (DHE), 569
  
- E**
- EAFD treatment technologies, 311, 312
- EBT opening frequency, 348
- ECOARC, 329, 342, 343
- Economic analysis, 533
- Electric arc furnace (EAF), 419, 446
  - advantages and disadvantages, 306
  - bottom stirring/stirring gas injection (*see* Bottom stirring)
  - burners, 323, 324, 326
  - carbon, 311
  - cations, 313
  - Consteel, 345, 359
  - cost and quality competitive, 303, 309
  - DC arc furnace, 351
  - dioxins, emissions, 329
  - direct and indirect GHG emission factors, 367
  - disposal, EAF dust, 311
  - electricity consumption, 318
    - with EMS, 348
  - energy efficiency, 305, 317, 366
  - energy-intensive process, 322
  - energy issues, 342
  - GHG reduction, 305, 367
  - iEAF system, 368
  - indirect CO<sub>2</sub> emissions, 303
  - LIBS, 328
  - major technology developments, 310
  - modern electrical energy consumption, 304
  - modern steelmaking, 307
  - molten pool, 350
  - online LIBS measurement, 328
  - oxyfuel burners (*see* Oxyfuel burners)
  - pilot flame, 308, 309
  - post-combustion, EAF flue gas, 364
  - power consumption, 303, 309
  - process optimization and control, 365–367
  - raw materials
    - carbon steel quality, 317
    - classification, 317
    - DRI, 317, 319, 320
    - secondary material, 322
  - route, 14
  - scrap charging, 308
  - scrap melting, 307
  - scrap recycling process, 303
  - shaft furnace (*see* Shaft furnace)
  - social wastes, 303
  - S/S, 313
  - stages, 304
  - steelmakers, 316, 324
  - steelmaking, 324
  - tapping temperature, 305
  - theoretical minimum energy requirements, 309, 310
  - tunnel furnace preheating, 344–345
  - twin-shell, 361–364
  - WHR approach (*see* Waste heat recovery (WHR))
- Electric arc-melting process, 329
- Electric energy consumption, 364
- Electric furnaces, 303
- Electricity, 303, 305, 317, 319, 320, 324, 329, 340
- Electric power production, 89
- Electric smelting, 379, 380
- Electric steel production, 305
- Electrolysis
  - aluminum/lithium, 555
  - electrowinning process, 555
  - energy consumption, 556
  - iron ore, 555
  - MOE, 555
  - production, 556
  - reducing agent, 555
  - ULCOWIN, 556
  - zero-carbon, 556, 574
- Electromagnetic force, 350
- Electromagnetic stirring, 346, 347
- Electrostatic precipitator (ESP), 158
  - vs.* alkali input, 123, 124
  - capture PCDD/Fs, 124
  - capturing efficiency, 123
  - chlorine, 123
  - configurations and types, 123
  - and cyclone, 130
  - data, 124, 125
  - dedusting stage, 117
  - dust emission, 121
  - efficiency, 123
  - maximal dedusting efficiency, 123
  - solid-phase PCDD/Fs, 131
  - waste gases, 121
  - and WS, 131
- Electrostatic space cleaner super (ESCS), 123

- Electrowinning
    - anode potential, 571
    - crystal orientation of  $\alpha$ -Fe, 570
    - current density, 573
    - efficient iron production, 570
    - electrochemical reduction, 574
    - extraction technique, 567
    - faradaic yield, 568
    - Fe fraction vs.  $\text{Fe}_3\text{O}_4$  density, 566, 567
    - goethite reduction, 573
    - $\text{H}_2$  evolution, 568, 569
    - iron electrochemical reactivity, 572
    - iron electrodeposited, 570, 571
    - morphology changes, 569
    - $\text{NaOH-H}_2\text{O}$  system, 569, 570
    - principle of iron, 568
    - reduction of dissolved metal cations, 566
    - slag composition, 572
    - ULCOWIN steelmaking route, 571
  - Emerging technologies, 170
  - Emissions optimized sintering (EOS), 136, 137
  - Emissions reduction, 136, 138, 159–161
  - Encapsulation, 314
  - End-of-life (EoL), 6
  - Endothermic, 462
  - Energiron HYL technology, 432
  - Energy consumption, 420
  - Energy efficiency, 485
    - CCS, 23
    - $\text{CO}_2$  emissions, 20, 27
    - cost, 6
    - energy consumption, 26
    - methods, 21
    - vs. raw material, 7
    - short- to medium-term approach, 24
    - steel production, 10
    - utilization, by-product gases, 11
  - Energy-intensive industry (EII), 1
  - Energy optimized sintering process, 142
  - Energy penalty, 531
  - Energy recovery
    - CO concentration, 282
    - combustion/non-combustion
      - processes, 282
      - gas composition, 282
    - open/closed hood vessels, 281, 282
    - open combustion systems, 284
    - suppressed combustion systems, 284
  - Energy saving, 349
  - Energy Transition Commission, 547
  - Enhanced oil recovery (EOR), 31
  - Environmental management system (EMSy), 8
  - EN 12457 test, 315
  - EPOSINT process, 137, 138, 160
  - ETC, 5
  - EUD methodology, 79
  - European blast furnaces, 198
  - European Commission (EC), 1
  - Excess oxygen, 470
  - Exergy of waste heat recovery (EWHR), 121
  - Exhaust gas treatment
    - acid gases, 127
    - activated carbon
      - adsorption of PCDD/Fs, 126
      - adsorption performance, 124, 126
      - dioxin, 124
      - and MWCNTs, 127
      - PCDD/Fs adsorption efficiency, 127
      - PCDDs and PCDFs, 125
      - RAC, 127, 128
    - activated coal, 124
    - activated coke method, 121, 122
    - additive injection and bag filter dedusting, 127, 129
    - adsorb and recover  $\text{SO}_x$ , 121
    - characteristics of activated carbon, 130
    - desulfurization reagents, 129
    - electrostatic field, 123
    - ESCS, 123
    - ESP, 121, 123–125
    - hazardous organic pollutants, 127
    - heavy metals, 127
    - low-temperature plasma, 127, 129
    - MEEP, 123
    - MSFB, 130
    - PCDDs and PCDFs, 131
    - PM, 130
    - selective catalytic reduction, 121, 122, 124
    - system efficiency, 123
    - wet configuration, 123
    - wet fine scrubbers, 130
  - Exothermic process, 72
- F**
- Faradaic efficiency, 562
  - FASTMELT process, 440, 441
  - FASTMET process, 440, 441
  - Feasibility studies, 28
  - Fenton and EF-Feox methods, 48
  - FeO surface, 431
  - FGRS, 143
  - Fifth hole, 434
  - Final reduction reactor, 468
  - Final sinter temperature (FST), 121

- FINEX, 402, 421  
balance data, 405  
BF and FINEX integration, 404  
and blast furnace, 405  
description, 402  
dried ores, 403  
export gas, 402  
fluidized bed chemical reactions, 403  
fuel consumption and savings, 405, 406  
LRI and reduced gas, 404  
plant, 403
- Finger Shaft EAF, 343
- FINMET, 450, 494
- Fischer–Tropsch (FT) synthesis, 71
- Flash ironmaking technology, 412
- Flat flame burners, 134
- Flue gas recirculation (FGR), 119, 142, 144, 145
- Fluidized bed, 379–381, 385, 402, 412, 413
- Fly ash-based geopolymerization systems, 314
- Foamy slag  
basicity, 332  
carbonaceous compounds, 333  
chemical energy, 332  
CO gas, production, 332  
components, EAF slag, 333  
control, 333  
EAF, 343  
economic practice, 332  
energy-generating reactions, 332  
energy recovery, 334  
granules, 335  
heat recovery, 334  
ironmaking and steelmaking practices, 333  
promotion, 332  
thermal conductivity, 334  
thermal efficiency, EAF, 334  
thermodynamic predictions, 336
- Food and Agriculture Organization of the United Nations, 183
- Fossil media, 455
- Free space post-combustion, 323, 325
- Fresh water consumption (FWC), 40
- Fuel arc furnace (FAF), 341
- Fuel composition, 226
- Fuel rate, 153
- Fuel reductions, 117
- Fugitive emissions, 115
- Furans, 116, 124, 130, 137, 153, 158
- Furnace conditions, 213
- Furnace gas, 215
- G**
- Gangue, 311
- Gas-assisted coal to olefins (GaCTO), 67–69
- Gas-based DRI processes, 433
- Gaseous fuel injection technology, 152
- Gas flow rates, 119
- Gas-phase equilibrium, 177
- Gas recycling process, 186
- Gas separation, 516
- Gas-solid interphase, 521
- Genetic algorithm (GA), 121
- Geopolymerization, 313
- Geopolymers, 313, 314
- Global Carbon Capture and Storage Initiative (GCCSI), 547
- Global sensitivity analysis, 77
- Global warming, 13, 19, 21, 29, 33, 422
- Goethite reduction, 573
- Granulated into small particles (GBFS), 254
- Graphite, 434
- Greenhouse gas (GHG), 39, 57, 63, 68, 70, 77, 309
- Greenhouse gas emission (GHG), 146, 221  
breakthrough technologies, 28  
CCS, 19  
climate change, 4  
data, 21  
impacts, 9  
ironmaking and steelmaking sector, 9  
pathways, 19, 26  
UNFCCC, 16
- Greenhouse gas regulations, 309
- H**
- Hall-Heroult cell technology, 559, 563
- Heat balance, 186
- Heat recovery, 159  
coke making, 89  
ovens, 83  
stamp-charged coke making technology, 85
- Heating value of mixture (HVM), 223
- Heat-resistant diagnostic system, 82
- Heavy metal emissions, 117
- H<sub>2</sub> economy, 458
- High-carbon DRI, 435
- High-carbon metallic briquettes (HCMB), 233
- High-pressure ammonia liquor aspiration system (HPALA), 87
- High-temperature operation, 546
- HIIsarna, 471
- HIsmelt<sup>®</sup>, 378, 379, 406–408
- Holistic ironmaking optimization, 7

- Hot blast temperature
  - BF operation, 201
  - COG, 201
- Hot briquetted iron (HBI), 422, 424, 435, 446, 447, 461, 478, 479, 501
- Hot rolled coil (HRC), 512
- Hot stove process control
  - combustion process control, 193
  - dome temperature, 193
  - energy saving, 191
  - gas consumption, 193
  - production situation, 193
  - Siemens VAI control system, 193
- Hüttenwerke Krupp Mannesmann GmbH (HKM), 132
- Hydrocarbons, 184, 322
- Hydrogen, 31
  - economy, 462, 477
  - iron ore reduction technology, 241
  - separation, 527
  - and synthesis gas, 204
- Hydrogen direct reduction (H-DRI), 463
- Hydrogen Energy California (HECA) facility process, 77, 78
- Hydrogen reduction, 246
  - Baur-Glaessner type diagram, 469
  - BFG, 461
  - biogas, 462
  - biomass, 462
  - bottom-up energy system models, 462
  - carbon-based reductant, 452
  - chemical potentials, 456
  - CO<sub>2</sub> emissions, 452, 455, 458, 471, 475
  - COG, 461
  - coke-less processes, 471
  - coke-using processes, 471
  - cooling and carburizing process, 468
  - cooling and extra reduction reactor, 468
  - DAV, 471
  - decarbonization costs, 463
  - diffusion-controlled mechanism, 456
  - DRI, 458, 459
  - dynamic control, 456
  - EAF steelmaking practice, 461
  - economy development, 461
  - electrolysis cell, 468
  - electrolysis module parameters, 476, 477
  - endothermic, 462
  - end-to-end TGNs and TFNs, 471, 475
  - energy and emissions comparison, 467
  - energy balance, 456, 457
  - excess oxygen, 470
  - ferrous metallurgy, 455
  - flowsheet, 472, 476
  - fossil media, 455
  - and fuel cells, 462
  - H<sub>2</sub>/H<sub>2</sub>-CO mixtures, 458
  - high temperature, 456
  - Hisarna, 471
  - hydrogen economy, 462, 477
  - HYL technology, 468
  - IEA, 458
  - IJmuiden, 477
  - industrial sector, 463
  - innovative routes, 463
  - input-output description, 456
  - kinetic models, 457
  - kinetics analysis, 462
  - Midrex H<sub>2</sub> process, 460
  - Midrex process, 458–460
  - natural gas-based plant, 458
  - plasma hydrogen, 463
  - power-to-gas solutions, 474
  - production costs, 463, 466
  - ranking
    - TFN, 471, 475
    - TFN + TGN, 471, 475
    - TGN, 471, 475
  - renewable electricity, 477
  - renewable energy-powered water electrolysis, 477
  - renewable power integration, 466
  - sponge iron, 468, 469
  - steel industry global energy demand and emissions, 466, 467
  - techno-economic parameters, 463–465
  - TFN: EAF operating, 471
  - TGN and TFN, 471–475
  - three-zone model, 457
  - thyssenkrupp Industrial Solutions, 472
  - value chains by thyssenkrupp, 473, 474, 476
  - water electrolysis, 455, 472, 475
  - water hydrogen, 467
  - WGS equilibrium, 470
  - zero-gap electrolysis technology, 473
- Hydrogen-rich reductants, 422
- Hyl-energiron process
  - auxiliary energy demand, 437
  - CH<sub>4</sub>, 435
  - chemical absorption process, 432
  - CO<sub>2</sub> emissions, 432
  - DRI, 433
    - CO<sub>2</sub> emissions, 438, 439
    - EAFs, 435
    - high-carbon, 435
    - measurements and calculations, 435, 436

- minimum CO<sub>2</sub> measured, 438, 440
    - PMDR, 438–440
    - quantity, 438
    - use in BF, 435, 436
  - energy balance, 437, 438
  - Fe<sub>3</sub>C, 435
  - fifth hole, 434
  - furnace model, 437
  - gas-based DRI processes, 433
  - graphite, 434
  - hot blast, 437
  - isothermal equilibrium reactors, 437
  - operating conditions assumptions, 438
  - principles, 432
  - production of cold DRI, 433, 434
  - reducing gas, 432
  - shift reactor, 432
- I**
- iEAF system, 368
  - Ignition control system, 134–136
  - Ignition oven efficiency, 134–136
  - IJmuiden, 477
  - Improved charging method, sintering, 139–141
  - Impurities/alloying elements, 320
  - Indirect emissions, EAFs, 303, 329
  - Indirect reduction (IR), 64
  - Industrial energy, 485
  - Industrial-scale grinding mills, 187
  - In-furnace post-combustion, 296, 297
  - Initial reduction reactor, 468
  - Intensified sifting feeder (ISF), 139
  - Intergovernmental Panel on Climate Change (IPCC), 19
  - Internal carbon material acts, 139
  - International Energy Agency, 485
  - Iron and steel industry, 486, 496
  - Iron carbide process, 450–452
  - Iron coke hot briquette (ICHB), 240
  - Ironmaking
    - BF/BOF route, 14
    - DRI/EAF route, 15
    - energy consumption, 10, 21
    - energy intensity, 20
    - GHG emissions, 9
    - LCA, 8
    - MFA, 8
    - optimization, 7
    - ore-based, 7
    - process, 13–15
    - reaction, 460
    - scrap/EAF route, 14
    - smelting reduction route, 15
  - Iron-molybdenum hydrodesulphurization technology, 74
  - Iron ore electrolysis (EW), 463
  - Iron ores, 111, 112, 114, 115, 117, 119, 130, 136, 139, 140, 144, 145, 147–149, 151, 152, 154, 156
  - Iron oxides, 167, 311
  - ITmk3<sup>®</sup> process, 441, 442
- J**
- Japan Iron and Steel Federation (JISF), 255
  - Japanese sintering plants, 120
- K**
- Kaolinite, 315
  - Key enabling technology (KET), 1
- L**
- Ladle preheating, 295
  - Lagrange extrapolation technique, 94
  - Langmuir adsorption equations, 431
  - Large-scale bio char utilization, 535
  - Laser-induced breakdown spectroscopy (LIBS), 327
  - Leachate pH, 315
  - Lean MEA cooler, 505
  - LEEP, 137
  - Life cycle analysis (LCA), 7–9
  - Lignin, 226
  - Limestone, 159
  - Limonite, 139
  - Linz–Donawitz (LD) process, 275
  - Liquefied natural gas (LNG), 447
  - Liquid phase ratio, 152
  - Long-term approaches, 24
  - Low-carbon innovations, 23
  - Low emissions sintering process, 142
  - Low-grade MgO (LGMgO), 312
  - Low levels of carbon, 434
  - LPM-derived carbons (LPMCs), 227
  - Lump ore, 111
  - Lurgi Rectisol<sup>®</sup> unit, 443
- M**
- Magnetically stabilized fluidized bed (MSFB), 130
  - Magnetic braking feeder (MBF), 139

- Materials flow analysis (MFA), 8
  - Mathematical model, 214
  - Mature CO<sub>2</sub> capture technologies, 522
  - Mature COG usage technologies, 528
  - Melter-gasifier, 379, 381, 385–387, 389, 402, 403, 413
  - Melting, 307
  - Metakaolinite, 315
  - Metallized iron usage
    - calorific value, 281
    - DRI/HBI, 280
    - hot metal ratio, 280
    - post-combustion of CO to CO<sub>2</sub>, 280, 281
    - steelmaking cycle, 280, 281
  - Metallurgical coke manufacture, 102
  - Methanation, 492
  - Methane, 469
  - Methane partial oxidation (MPO), 74
  - Methane steam reforming reaction (MSR), 255, 336
  - Methanol synthesis reactor, 505
  - Middle East/North Africa (MENA), 446
  - Midrex<sup>®</sup> process
    - amine-based plant, CO<sub>2</sub>, 426
    - BF-BOF route, 426, 427
    - BF-MIDREX-EAF process, 426
    - CO<sub>2</sub> emissions analysis, 429
    - COG, 426
    - energy consumption analysis, 426, 430
    - energy use and productivity, 426, 428
    - FeO surface, 431
    - gas consumption, 426
    - gasification and CO<sub>2</sub> removal equipment, 424, 425
    - gas mixtures, 424
    - HBI, 424
    - H<sub>2</sub> process, 460
    - hydrogen reduction, 458–460
    - mass and heat balance, 431
    - NG, 426
    - process syngas, 426
    - reducing atmosphere, 424, 425
    - shaft furnace, 424, 431
    - technologies, 494
    - TRS, 426
    - used and wasted energies, 426, 427
  - Mined iron ore, 377
  - 92 MJ/t-sinter, 143
  - MLSS, 45
  - Modern steelmaking, 307
  - Modules, 146
  - Molten oxide electrolysis (MOE), 556
    - advantage, 558
  - CO<sub>2</sub>
    - mitigation factor, 559
    - reduction, 557
  - current densities, 557
  - electrical energy variations, 558
  - electrochemical techniques, 565
  - electrolytic reduction, 565
  - E-logpO<sub>2</sub>, 561
  - energy consumption, 562
  - faradaic efficiency, 562, 563
  - vs. Hall-Heroult cell, 563
  - industrial cell, 564
  - iridium, 564
  - iron-oxygen phase, 559, 560
  - mass transfer correlations, 557
  - minimum practical electrical energy, 558
  - molybdenum crucibles, 564
  - molybdenum-iron transition, 564
  - range of G factor, 558, 559
  - reduction reaction, 565
  - structure and properties, 557
  - temperature levels, 557
  - T-logpO<sub>2</sub>, 559, 560
  - valence distribution, 562
  - YSZ, 565
- Molybdenum crucibles, 564
  - Monitoring systems, 328
  - Monoethanolamine (MEA), 503, 507
  - Monolithic leaching test, 313
  - Moving bed biofilm reactor (MBBR), 45
  - Moving electrode electrostatic precipitator (MEEP), 123
  - Multi-slit burners, 134–136
  - Municipal solid waste (MSW), 257
  - MXCOAL<sup>™</sup> process
    - description, 443
    - emission allowance cost, 445
    - gas pipeline and distribution infrastructure, 444
    - gas prices, 444
    - global natural gas producers, 445
    - HBI, 446
    - iron ore, 446
    - Lurgi Rectisol<sup>®</sup> unit, 443
    - merchant HBI plant, 446, 447
    - reduction rate of oxidized pellets, 443, 444
    - seaborne trade, 446
    - syngas, 443
    - UBS studies, 444
    - world DRI production vs. region, 447

**N**

- Nanofiltration (NF), 46
- Natural gas (NG), 419–422, 424, 426, 427, 431–433, 435, 437, 439, 443–448, 450, 452, 455, 458, 460, 461, 468, 469, 474, 478, 479
  - blast furnace, 211, 214
  - coke rate, 210
  - EISCO, 211
  - furnace conditions, 211
  - internal exergy, 215
  - mathematical models, 214
  - PCI, 209
  - prereduction ratios, 215
  - sub-process, 211
  - theoretical model, 215
  - tuyere area, 215
  - tuyeres level, 209
- Natural gas (NG)-based MIDREX shaft model, 426
- Near-term targets, 22
- Nippon Steel, 82
- Nitrogen reduction ratio (NRR), 145
- Noise pollution, 115
- Non-coking coal in blast furnace, 55
- Non-coking coal resources, 440
- Non-recovery coke making, 88
- Non-recovery coke ovens
  - annual emissions, 90, 92
  - applications, 89
  - carbonization process, 88
  - coal properties vs. emissions parameters, 91, 93
  - coke properties, 90, 91
  - coke quality, 91, 94
  - combusted gases, 88
  - crystallite size, 94
  - CSR, 92, 94
  - direct heating, 89
  - down-comer passages, 88
  - fuel consumption, 89
  - heat recovery coke making, 89
  - Lagrange extrapolation technique, 94
  - mathematical model, 94
  - off-gas, 89, 92
  - properties, 94
  - and recovery, 89, 90
  - secondary flux of air, 89
  - slot-oven coke, 94
  - statistical analysis, 91
  - TSP, 91
  - vibro-compaction, 89
- Nuclear energy, 479
- Nucor plant, 448

**O**

- Oil/waste oil
  - fuel, 208
  - hydrogen, 209
  - thermal effect, 208
- On-line switching control strategy, 82
- Open combustion systems, 284
- Operation guidance system (OGS), 133
- Optical sensors, 326
- Optical texture index (OTI), 240
- Optimal disk atomization, 261
- Ore agglomeration, 311
- Oxidation reactions, 276
- Oxyfuel burners, 369, 501
  - effect, 325
  - electrical energy consumption, 325
  - emissions, 324
  - energy saving, 326, 327
  - net methane reaction, 326
  - post-combustion strategies, 324
  - scrap melting, 326
  - temperature, 324
  - ultrahigh power EAFs, 323
- Oxyfuel combustion scheme, 537
- Oxygen blast furnace, 207, 215
- Oxygen bottom-blowing (OBM), 275, 291
- Oxygen carrier, 78
- Oxygen injection, 331
- Oxygen-supplying technology, 324
- Oxy-oil injection
  - burners, 221
  - CO<sub>2</sub> reduction, 221
  - steelmaking, 221
- Ozone, 46

**P**

- Packing wetting phenomena, 526
- Parallel factor analysis (PARAFAC), 49, 50
- Partial oxidation (POX), 461
- Particulate matter (PM), 130
- Pellets, 440
- Persistent organic pollutants (POPs), 148
- Photo-Fenton process, 48
- Photosynthesis, 493
- Physical absorption, 508, 509
- Physical pre-treatment methods, 45
- “Pipe inside a pipe” arrangement, 326
- Plastic waste injection
  - BF, 216, 217
  - char reactivity, 219
  - chlorine-containing plastics, 216
  - CO<sub>2</sub> emissions, 220
  - coal and waste plastics, 220

- Plastic waste injection (*cont.*)  
 flame temperature, 216  
 furnace permeability, 219  
 HV coal, 219  
 injectants influence, 218  
 injecting coal, 220  
 PCI/WPI, 220  
 PVC, 216, 217  
 thermochemical and kinetic conditions, 216  
 transport, 219  
 tuyere level, 216  
 waste impurities, 217
- Pollutant emissions, 53
- Polychlorinated dibenzofurans (PCDFs), 116, 131, 148, 149
- Polychlorinated dibenzo-p-dioxins (PCDDs), 116, 131, 148, 149
- Polychlorinated dibenzo-p-dioxins and dibenzofurans (PCDD/F), 115, 159
- Polycyclic aromatic hydrocarbons (PAHs), 41, 43, 148
- Polyethylene terephthalate (PET), 100
- Polymeric Si–O–Al framework, 313
- Polymer injection technology, 324
- Polyolefin-enriched wastes, 102
- Polyolefins, 102, 103
- Polyolefins to polystyrene (PS), 100
- Polyvinylchloride (PVC), 148
- Post-combustion, 323, 324, 378
- Post-combustion capture (PCC)  
 carbon abatement options, 535  
 CCS, 535–537  
 CO<sub>2</sub> emissions, 535  
 conventional blast furnace process, 536  
 feasibility, 536  
 industrial processes, 536  
 MEA, 534, 535  
 prototype, 534  
 steel mill, 534  
 VPSA, 536
- Post-combustion optimization, steelmaking, 328–331
- Pre-combustion capture systems, 545
- Pre-reduced agglomerates, 139, 141
- Principal component analysis, 50
- Process gas (PG), 512
- Process-specific capture technologies, 532
- Process syngas, 426
- PSA, 64, 65
- PSA CO<sub>2</sub> scrubbing technology, 510
- Pulverized coal injection (PCI), 189  
 BFG, 183  
 biomass, 183  
 bio-PCI, 188  
 carbon dioxide emissions, 185  
 CBP, 182  
 charcoal supply chains, 183  
 coal-charcoal mixtures, 188  
 coal devolatilization, 185  
 gaseous fuel, 186  
 global warming, 186  
 hydrocarbon fuel, 184  
 integrated steelworks, 185  
 ironmaking process, 187  
 iron oxides reduction, 181  
 non-coked coal, 181  
 oxygen consumption, 182  
 productivity, 187  
 profitability, 184  
 rate, 183  
 screening, 188  
 tuyere, 184  
 unconventional energy resources, 185  
 VIU, 187
- Purified and recycled top gas, 537
- Pyrolysis, 183
- Pyrometallurgical processes, 556
- R**
- Radiation model, 334
- Recovery and utilization of residual energy and heat (RUREH), 486
- Rectisol<sup>®</sup>, 508
- Recycling procedures, 7
- Recycling wastes, 26
- Redsmelt, 452, 454, 455
- Reduction disintegration (RDI), 152
- Reference electrode (RE), 565
- Regenerated activated carbon system (RAC), 127, 128
- Renewable electricity, 477
- Residue injection scheme, 222
- Reverse WGS (RWGS), 71
- Rotary hearth furnace (RHF), 380–382, 440
- Rotary hearth processes, 421
- Rotary kiln direct reduction, 449
- S**
- Scrap  
 grades, 316  
 “invested” energy, 309, 311  
 obsolete, 316  
 preheating, 337–339  
 quality, 322  
 Tecnored process, 409
- Scrap heating, 306
- Scrap melting, 306, 309
- Seaborne trade, 446



- Sectional gas recirculation
  - environmental process optimized
    - sintering, 144
  - FGR (*see* Flue gas recirculation (FGR))
  - FGRS, 143
  - function of composition, 143
  - hazardous substances, 142
  - iron ores, 144
  - limonite, 145
  - low emission and energy optimized
    - sintering, 144
  - NO-CO catalytic reduction, 145
  - NOx reduction, 144
  - NRR, 145
  - properties, 143
  - selective waste gas recirculation, 144
  - thermal state of sintering bed, 144
- Sedimentation tank, 45
- Segregating slit wires (SSW) feeder, 139
- Selective catalytic reduction (SCR), 58
- Selective crystallization and phase separation (SCPS), 255
- Selexol™, 508, 509
- Sequential batch reactor (SBR), 45
- Shaft furnace, 420, 431
  - air-gas burners, 341
  - COREX, 381, 385, 392, 393
  - ECOARC, 343
  - FAF, 341
  - Finger Shaft EAF, 343
  - heat transfer, 339
  - oxy-gas burner flames, 341
  - pellet and lump ore, 380
  - productivity, 339
  - scrap preheating, 340
  - Tecnored process, 408
- Shaft injection (SI), 235
- Shift reactions
  - BFG, 502
  - CO<sub>2</sub> and H<sub>2</sub>, 502
  - CO content, 502
- Short- to medium-term approach, 24
- SIMETAL, 132
- Single-chamber CDQ, 55
- Single-chamber system (SCS), 96, 97
- Single dry quenching (SDQ), 57
- Sinter feed ore, 377
- Sintering
  - air emissions, 115
  - atmospheric emissions, 115
  - BFs, 111
  - in biomass (*see* Biomass)
  - centralized dedust system, 115
  - characteristics ferrous, 111
  - in charcoal (*see* Charcoal)
    - cleaner technology, 117
    - CO<sub>2</sub> emissions, 117
    - coke breeze, 112, 114
    - coke combustion, 113
    - combustion gases, 115
    - combustion zone, 113
    - computer control technologies, 159
    - cooled sinter, 114
    - critical temperature, 116
    - curtain flame ignition system, 145–147
    - desulfurization and dust collection, 117
    - dioxins (*see* Dioxins)
    - dust emission, 117
    - emissions, 115
      - limits, 117
      - reduction, 160, 161
    - energy consumption, 117
    - energy efficiency, 160, 161
    - energy optimized, 142
    - energy-saving solutions, 117, 118
    - environmental regulations, 115
    - EOS, 136, 137
    - EPOSINT process, 137, 138, 160
    - exhaust gas treatment (*see* Exhaust gas treatment)
      - flexibility, 115
      - fuel reductions, 117
      - fugitive emissions, 115
      - heat exchange process, 112
      - heavy metal emissions, 117
      - ignition oven efficiency, 134–136
      - improved charging method, 139–141
      - iron ores (*see* Iron ores)
      - limits for toxic emissions, 115, 116
      - low emissions, 142
      - lump ore, 111
      - materials, 112
      - multi-slit burners, 134–136, 160
      - noise pollution, 115
      - operations, 111, 112
      - PCDD/F, 115
      - process control, 131–133
      - quality assurance, 131–133
      - raw materials, 111
      - reaction zones vs. temperature, 114
      - sectional gas recirculation (*see* Sectional gas recirculation)
        - selective waste gas recycling, 137, 138
        - stack emissions, 115
        - static sinter bed, 112, 113
        - sulfur emission, 115
        - traveling grate, 112
        - treatment of pollutants, 116
        - VOC, 117
        - waste fuels, 146–148

- Sintering (*cont.*)  
 waste heat recovery (*see* Waste heat recovery)  
 wastes, 115  
 wastewater, 115
- Sintering energy control system (SECOS), 133
- Sinter plants, 15
- Slag foaming, 197
- Slag heat recovery  
 chemical methods, 255, 259  
 JISF, 255  
 methane reforming, 257  
 MSR, 255  
 RCA, 256, 257  
 SCPS, 258  
 waste heat, 255
- Small-scale sinter pot experiments, 154
- Smelting, 379  
 charcoal substitutes, 379  
 processes, 378  
 and pre-reduction stages, 379  
 schematic and reactor, 378
- Smelting reduction  
 classification, 380  
 COREX process, 381, 398, 400, 402  
 FINEX process, 402  
 heat and CO-rich hot gas, 378  
 HIs melt, 406  
 hot metal production, 377  
 processes comparison, 379, 421  
 route, 15  
 stage, 379
- Smelting technologies, 27
- Solid sorbents  
 by-product gases, 513  
 coking coal consumption, 516  
 polymeric membranes, 517  
 PSA and VPSA, 511  
 water molecules, 517  
 zeolites, 511
- Solid-state reduction, 424
- Source device supersonic burner (SSB), 331
- Space velocity, 73
- Sponge iron, 419, 468, 469, 472, 473
- SRe processes, 378–380
- Stabilization/solidification (S/S), 311–314
- Stack emissions, 115
- Stamp charging process, 84
- Steam methane reforming (SMR), 67, 74
- Steam reforming (SR) of COG, 63
- Steam stripping, 47
- Steel  
 artifacts, 3  
 complex mixture, elements, 9  
 EII, 1  
 emissions type, integrated steel mill, 17  
 energy consumption, 10  
 EU steel industry, 4  
 global industry, 1  
 heavily traded, 3  
 integrated steel plant, 15, 16  
 iron and carbon, 9  
 KET, 1  
 LCA, 8  
 off-gas dust, 7  
 off-gases, 16, 18  
 plant, 3, 7, 11, 15, 20, 21, 27, 28, 31  
 raw material efficiency, 7  
 recycled material, 4
- Steelmakers, 28
- Steelmaking, 527  
 BF-BOF-CC route, 11  
 BOF, 20  
 breakthrough technologies, 28  
 China, 3  
 companies, 3, 4  
 energy intensity, 20  
 ETC, 5  
 EU, 3, 4  
 hydrogen, 27  
 low-carbon technologies, 28  
 Net export-import per country, 3, 5  
 next-generation nuclear power plants, 32  
 policy mechanisms, 23  
 post-combustion optimization, 328–331  
 primary and secondary production, 1, 2  
 raw materials and reactants, 9  
 renewable energy storage technologies, 32  
 technologies, 4  
 TGR-BF, 28  
 wasted energy, 12
- Steel production, 485  
 China crude, growing rate, 2, 3  
 energy efficiency and CO<sub>2</sub> emissions reduction technologies, 10  
 global crude, 2  
 raw materials, 9
- Steelwork off-gases, 16, 18
- Stelco-Lurgi/Republic Steel-National Lead (SL/RN) process, 448, 449
- Stove hot gas recovery, 200
- Submerged CO<sub>2</sub> and O<sub>2</sub> mixed injection (S-COMI), 324
- Sulfur emission, 115
- Super Coke Oven for Productivity and Environment enhancement towards the twenty-first century (SCOPE21), 97–99
- Super Detox technology, 353

- Supplementary cementitious material (SCM), 261
- Suppressed combustion systems, 284
- Surplus sludge, 45
- Swirlers, 146
- Syngas, 443, 479, 530
- Synthesis gas production, 527, 530
  
- T**
- Tammann furnace tests, 225
- Technological greenhouse number (TGN), 471–475
- Technology
  - CCS, 26
  - DRI, 27, 28
  - energy consumption per each analyze, 21
  - innovation and diffusion policy approaches, 23, 24
  - LCA, 8
  - smelting, 27
  - top gas recycling blast furnace, 27
- Tecnored process
  - agglomerates, 408
  - carbon units, 410
  - consumptions, fuels, 411
  - description, 408
  - furnace, 408, 410
  - lumpy fuel, 410
  - plant, 409
- Temperature, 324
- Tenova's evaporative cooling system technology, 357
- TFN, 471–475
- Theoretical combustion temperature (TCT), 206
- Thermally treated biomass, 231
- Thermal reactor system (TRS), 426
- Thyssenkrupp Industrial Solutions, 472
- Thyssenkrupp Steel, 508
- Top gas recycling (TGR), 206, 494
- Top gas recycling blast furnaces (TGR-BF), 21, 27
  - BF configuration, 246
  - carbon consumption, 247–249
  - Chinese mill, 244
  - CO<sub>2</sub> removal, 243
  - CO<sub>2</sub>-stripped BFG, 243
  - COG composition, 245
  - furnace, 248
  - OBF, 248
  - PCI, 251
  - TGR, 251, 253
  - TGR-OBF, 244, 245
- Top-pressure control system, 192
- Top-pressure recovery turbine (TRT)
  - bio-CCS, 190
  - CO<sub>2</sub>
    - abatement, 189
    - emissions, 190
  - costs, 190
  - low-BTU gas turbine, 190
  - wet/dry, 189
- Torrefied pellets (TP), 228
- Total suspended particulates (TSP), 91
- Toxicity characteristic leaching procedure (TCLP), 314, 315
- Traveling grate, 112
- Trend, 19
- Tri-reforming of methane (TRM), 75
- Tube-in-tube burners, 134
- Tumble index, 155, 156
- Turbulent burners, 134
- Tuyere injection, 211
- Twin-shell EAF, 361, 366
  
- U**
- ULCOWIN steelmaking route, 571
- Usable exergy, 51
  
- V**
- Variable speed drive (VSD) COG compressors, 95
- Vitrification, 311
- Voest-Alpine Industrieanlagenbau (VAI), 132, 133
- Volatile organic compounds (VOCs), 115, 117
  
- W**
- Waelz kiln, 354
- Waste desulfurizer, 398
- Waste energy recovery, 495
- Waste fuels, sintering, 146–148
- Waste gas recirculation, 119
- Waste gas recycling, sintering, 137, 138
- Waste heat recovery (WHR)
  - effective recovery and utilization, 121
  - for EAF, 354
    - approach, 356
    - chemical and physical heat, furnace gas, 357
    - coal gas production, 357
    - CO gas, 360
    - CO<sub>2</sub> recycling, 359
    - Consteel furnace, 358
    - energy balance, 353
    - exergy transfer, 355
    - flue gas exergy determination, 355

- Waste heat recovery (WHR) (*cont.*)
- hot gas line, 356
  - molten salt testing plant, 356
  - off-gas heat recovery, 356
  - organic rankine cycle generators, 358
  - steam and power generation, 358
  - sustainability and resource conservation, 354
  - thermocline storage tank, 356
  - vaporization, 355
  - Waelz kiln, 354
  - electricity generation, 119
  - energy analysis, 121
  - EWHR, 121
  - exergy, 121
  - exhaust gas, 119
  - FGR, 119
  - heat consumed, 118
  - high-temperature flux vs. lower-temperature flux, 120
  - iron ore sintering bed, 119
  - operating parameters, 120
  - recirculation system, 119
  - rotary kiln direct reduction, 449
  - steam generation, 119, 120
  - traditional researches, 121
  - waste gas recirculation, 119
  - in WHRS system, 119, 120
- Waste materials, coke making, 99–103
- Waste plastics, 100
- Wastewater treatment
- aeration tank, 45
  - ammonia salts, 41
  - anaerobic degradation, 46
  - AOPs, 46
  - average concentration, substances before and after treatment, 47
  - biological treatment method, 45
  - COD removal efficiency, 48, 49
  - coke dusts, 49
  - CWW, 49
  - discharges higher quantities, 40
  - documented values from EPB, 47
  - efficiency of A<sup>2</sup>/O system, 47
  - effluent discharge limits and typical emissions, 43, 44
  - Fenton and EF-Feox methods, 48
  - FWC, 40
  - MBBR, 45
  - MLSS, 45
  - NF, 46
  - ozone, 46
  - PAHs, 41, 43
  - PARAFAC, 49, 50
  - photo-Fenton process, 48
  - physical pre-treatment methods, 45
  - plant active at SSAB, 47, 48
  - pre-microfiltration step, 48
  - primary treatment, 45
  - principal component analysis, 50
  - sedimentation tank, 45
  - steam stripping, 47
  - steel industry, 40
  - substances classified as PHS, 43, 44
  - surplus sludge, 45
  - toxic compounds, 41
  - water FWC and TWC, plant sector, 40, 43
  - WFD, 41
- Water
- capillary, 84
  - and carbon dioxide, 45
  - consumption, 43
  - cooling, 52
  - electrolysis, 435, 455, 458, 472, 474, 475, 477, 479
  - FWC, 40
  - hydrogen, 467
  - quenching, 55
  - RWGS+SR pathway, 71
  - velocity, 334
  - WFD, 41
  - World Steel Association, 40
  - Water-cooled panels (WCP), 332, 333
  - Water Framework Directive (WFD), 41
  - Water-gas shift reaction (WGSR), 178, 461, 470
  - Water-intensive industry processes, 40
  - Wet vs. dry cleaning systems, 287
  - Wet fine scrubbers (WS), 130, 131
  - Wet flue gas desulfurization (WFGD), 58, 60
  - Working and counter electrodes (WE and CE), 565
  - Wuhan Iron and Steel Company (WISCO), 133
- Y**
- Yttria-stabilized zirconia (YSZ) cell, 565
- Z**
- Zero-Gap electrolysis technology, 473
  - Zero/low-carbon technologies, 22
  - Zero reformer (ZR), 433, 434, 478
  - Zero waste, 287