

Index

A

Acceptance of models, 15, 19, 23–28, 106–107, 235
Accreditation of models, 24, 114, 115, 118, 236–240
Actin, 206
Active control technology, 147
Active state (muscle), 209, 211
Advisory Group for Aerospace Research and Development (AGARD)
AGARD Working Group WG18
149, 151
Aeronautical engineering, 12
Aggregation (model), 236, 241
Aircraft
active control technology, 147
flight control, 13, 147, 148, 150
flight mechanics, 45, 61, 74, 89, 104, 107, 151, 169, 172, 235
fly-by-wire, 147
model, 156
Algorithmic checks, 81, 119, 135
Alveolar compartment, 178, 181, 182, 184, 185, 190, 191, 194–196
Alveolar-capillary membrane, 179
American Institute of Aeronautics and Astronautics
Committee on Standards in Computational Fluid Dynamics, 26, 77
American Society of Mechanical Engineers (ASME)
Committee on Verification and Validation in Computational Modeling of Medical Devices, 26

Committee on Verification and Validation in Computational Modeling and Simulation, 26
Amplitude range for model testing, 103
Anaesthetic gas, 180, 197
Analogue-to-digital converter (ADC), 8, 12, 59, 106, 130
Animation, 46, 79
Arterial blood, 179, 184, 188
Automotive engineering, 8
Autospectrum, 159, 160, 164, 165

B

Barrier certificate, 15, 86, 87, 92
Biology, 9, 24, 30, 204, 218, 237, 239
Biomedical engineering, 61
Black box model, 9, 222
Block diagram, 21, 24, 54, 62, 68, 80, 81, 118, 134–135, 211, 217, 220, 221
Blood
arterial, 179, 184, 188
mixed-venous, 179, 180, 184, 186, 188
Blood-gas barrier, 175, 179
Bo-105 helicopter, 37, 152, 159
Brain, 175, 176, 205, 207
Building Information Modelling (BIM) Task Group, 238

C

Carbon dioxide, 175, 179, 181, 183–190, 197
Cardiovascular system, 175
Central pattern generator, 207

Chemical engineering, 123
 Chemo-receptors, 176
 Chirp-z transform, 151
 Code review (in model verification), 78
 Coherence function, 43, 44, 65, 89, 159
 Compartmental model, 69
 Compartments
 alveolar, 178, 181, 182, 184, 185, 190, 191, 194–196
 dead-space, 181, 182, 186, 194, 195, 197
 tissue, 183, 184, 191
 Computational fluid dynamics (CFD), 106
 Computer
 aided design (CAD), 14
 control, 2
 digital, 8
 Condition number (of matrix), 70, 188
 Constraints, 15, 27, 114, 117, 122, 137, 160, 189–190, 233
 Continuous
 system simulation, 1, 12, 14, 59, 74, 80
 81, 106
 variables, 9–11, 50, 59
 ventilation, 181
 Contractile element (muscle model), 206
 209–211
 Control
 computer-based, 2
 engineering, 9, 61, 127, 203, 204, 239
 helicopter flight, 170
 of liquid level, 127, 136, 137
 neuromuscular, 13, 203, 207, 208, 218, 220, 223–228, 234
 respiratory, 196, 199
 Convergence, 68, 80
 Coupled-tanks system, 15, 61, 128–130
 134–136, 138, 143, 171, 234
 Cramer-Rao bound, 70, 74, 75, 156
 Credibility (of model), 233
 Criteria for test signal selection
 A-optimal, 72
 D-optimal, 72, 73, 191
 E-optimal, 72
 Crossover (in context of evolutionary computing methods), 67, 68
 Crossover frequency, 68

D

Data model, 9, 41, 117, 166
 Defense Science Board (USA), 236
 Department of Defense (USA), 26, 120

Design

 model-driven, 236
 multidisciplinary, 6, 113, 203
 optimisation, 238
 prototype, 2, 6, 88, 101, 122
 trade-off, 2, 20
 Detail, level of (in model), 5, 7, 122
 208, 235
 Determinancy, 70
 Deutsches Zentrum für Luft- und Raumfahrt (DLR - German Aerospace Centre), 151
 Difference equation, 8, 58, 64
 Differential
 algebraic equations (DAE), 8, 10, 78, 80, 81, 127, 134
 equation, ordinary (ODE), 8, 10, 12, 53, 55, 64, 78, 80–81, 93, 127, 130, 181
 equation, partial (PDE), 8, 10–12, 65, 81, 91, 98, 99
 Digital
 computer, 8
 -to-analogue converter, 8, 82, 106
 Discontinuity, 11, 78, 80, 97
 Discrete-event
 model, 11, 81, 95, 106
 simulation, 58, 106
 Dispersion matrix, 70, 72, 159, 160, 162
 Distortion
 model, 15, 92–94, 139–142, 144
 Distributed parameter model, 10, 11, 81, 105–106, 127
 Documentation (of models and simulations), 6, 79, 102, 117–121, 238
 Domain
 frequency, 14, 29, 43–44, 72, 73, 89, 95, 102, 104, 107, 149, 150, 163, 164, 172, 217, 220
 time, 42, 46
 D-optimal criterion
 truncated D-optimal criterion, 73
 Double doublet, 165
 Doublet, 157, 171
 “Driving” phenomena (muscle spindle receptors), 221
 Dynamic testing (in model verification), 78, 85
 Dystonia (neuromuscular system), 226

E

Education, 16, 96, 128, 241–242
 Electrical
 engineering, 12, 72, 198

- power, generation and distribution, 7, 9, 95, 96, 98, 100, 127, 130, 226
- Electronic
 - systems, 7, 22, 86, 98
- Electro-optic sensor system models, 105
- Embedded systems, 27, 242
- Engineering
 - aeronautical, 12
 - automotive, 8
 - control, 9, 61, 127, 203, 204, 239
 - electrical, 12, 72
 - mechanical, 12, 98
 - software, 26, 119, 238
 - system, 1, 2, 8, 12, 14, 15, 27, 49, 58, 96, 114, 118, 233, 237, 239
- E-optimal criterion, 72
- Equation-error system identification, 64, 154–156, 164
- Errors
 - coding errors, 27, 81
 - discretisation errors, 81
 - model errors, 20, 107, 150, 240
 - numerical errors, 52
 - truncation errors, 80, 81
- Estimates
 - accuracy of estimates, 74–75, 198
 - biased, 123
 - covariance of, 87, 154–156
 - of model structure, 15, 24, 32, 49, 74, 87, 123, 177
 - of parameter of helicopter models, 89, 147–157, 164, 166
 - of parameters, 49, 62, 64, 69, 79, 92, 144, 223
 - of parameters of coupled-tanks system, 128–130, 134–136, 138, 143, 171, 172, 234
 - of parameters (general), 65, 67, 131–134, 137, 150, 188, 192–194, 196
 - of parameters of lung models, 178, 188, 192, 196
 - of parameters of muscle models, 211–214, 222
 - of parameters of muscle receptor models, 224
 - unbiased, 156, 157
- European Space Agency (ESA), 8
- Event, 59, 106, 135, 216, 226, 240
- Evolution
 - algorithm, 63, 65, 67
- Experimental
 - data, 5, 9, 15, 25, 31, 43, 61–67, 69–75, 85, 87, 90, 103–105, 114, 128, 208, 210, 213, 214, 217, 220–223, 234, 235
 - design, 29, 62, 69, 73, 74, 90, 115, 157, 186, 190–194, 198, 218
 - modelling, 12, 61–75, 91, 103, 104, 148, 166, 170, 186, 188, 198, 205, 208–211, 220
- Expiratory period, 181
- External validation, 25, 77, 85, 86, 90, 103, 107, 120, 159, 223, 227, 233, 234
- Extrafusal fibres (muscle), 206, 218
- F**
 - Face validation, 58, 95–101, 115, 120, 123, 224, 227, 241, 242
 - Fast Fourier transformation, 151
 - Fault detection, 2, 234, 240
 - Feed-forward control, 13, 148
 - Fibril (muscle), 206
 - Fidelity
 - physical, 20, 149–150
 - Finite element modelling, 11, 43, 65, 66, 91
 - Fitness-for-purpose (of model), 3, 20
 - Flight
 - control, 13, 147–150, 164–166, 170
 - mechanics, 45, 61, 74, 89, 91, 104, 107, 151, 160, 164, 167, 169, 172, 235
 - testing, 22, 37, 123, 147–153, 158, 168, 171
 - Flow diagram, 79
 - Fly-by-wire, 147
 - Formal methods, 15, 27, 82–83, 86, 241
 - Foundations '02 Workshop, 240, 241
 - Fourier transformation, 151
 - Frequency domain
 - model reduction, 102, 151
 - system identification, 15, 43, 71, 73, 89, 91, 103, 141, 150, 159, 160, 164, 172, 217, 218, 220
 - Frequency range for model testing, 103
 - Frequency sweep signal, 72
 - Frequentist methods, 91
 - Functional neuromuscular stimulation (FNS), 226
 - Functional validity, 30, 107, 234
 - Fusimotor axons (muscle spindle receptors), 219, 222–224
 - Fuzzy control, 227
- G**
 - Gamma motoneurons (muscle spindle receptors), 218, 219, 222–224
 - GAP3 software package, 217
 - GAPTUTOR software package, 217

Gas exchange
 model, 24, 71, 73, 175–178, 180–182, 184, 186–190, 195–199

Gaussian noise, 155

Gaussian process models, 104

Gene (in context of evolutionary algorithms), 65, 67

Generation (in context of evolutionary algorithms), 67

Generic model, 7–8, 105, 114

Genetic algorithm (GA), 65

Genetic programming (GP), 67–69, 141–142

Global
 identifiability, 186, 196
 optimisation, 65, 107

Gradient-based optimisation, 63, 64

Graphical methods for model and system comparison, 90, 120, 137–139

Green Building XML schema (gbXML), 238

Grey-box model, 9

Group Ia/primary axons (muscle spindle receptors), 218, 219, 222–224

Group II/secondary axons (muscle spindle receptors), 219, 222–224

H

Handling qualities, helicopter, 147–150, 170

Hardware-in-the-loop simulation, 242

H^∞ control system design method, 150

Helicopter
 Bo-105, 37, 152, 159
 flight tests, 22, 123, 147–153, 158, 168
 handling qualities, 147–150, 170
 identification and parameter estimation, 61, 62, 64–66, 74, 91, 103, 123, 147, 148, 150–157, 159, 164, 169
 Lynx, 153, 163, 164
 model, 148–149, 154, 164–169
 rotor models, coupled flapping/inflow, 170
 SA-330 Puma, 166–169, 172
 six-degrees-of-freedom model, 172

HELISTAB helicopter flight mechanics model, 164, 168, 169

Hierarchical systems, 205

HiFlow3 software, 11

Hill's model of muscle, 222

Human operator, 12

Human Physiome Project, 237

Hybrid systems, models of, 59

Hydraulic impedance, 98

Hydro turbine, 96

Hypothesis testing, 22, 102, 197, 204, 225

I

Identifiability
 global, 196
 numerical, 70
 pathological, 70, 186, 188, 189, 193, 196
 structural, 70

Identification, system, 12, 15, 23, 31, 36, 43, 49, 53, 58, 62–66, 69–74, 86, 88–92, 94, 103, 118, 141, 144, 147, 148, 150–167, 171, 172, 177, 179, 186, 188, 190, 192, 197, 205, 216, 217, 218, 220, 235, 241

Inert gases, 178, 180, 194, 195, 197

Information matrix, 70, 162

Inspiratory period, 180, 181

Integration, numerical, 80

Interface, model, 82

Internal verification, 25, 77–80, 85, 109, 117, 134–136, 233

International Union of Physiological Sciences (IUPS), 237

Intrafusal fibres (muscle spindle receptors), 220–223

Invalidation, 15, 19, 85–109

Inverse
 model, 12–14
 simulation techniques and applications, 142–143

Isometric conditions (muscle), 211

Isotonic conditions (muscle), 215

K

Kalman filter
 extended Kalman filter, 36, 197

Kiviat diagram, 46

L

Laplace transformation, 9, 54, 55, 186, 196

Least squares minimisation, 65

Library (model), 6, 7, 68, 104, 118, 120

Life cycle, model, 26, 124

Limits
 amplitude, 165
 rate, 99, 149

Linear models, 42, 53, 55, 58, 73, 89, 103, 104, 149, 152, 166, 181, 241

Liquid-level control, 127, 136, 137

Lumped parameter model, 10, 43, 98, 99, 105, 127, 180, 181, 185, 209, 223

Lung

- function, 180, 197
 - homogeneous model, 194, 196
 - inhomogeneous model, 195–197
- Lynx helicopter, 153, 163, 164

M

- MACPUF model, 198
- Management (of models), 6, 91, 102, 114, 117, 119, 121–124, 241
- Marine engineering, 236
- MATLAB®/Simulink®, 7
- Maximum likelihood identification, 74, 156, 159, 192
- Mechanical engineering, 12
- Microfilaments (muscle), 206
- Missile models, 22, 105
- Mixed-venous blood, 179, 180
- Model
- acceptance, 15, 19, 23–28, 85, 104, 228
 - accreditation, 15, 24, 85, 118, 120
 - aggregation, 236, 241
 - black box, 9, 222
 - block diagram, 5, 24, 53, 55, 56, 68, 119, 211–215, 225
 - calibration, 32, 49, 62, 88
 - compartmental, 15, 50, 51, 175–191, 193, 195–199
 - complexity, 5, 15, 20, 22, 23, 29, 30, 45, 51, 63, 66, 91, 102, 114, 176
 - conceptual, 4, 13, 58, 67, 95, 105, 118
 - continuous-variable, 8, 204
 - credibility, 20, 26, 58, 89, 93, 167, 242
 - of data, 87, 102–104, 148, 166, 167, 237, 240, 242
 - discrete-event, 8, 11–12, 14, 58–59, 81–82, 95, 106
 - distortion method, 139, 140
 - distributed parameter, 10, 81, 105–106, 127
 - documentation, 8, 22, 36, 79, 103, 113, 114, 117–123, 128
 - error, 5, 14, 19–22, 25, 28, 64, 65, 74, 94, 107, 143, 157
 - fitness-for-purpose, 3, 20, 239
 - generic, 7, 15, 104–105, 114, 120, 123, 124, 236, 242
 - grey box, 9
 - hybrid system, 8, 11–12, 14, 25, 31, 58–59, 81–82, 106
 - interface, 28
 - invalidation, 15, 19, 160
 - inverse, 12–14, 171

- level of detail, 28
- library, 6–8, 68, 114, 117–121, 124, 236, 242
- linear, 13, 91, 181
- lumped-parameter, 208
- management, 91, 102, 103, 241
- Model Driven Architecture (MDA), 236
- multi-input multi-output, 13, 53, 89, 91, 94, 147, 151
- nonlinear, 13, 15, 52–54, 65, 67, 69, 73, 82, 89, 92, 104, 107, 128–130, 135, 167, 168, 181, 186
- optimisation, 66–69, 166
- physically-based, 90, 95, 151, 153, 168, 242
- quality, 31, 81, 88, 94, 101, 113, 117, 198–199, 236
- reduction, 238
- requirements, 3–5, 24, 27, 35, 86, 114, 117, 119, 123, 234, 236, 239
- re-use, 6–8, 114, 117–119, 121, 123, 124, 236
- robustness, 240
- single-input, 90, 94
- as a specification, 1, 3, 6, 7, 23, 28, 29, 32, 51, 69, 88, 94, 96, 103, 104, 107, 114, 115, 191, 198, 233, 234, 237, 239
- speed of solution, 5
- state space, 51, 54–55, 75, 82, 154, 155
- structure, 4, 20, 23, 28, 30, 42, 50, 53, 54, 62, 66, 68, 80, 88, 90, 95, 105, 107, 121, 139, 150, 157, 170, 171, 176, 180, 185, 192, 195, 196, 198, 218, 221, 228, 235, 238
- testing, 1, 3, 6, 14, 15, 67, 92, 102–104, 108, 113, 117, 123, 129, 205, 224–226, 233–236, 242, 243
- time-invariant, 9, 54
- trade-off, 20, 115
- transparency, 5, 6, 238
- uncertainty, 14, 19–22, 25, 29, 31, 45, 80, 87, 94, 114, 115, 157, 158, 164, 234
- upgrading, 23, 26, 49, 58, 106–107
- validation, 4, 6, 7, 14, 15, 22, 26, 29, 30, 43, 53, 58, 59, 62–75, 88, 92, 94, 103, 104, 106, 107, 113–115, 121–123, 129, 137, 141–143, 147–151, 153–158, 160, 162–167, 169–171, 186, 190, 193, 198, 203, 205, 211, 222, 223, 225, 228, 238, 240, 242
- verification, 14, 43, 77–82, 104, 105, 113–115, 123, 234, 236–240

- Modelica® language, 7
- Modelling
- Defense Modeling and Simulation Office (US Dept. of Defense), 26
 - Good Research Practices Task Force (ISPOR-SMDM), 238
 - Modeling and Simulation Coordination Office (M&SCO) (US Dept. of Defense), 26
 - principles, 6, 15, 28–30
 - software, 78
- Modified condition/decision coverage (MC/DC), 79
- Modularisation (of models), 71, 105
- Motoneurone, 206, 224
- Multi-input-multi-output (MIMO) model, 89, 91, 94
- Multi-step test input signal, 163
- Muscle
- extrafusal fibres, 206, 222, 224
 - intrafusal fibres, 218, 219, 221, 222, 224
 - isometric conditions, 210, 212
 - isotonic conditions, 211
 - mechanical properties, 209, 220
 - models, 211, 212, 214–216, 224
 - skeletal, 207–216, 223, 224
 - spindle receptors, 219, 222, 224
- Mutation, 68
- Myosin, 206
- N**
- Nerve cell, 205, 206, 216, 217
- Nerve fibres, 206, 216
- Nervous system
- central, 13, 176, 205, 225
 - peripheral, 15, 176, 205, 207
- Neuromuscular
- control system, 15, 203–212, 214–228
- Neuron, 91, 206, 216, 217, 219
- Neuroprosthetics, 226
- Nonlinear
- least squares algorithm, 64, 65, 154
 - model, 55, 67, 68, 90, 91, 93, 130, 167
- Nonlinearity
- amplitude limit, 73, 89, 90, 103, 107, 141, 148, 157, 158, 165
 - backlash, 82, 99
 - rate limit, 99, 149
 - saturation, 82, 99
 - static friction, 82
- North of Scotland Hydro Electric Board (NSHEB), 96, 98, 99
- Nuclear bag fibres (muscle spindle receptors), 219
- Nuclear chain fibres (muscle spindle receptors), 219
- Nuclear waste repository design, 27
- Numerical
- identifiability, 69–71
 - integration, 80
 - stability, 79, 80
- O**
- Object-oriented
- methods, 7, 119
- Office of Naval Research (US), 4, 239
- Optimal test input design
- A-optimal criterion, 72
 - D-optimal criterion, 72, 191
 - E-optimal criterion, 72
 - for gas-exchange models, 65
 - for helicopter models, 164, 170
 - truncated D-optimal criterion, 73, 191
- Optimisation
- evolutionary, 67, 68, 141
 - global, 63, 65, 107
 - gradient-based, 63
 - model, 66–69
 - search-based, 13
 - of test inputs, 170, 190
- Ordinary differential equation (ODE), 10, 12, 53, 55, 64, 80, 81, 93, 127, 130, 181
- Output-error system identification, 64, 153, 155–156
- Oxygen, 175, 180, 183–185, 190, 197
- P**
- Parallel elastic element (muscle model), 209
- Parameter
- correlation matrix, 71, 189, 193
 - correlation problems, 89
 - distortion, 86, 92, 139, 144
 - estimation, 12, 15, 23, 31, 54, 58, 61–66, 71, 73, 86, 88–92, 94, 103, 118, 123, 131, 139, 147, 148, 150–157, 159, 166, 169, 170, 177, 179, 186, 188, 190, 198, 211, 220, 241
 - independency, 69–71, 94, 196
 - information matrix, 70, 72, 159, 188, 190, 196
 - optimisation, 5, 46, 49, 62, 64, 66, 67, 69, 88, 107

- perturbation, 50–52, 58
- sensitivity analysis, 15, 23, 45, 50–59, 86, 94–95, 143, 167, 214
- sensitivity matrix, 53, 70, 72, 188, 190
- Partial
 - coherence, 107
 - differential equation (PDEs), 8, 10, 12, 65, 81, 91, 98, 99, 127
- Pathological identifiability, 70, 186, 188, 189, 193, 196
- Performance based design continuum, 239
- Pharmacokinetics, 69
- Physically-based model, 9, 61, 64, 67, 90, 102, 148, 150, 166, 167, 236, 237
- Physical validation, 29, 87, 105, 107, 150, 167, 236, 237
- Physiology, 2, 176–177, 181, 198, 203–207, 227, 234
- Pipeline model, 98
- Poles, 13
- Polygon diagram for model and system comparison, 45
- PolySpace® tools, 82
- Positive feedback, 225
- Predictive validation, 30, 86–87, 115
- Prototype, virtual, 6, 150, 242
- Pseudo-random binary (PRB) signals, 72, 91
- Pulmonary blood flow estimation, 198
- Pulmonary gas-exchange processes, 177

- Q**
- Qualitative model, 5, 58, 224, 225, 233, 241
- Quality (of model), 5–6, 14, 19–22, 24, 26, 35, 43, 44, 64, 75, 93, 103, 104, 113, 122, 149, 165, 166, 180–181, 189, 198, 203, 228, 233, 234, 239–241
- Quantitative measures (for model and system comparison), 43, 90

- R**
- Realisability, 13
- Real-time simulation, 8, 31, 96–99, 101, 170
- Record length (in system identification and parameter estimation), 171
- Reduction (of model), 11, 102, 151, 196
- Regressive testing, 105, 119
- Renshaw cells, 225
- Reproduction, 3, 121, 226, 238
- Residuals, 87, 150, 192, 198
- Resonance, 160, 164

- Respiratory system, 175, 181, 198, 235
- Re-use (of model), 6–8, 117–119, 121, 123, 124, 236
- Reverse engineering, 116
- Robotics, 203, 204, 227
- Robustness (model), 62, 63, 164, 171, 235
- Royal Aerospace Establishment (UK), 164

- S**
- SA-330 Puma helicopter, 166–169, 171, 172
- Safety-critical application, 2, 3, 27, 79, 86, 236
- Search-based optimisation, 67
- Segmental level (within peripheral nervous system), 205, 206
- Sensitivity
 - analysis, parameter, 15, 23, 31, 58, 63, 94–95, 114
 - function, relative, 51
 - functions, 50–57, 70
 - matrix, 53, 70, 72, 73, 188, 190
 - model, 52–57
- Sensory receptors
 - chemo-receptors, 176
 - Golgi tendon organ, 218, 220, 223–225
 - muscle spindle, 206, 218, 219, 222–225
- Series elastic element (muscle model), 209–211, 215
- Ship-Smart System Design (S3D) tool, 4, 239
- Shunt (circulatory), 177–179, 184, 194, 196
- SIMH helicopter flight mechanics model, 37, 151, 152
- Simscape™, 7
- Simulated annealing (SA), 65, 69, 141
- Simulation
 - continuous system, 1, 12, 13, 80–82, 106
 - discrete-event, 12, 106
 - hardware-in-the-loop, 8, 22, 31, 96, 98, 242
 - hybrid, 12, 59, 106, 204
 - inverse, 14, 15, 70, 142–143, 191
 - software, 3, 6, 7, 14, 27, 77, 79, 86, 116
- Simulator
 - hardware-in-the loop, 2, 96
 - research and development, 15, 148
 - training, 2, 15, 67, 121
- Sine wave signal, 71
- Single-input-single-output (SISO) model, 13, 44, 55, 90, 94, 162, 220, 240
- Sloy Power Station, 96

- Society for Modeling and Simulation
International (SCS)
SCS Technical Committee on Model
Credibility, 25
- Software
engineering, 1, 116, 118
for simulation, 3, 7, 14, 27, 46, 78, 79,
82–83, 114, 116, 119, 121, 122, 217
- SOSTOOLS, 92
- Speed of solution (of simulation model), 5
- Spike train (nervous system signal), 216, 219
- Spinal cord, 205, 206, 219, 225
- Stability
numerical, 79, 80
system, 92, 150, 223, 240
- State-space models, 54
- State variable, 40, 51–54, 56, 93, 103, 107, 141,
154, 156, 157
- Static analysis (in model verification), 78
- Stiffness (in modelling and simulation
context), 207, 209, 223
- Stretch reflex, 205, 207, 208, 224, 226
- Structural identifiability, 69, 170
- Structure (of model), 4, 8, 11, 20, 24, 28, 32,
42, 49, 64, 67, 68, 90, 139, 149, 170,
181, 185, 197, 235
- Sub-model, 4, 6, 8, 9, 14, 22, 30–31, 63,
80, 82, 89, 104–105, 114, 115,
118, 120, 130, 176, 196, 222, 235, 236
- Switch function, 59
- System identification
equation-error, 153, 155
frequency-domain, 44, 90, 164
maximum-likelihood, 156–157
methods, 45, 89, 90, 123, 166, 168, 177,
197, 217
output-error, 41, 107, 156
- T**
- Taylor series, 50
- Terminal nodes, 67, 141
- Test input signals
3-2-1-1, 157, 158, 160, 161, 164
binary multi-step, 72, 74, 160, 162–164
double-doublet, 164, 165
doublet, 157, 158, 160, 161, 164
frequency-sweep, 71, 74, 91, 158, 160, 161
pseudo-random binary, 72, 91
- Tests (of models)
regressive, 105, 119
turing, 95, 228
- Theil's Inequality Coefficient (TIC), 41, 137
- Tidal ventilation, 181, 182, 184–186,
194–197
- Time delay, pure, 11, 44, 217
- Time domain, 14, 50, 72, 73, 90, 95,
102, 137, 149, 150, 152, 155,
196, 217
- Time-invariant model, 9
- Trade-offs, in model development, 2, 235
- Transfer function, 9, 13, 55–57, 69, 89–91,
162, 163, 220
- Transparency, model, 3, 6, 238
- Trends, parametric, 168
- Truncated D-optimal criterion, 73, 191
- Turbine, hydro, 96, 102
- Turing test (for model), 95
- U**
- Uncertainty, model, 4, 32, 80, 95
- Upgrading of models, 106–107
- V**
- Validation
external, 25, 77, 85, 86, 90, 103, 107–109,
120, 159, 223, 227, 233, 234
face, 15, 58, 95–101, 115, 120, 123, 227,
241, 242
physical, 63
pragmatic, 234
predictive, 26, 29
theoretical, 30, 233
- Variance (of parameter estimates), 70, 171
- Ventilation
continuous, 180–181, 183, 184
tidal, 181, 182, 184–186, 194–197, 199
- Verification
internal, 25, 77–80, 85, 117,
134–136, 233
validation and accreditation (VV&A), 114,
115, 122, 236–240
- Virtual
prototype, 6
test bed (VTB), 7
- Visualisation, 14, 29, 37, 45–46, 62, 169, 238