

# Index

## A

- Action potential
  - cell body, 26
  - dendrites, 26
  - development, 26
  - different phases, 24, 25
  - impulse conduction and information flow
    - in neuron, 26
  - ionic activities, 26
  - sodium channels, 26
  - threshold stimulus, 26
  - values, 24
- Active charge balancing, 104
  - charge surveillance, 105
  - pulse insertion, 105
- Active implantable devices, 18, 19
  - components, 32, 33
  - drug delivery systems, 19
  - electronic systems
    - continuous health status monitoring, 18, 19
    - electrical stimulation, 18
    - neural amplifiers, 18
- Active telemetry, 192
- Adaptive control load-shift keying, 200–201
- Advanced RISC machines (ARM), 142
- Age-related macular degeneration, 397
- Alpha IMS retinal implant, 403, 406
- Alzheimer's Disease, 326
- Amplitude control
  - active resistance, 148
  - FET, 148
  - optocoupler, 149
  - PWM, 149
- Amplitude-shift keying (ASK), 193, 194
  - data transmission, 202
  - limitations, 203
- Analog front end (AFE)
  - analog circuitry unlike digital circuitry, 49
  - ASICs, 49
  - CMRR, 49
  - filters, 49
  - OP-AMPs, 49
  - parameters, 49
- Analog signal processing, 49, 71–72
- Analog-to-digital converters (ADCs), 46, 47
  - binary number, 89
  - digital circuit, 89
  - direct conversion architecture, 89, 90
  - LSB, 89
  - MSB, 89, 91
  - OP-AMP comparators, 89
  - parallel, 89
  - SAR, 90, 91
  - types, 89
- Antenna, 33, 36
- Application-specific integrated circuits (ASICs), 49
- Argus II retinal system, 403
- Arithmetic and logic units (ALUs), 46
- ARM. *See* Advanced RISC machines (ARM)
- Arrhythmias
  - detection
    - dual-chamber ICDs, 303
    - ECG signals, 302
    - single lead, 302
    - single-chamber ICDs, 302–303
  - and pacemaker indications
    - AV block, 275
    - bradycardia, 274
    - heart upper chambers, 275
    - SA node, 274
- ASK. *See* Amplitude-shift keying (ASK)

- Astable multivibrator, 118–119
  - charging time, 129
  - circuit and waveforms, 128
  - discharging time, 129
  - duty cycle, 129
  - external capacitor, 126, 129
  - flip-flop, 129
  - free-running oscillation frequency, 129
  - total period, 129
- Auditory nerve, 7, 379–385, 388
- Auto-zeroing amplifier (AZA)
  - main amplifier  $A_M$ , 236
  - nulling amplifier  $A_N$ , 236
  - signal sampling-based technique, 236
  - subtraction process, 237
- Auxiliary-carrier load-shift keying, 199–200
  
- B**
- Back electromotive force (EMF), 99
- Bandgap reference circuit, 38, 41, 42
- Bandgap voltage reference circuit, 40–43
- Barrier lowering, 69
- Battery
  - cathode materials, 170
  - electrochemical energy, 167
  - electrodes, 167
  - electrolytic solutions, 170
  - electropositive elements, 169
  - lifetime, 181
  - lithium, 169
  - neurostimulators, 170
  - primary cells and secondary/rechargeable cells, 170
  - safety, 181
  - spectacular electrochemical equivalent, 170
  - terminology, 167, 168
- Battery-less implant, 44
- Binary search algorithm, 91
- Binary weighted DAC, 86, 88
- Bioceramics
  - corrosion, 161
  - dental ceramics, 160–161
  - RF communication, 160
  - toxic effects, 161
  - types, 160
- Biocompatibility
  - biotechnological applications, 154
  - cellular/tissue functions, 155
  - factors, 154
  - innovatory systems, 154
  - materials, 154, 155
  - polymeric materials
    - advantages, 162
    - LCP, 163
    - metals and ceramics, 161
    - parylene-C, 163
    - PDMS, 163
    - PEEK, 162
    - polyimide, 162
    - polymer integration, 163
    - PVDF, 162
  - properties, 154
  - toxicity, 154
- Biodegradation
  - category, 421
  - nonbiodegradable, 421
- Bioelectricity
  - action potential, 24–26
  - by cells, 22
  - membrane potential, 22–24
  - voltages, 21
- Biomaterials, 154
  - acute inflammation, 156
  - biocompatibility, 154, 155
  - blood–material interactions, 155
  - bone/joint replacements, 154
  - chronic inflammation, 156
  - definition, 153
  - fibrosis and fibrous encapsulation, 157
  - foreign body reaction, 157
  - granulation tissue, 156
  - implantation, 153
  - injury, 155
  - metal/polymer, 153
  - provisional matrix formation, 156
- Bionic ear, 379
- Biotelemetry
  - active, 192
  - passive, 192–193
- Biphasic defibrillator, 83, 84
- Biphasic pulses, 103
- Bipolar electrode, 82, 83
- Bistable multivibrator, 119–120
- Bladder control, 370, 371
- Blocking capacitor, 103–104
- Blood pressure/glucose level, 18
- Blood pressure sensor
  - accelerometers, 251–253
  - capacitive, 251, 252
  - SAW sensor system, 253–255
- Boost converter, 98–99
- Bulk model/mobility fluctuation model, 66
  
- C**
- Carbon monofluoride–silver vanadium oxide
  - hybrid battery, 178
- Cardiac pacemakers, 20
  - asynchronous, 279

- automatic safety, 287
  - backup features, 287
  - biventricular, 275, 278
  - dual-chamber, 268, 275, 277
  - electromagnetic interference, 289
  - heart chambers, 269
  - heart medications, 290
  - high blood pressure, 290
  - multi-programmable, 268
  - rate responsiveness, 286–287
  - rate-responsive/frequency-responsive, 276
  - sense amplifier, 268
  - single-chamber, 275, 276
  - stimulating pulse, 275
  - synchronous, 279
- Catheter, 16, 19, 257, 259, 334, 368, 414, 416, 422
- Central processing unit (CPU)
  - ADC, 46, 47
  - ALUs, 46
  - brain/intellect, implant, 46
  - DSP, 47
  - floating-point, 46
  - FPU, 47
  - microprocessor, 46
  - Nyquist rate, 47
- Cerebral ventriculography, 319
- Channel length, 69, 71
- Charge balancing
  - biphasic pulses, 103
  - passive, 103–104
- Charge transfer sense amplifier, 76
- Chargeable battery, 37
- Charge-controlled stimulation (ChCS), 102, 103
- Chopper-stabilized amplifier
  - amplitude modulation, 232
  - baseband frequency, 232
  - chopping frequency, 233
  - clock signal, 234
  - CMOSFET, 233
  - concept, 232
  - gain-phase limitations, 234
  - modulator/demodulator, 234
  - switch modulator, 233
  - wide bandwidth, 235, 236
- CI. *See* Cochlear implant (CI)
- CISC. *See* Clean sporadic self-catheterization (CISC)
- Clean sporadic self-catheterization (CISC), 371
- Clock-based amplifiers, 230–237
  - AZA, 236, 237
  - chopper-stabilized amplifier, 232–236
  - switched-biasing amplifier, 230, 231
- Clock divider, 145
- Clock generators, 110–111
- CMOS switch, 85
- CMOSFET noise sources
  - flicker, 65–66
  - generation–recombination, 67
  - popcorn/burst, 67
  - shot, 66–67
  - thermal, 65
- CMRR. *See* Common-mode rejection ratio (CMRR)
- Cochlear implant (CI), 380–382, 385–389
  - acoustic vs. electrical hearing, 383–385
  - auditory nerve, 380
  - bionic ear, 379
  - candidacy
    - postsurgery, 389
    - presurgery, 388
    - surgical procedure, 389
  - components
    - external functionality, 385–387
    - internal functionality, 387, 388
  - development, 380
  - vs. hearing aid, 382–384
  - hearing loss
    - conductive, 380–382
    - mixed, 382
    - sensorineural, 381, 382
  - microelectrode array, 379
- Common-mode rejection ratio (CMRR), 49, 238
- Complementary metal–oxide–semiconductor (CMOS) device
  - advantages, 58, 60
  - inverter, 58
  - NAND gate, 58, 59
  - NMOS transistors, 56
  - NOR gate, 58, 59
  - NOT gate, 58
  - N-well, 56, 57
  - PDN, 56, 58
  - PMOS transistors, 56
  - P-type and N-type MOSFETs, 56
  - PUN, 56, 58
  - P-well, 56, 57
  - twin-tub, 56, 57
- Continuous-time amplifier circuits
  - bipolar transistor, 241
  - clock-based circuits, 240
  - CMOS amplifier, 243, 244
  - low input capacitance amplifier, 245
  - OTA, 240, 242
- Conventional drug delivery systems
  - intramuscular method, 415
  - intravenous method, 413–415

- Conventional drug delivery systems (*cont.*)  
 nasal method, 410  
 oral method, 410  
 pulmonary method, 410, 412  
 time-honored and preferred routes, 410, 411  
 traditional drug delivery routes, 410, 412  
 transdermal method, 412, 413
- CRC. *See* Cyclic redundancy check (CRC)
- Crystal oscillator (XO), 111–112  
 ample negative resistance, 115  
 CMOS, 114  
 inverters, 115, 116  
 Pierce design, 114  
 P–N MOSFET, 114  
 practical oscillator circuit, 115  
 and RC, 114  
 square wave, 114  
 unbuffered inverter, 114
- Current mirror, 92, 94, 95
- Current sink, 92, 94
- Current source, 92–94
- Current-controlled current source (CCCS), 92
- Current-controlled stimulation (CCS), 100, 103
- Current-mode sense amplifier, 75–76
- Current-mode stimulation, 100, 101
- Cyber security  
 adversaries types, 212  
 apprehensions, 210  
 authentication, 220  
 confidentiality/privacy, 209  
 data integrity, 211  
 deliberate breaches, 211  
 device-existence privacy, 211  
 device modification, 221–222  
 device-type privacy, 211  
 efficiency and usability, 220  
 hacking, 210  
 rigorous testing and verification, 211  
 safety, 209, 220  
 shield, 221, 222  
 specific device ID privacy, 211  
 UHM, 222  
 unintentional breaches, 212  
 wireless and internet connectivity, 210
- Cyclic redundancy check (CRC), 216
- D**
- DAC. *See* Digital-to-analog converter (DAC)
- Data acquisition, 218–220
- Data telemetry downlink  
 ASK, 202–203  
 FSK, 203  
 PSK, 203–204
- Data telemetry unit, 44–46
- Data telemetry uplink  
 adaptive control load-shift keying,  
 200–201  
 auxiliary-carrier load-shift keying,  
 199–200  
 digital modulation techniques, 193–195  
 load-shift keying and multilevel load-shift  
 keying  
 bandwidth, 198  
 bilevel and multilevel, 198  
 data rate, 198  
 power and data, 197  
 reflectance modulation, 196  
 passive phase-shift keying, 201  
 pulse harmonic modulation, 201–202
- DBS. *See* Deep brain stimulation (DBS)
- DC offset voltage, 67, 68
- DCS. *See* Dorsal/posterior column stimulation  
 (DCS)
- DC-to-DC converters, 96
- Deep brain stimulation (DBS), 311–313,  
 316–320, 324–326  
 description, 309  
 implant location, 315  
 vs. lesioning  
 advantages, 316  
 disadvantages, 316, 317  
 mechanisms, 321–324  
 movement disorders  
 dystonia, 313  
 PD, 311–312  
 tremor, 312–313  
 patient selection/exclusion criteria  
 idiopathic PD, 318  
 multidisciplinary committee, 317  
 personal expectancy, 317  
 progressive supranuclear palsy, 316  
 psychiatric and neurological disorders  
 Alzheimer’s disease, 326  
 major depression, 324–325  
 OCD, 325, 326  
 risks, surgery, 324  
 stimulation parameter, 321  
 surgical methodology  
 cerebral ventriculography, 319  
 DBS electrode, 320  
 dura, 320  
 electrical stimulation, 320  
 IPG, 320  
 system IPG, 320  
 thalamic VIM nucleus, 315  
 unilateral, 315
- Deep brain stimulator (DBS), 20

- Dendrites, 26, 394, 396
  - Dental ceramics, 160–161
  - Depression, 318, 324–325, 327
  - Design of implantable ICs, 56–60, 62–67
    - biological systems, 55
    - channel length, 69, 71
    - CMOSFET (*see* Complementary metal–oxide–semiconductor (CMOS))
    - DC offset voltage, 67, 68
    - industrial systems, 55
    - leakage currents, 61–62
    - N- and P-channel devices, 61
    - single-chip vs. multiple-chip, 60
    - speed and threshold voltage trade-off, 60
    - submicron transistors (*see* Submicron transistors)
    - temperature range, 55
    - testing and evaluation, 76–77
  - Diaphragm pacing vs. mechanical ventilation
    - air forcing, 359
    - breathing and speech patterns, 359
    - community and learning activities, 359
    - costs, 359
    - D/P nerve stimulation, 359
    - infection rate, 359
    - respiratory infections, 359
    - tracheostomy/tracheotomy, 360
  - Diaphragmatic/phrenic nerve (D/P) stimulation
    - axons, 356
    - brachiocephalic artery, 357
    - carotid sheath, 357
    - contraction, 357
    - electrode(s), 355
    - handles and controls breathing, 355
    - hypoventilation, 356
    - indications, 360–361
    - left subclavian vein, 357
    - lungs, 357
    - motor neurons, 356
    - natural breathing, 356
    - pacing system, 361–363
    - phrenic pacing, diaphragm pacing/
      - electrophrenic respiration, 355
    - quadriplegia/tetraplegia, 357
    - radio-frequency signals, 356
    - respiration, 356
    - surgical procedure, 363
    - thoracic cavity, 357
    - thoracic diaphragm, 356
    - training, rehabilitation and precautions, 363–364
  - Digital ICs, 51
  - Digital modulation techniques
    - ASK, 193
    - FSK, 193
    - N* bits, 195
    - PSK, 193
  - Digital pot/digipot/resistive digital-to-analog converter (RDAC), 147
  - Digital signal processing, 71–73
  - Digital signal processor (DSP), 47
  - Digital-to-analog converters (DACs), 147
    - binary weighted, 86, 88
    - pulse-width modulator, 86, 87
    - R/2R ladder, 86, 88
  - Dorsal column stimulation (DCS), 331
  - Drain-induced barrier lowering (DIBL)
    - barrier lowering, 69
    - long-channel and short-channel MOSFET, 68
    - parameters, 69
    - P–N junctions, 68, 69
    - reverse-biased depletion region, 69
    - semiconductor, 68
    - short-channel effects, 69, 70
    - VLSI, 68
  - Driver circuit, 99
  - Dura mater, 332
  - DVS. *See* Dynamic voltage scaling (DVS)
  - Dynamic RAM (DRAM), 47, 48
  - Dynamic voltage scaling (DVS), 143
  - Dystonia
    - botulinum toxin injection, 313
    - levodopa, 313
    - women, 313
- E**
- Economization unit, 43
  - EIA. *See* Electronic Industries Association (EIA)
  - Electrical hearing, 383–385
  - Electrical stimulation therapy, 373, 374
  - Electrically erasable programmable read-only memory (EEPROM), 48
  - Electro stimulation, 85–99
    - biphasic defibrillator, 83, 84
    - bipolar, 82, 83
    - functional circuit blocks (*see* Functional circuit blocks)
    - monophasic defibrillator, 83, 84
    - monopolar, 81, 83
  - Electrocardiogram (ECG) waveform
    - peak-to-peak values, 272
    - time delay, 274
  - Electroencephalography (EEG), 21
  - Electromagnetic interference (EMI), 38, 218
  - Electromyography (EMG), 21

Electronic block, 51–52  
 Electronic Industries Association (EIA), 145  
 Electrostatic discharge (ESD)  
   limit and protection, 72  
   protection circuits, 51  
   suppression components, 51  
   suppressors, 51  
 EMI. *See* Electromagnetic interference (EMI)  
 Epidural anesthesia, 333, 334  
 Epidural space, 332  
 Epileptic seizures, 341–342  
 Epiretinal implant  
   components, 401  
   electrical signals, 401  
   information-bearing signals, 403  
   microelectrodes, 401  
   microprocessor, 401  
   types, input, 401

## F

Failed back surgery syndrome (FBSS), 339  
 FBSS. *See* Failed back surgery syndrome (FBSS)  
 FDA. *See* Food and Drug Administration (FDA)  
 FDTD. *See* Finite-difference time-domain (FDTD)  
 Fecal incontinence, 372, 376, 377  
 Feedback oscillator, 110  
 Filter, 37–38  
 Finite-difference time-domain (FDTD), 191  
 Fitting pacemaker, 280, 281  
   post-operation follow- ups, 281  
   surgery  
     antibiotics, 280  
     collarbone, 280  
     epicardial implantation, 280  
     transvenous implantation, 280  
     transvenous method, 281  
     veins, 281  
 Flicker noise  
   bulk model/mobility fluctuation model, 66  
   carrier number fluctuation model, 65  
   charge exchange, 66  
   CMOSFETs, 66  
   CMOS transistors, 66  
   MOSFETs, 66  
    $1/f$  noise, 65  
   pink noise, 65  
   surface model, 65  
   trapping mechanisms, 65  
 Flip-flop, 4, 47, 117, 119–122, 124, 129, 145, 146  
 Floating gate MOSFETs (FGMOSFETs), 48

Floating-point unit (FPU), 47  
 Food and Drug Administration (FDA), 370  
 Fowler's syndrome, 372  
 Frequency-shift keying (FSK), 193, 195, 203  
 Fringe-lying Boolean circuits, 73  
 FSK. *See* Frequency-shift keying (FSK)  
 Full-wave voltage doubler, 96  
 Functional circuit blocks, 85  
   ADC, 89–91  
     boost converter, 98–99  
   CMOS switch, 85  
   current mirror, 92, 94, 95  
   current source, 92, 93  
   DACs (*see* Digital-to-analog converters (DACs))  
   driver circuit, 99  
   timer circuit, 99  
   VIC, 94–96  
   voltage multiplier, 96–98  
   voltage source, 92, 93

## G

GABA-B. *See* Gamma-aminobutyric acid (GABA)-B  
 Gamma-aminobutyric acid (GABA)-B, 338  
 Gate control theory (GCT), 337  
 Gate-induced drain leakage  
   doping levels, 61  
   gate-to-drain overlap region, 62  
   reduction of CMOS, 62  
   Zener-type leakage, 61  
 GCT. *See* Gate control theory (GCT)  
 Generation–recombination noise, 67  
 Globus pallidus, 309, 314, 315, 325

## H

Hearing aid, 382, 383  
 High-rate lithium  
   carbon monofluoride–silver vanadium oxide hybrid battery, 178  
   manganese dioxide battery, 178  
   silver vanadium oxide battery, 177  
 Hijacking. *See* Insulin infusion pump

## I

IC boost converter, 99  
 ICD. *See* Implantable cardioverter defibrillator (ICD)  
 IDDSs. *See* Implantable drug delivery systems (IDDSs)  
 IMD. *See* Intermodulation distortion (IMD)

- Immunoisolating capsule, 425
- Implant security
  - admission controllers, 213
  - cipher, 213
  - corporal security, 213
  - cryptography, 213
  - customary ciphers, 214
  - decryption, 213
  - encryption key, 213, 214
  - fundamental security ideas, 214, 215
  - product and manufacturing company, 213
  - security protocols, 214
  - source code, 213
  - threat modeling, 214
  - validation tests, 214
- Implantable cardioverter–defibrillator (ICD),
  - 294, 295, 304, 305
  - amiodarone hydrochloride, 294
  - arrhythmia detection, 300–302
  - arrhythmias, 297, 298
  - audio alerts, 218
  - beep warnings, 218
  - cardiac arrests, 297
  - cardioversion, 303
    - ATP, 295
    - electrical shock, 295
    - scrupulous attention, 295
    - tachyarrhythmia, 295
  - closed-loop system, 217
  - construction, 298
  - coronary heart disease, 297
  - defibrillation, 303
  - detection zones, 302
  - EMI, 218
  - endocardial (transvenous), 300, 304
    - vs. epicardial, 298
  - epicardial, 299
    - and endocardial leads, 299
  - monomorphic tachycardias, 304
  - and pacemaker
    - cajole and coax, 295
    - implantable medical devices, 295
    - low-energy pulses, 295
    - shrunk versions, 295
  - physiopathological mechanisms, 293
  - post-implantation
    - antiarrhythmic drugs, 305
    - cardiac emergency, 304
    - electrical shocks, 304
    - heart signals, 304
  - prevention, 297
  - radio transmissions, 217
  - subcutaneous, 301
  - user interface, 218
  - ventricles, 296
  - ventricular arrhythmias, 303
  - ventricular fibrillation, 303
  - ventricular tachyarrhythmias, 297
  - VT and VF
    - extrasystoles, 294
    - sinoatrial node, 294
    - sudden cardiac death, 294
- Implantable devices, 18, 21
  - active (*see* Active implantable devices)
  - bioelectricity (*see* Bioelectricity)
  - cardiac pacemaker, 20
  - DBS, 20
  - defibrillators, 20
  - definition, 14
  - electrical system, human body, 20, 21
  - invasive, 16
  - medical devices, 14
  - medicinal products, 14
  - MEMS, 20
  - mesmerizing and sensational field, 27
  - microwatt to milliwatt range, 20
  - noninvasive, 16
  - transmitters, 20
- Implantable drug delivery systems (IDDSs),
  - 410, 426
  - advantages, 415–418
  - biodegradation-based classification, 420, 421
  - conventional (*see* Conventional drug delivery systems)
  - disadvantages, 418, 419
  - micro- and nanoscale, 422, 423, 425, 426
  - micropumps (*see* Micropumps)
  - passive and active, 421, 422, 426
  - properties, 419, 420
  - types, 409
- Implantable electronic system
  - sensing action, 32
  - stimulating nerves/muscles, 32
  - teleactuation, 32
  - telemetry, 31, 32
  - transistor models, 71
- Implantable medical devices
  - definition, 17
  - objectives, 17
- Implantable medical electronics, 1–3
- Implantable power sources
  - conventional non-rechargeable unit, 336–337
  - radio-frequency unit, 337
  - rechargeable unit, 337
- Implanted biosensors, 218–220
- In-circuit serial programming, 145

- Induction charger, 34
    - electromagnetic field, 34
    - inductive coupling, 34
  - Inductive charging
    - applications, 190
    - conductor, 188
    - coupling and loading variations, 189
    - design considerations, 189
    - frequencies usage, 188–189
    - primary and secondary coil, 188
  - Insulin infusion pump
    - body-coupled communication, 217
    - communication packet, 216
    - CRC parameters, 216
    - data reception, 216
    - device PIN, 217
    - glucose meter/remote control accessory, 216
    - open-loop procedure, 215
    - open-loop system, 217
    - passive and active mode attacks, 216
    - rolling code technique, 217
    - security infringement, 216
    - subcutaneous glucose sensor, 215
    - system availability attacks, 216
    - system integrity attacks, 216
    - system privacy attacks, 216
    - USRP, 216
  - Intermodulation distortion (IMD), 239
  - Intramuscular method, 415
  - Intravenous method
    - fast drug delivery, 413, 414
    - IV push and IV infusion, 414
    - limitations, 415
    - medication, risk, 414
    - slow drug delivery, 414
  - Invasive device, 16
- J**
- Jamming, 212, 221
- L**
- Laminotomy, 336
  - LCP. *See* Liquid crystal polymer (LCP)
  - Leakage currents, 61–62
    - SILC, 62–63
      - submicron transistors
        - gate oxide, 62
      - GIDL, 61–62
  - Lesioning. *See also* Deep brain stimulation (DBS)
    - pallidotomy, 313–314
    - subthalamotomy, 313–314
    - thalamotomy, 313–314
  - Linear and nonlinear oscillators, 110
  - Linear power supply, 40, 41
  - Linear voltage regulator, 38, 39
  - Liquid crystal polymer (LCP), 163
  - Lithium/carbon monofluoride battery
    - carbothermal treatment, 176
    - chemical reaction, 176
    - customization process, 176
    - fluorine, 175
    - gravimetric and volumetric energy densities, 176
    - milliwatt power range, 175
    - solid electrolyte, 176
    - transitional phase, 176
  - Lithium/carbon monofluoride–silver vanadium oxide hybrid battery, 176–177
  - Lithium/iodine–polyvinylpyridine battery
    - ampere-hour, 172
    - anode and cathode, 170
    - discharging, 172
    - electronic conductivity, 171
    - energy density, 172
    - exothermic reaction, 170
    - Gibb’s free energy, 172
    - layers, 171
    - microampere range, 170
    - peak value, 171
    - polymeric structure, 170
    - sheet, 172
    - solid electrolyte/superionic, 171
  - Lithium-ion battery, 178–180
  - Lithium–manganese dioxide battery
    - alkali metal salt, 173
    - applications, 172
    - distinctive regions, 174
    - high ionic conductivity, 173
    - open-circuit voltage, 173
    - polyethylene layer, 173
    - solid core, 174
    - wound, 174, 175
  - Load shift keying (LSK) modulation, 46
- M**
- Major depressive disorder (MDD), 348
  - Manganese dioxide battery, 178
  - MDD. *See* Major depressive disorder (MDD)
  - Medical data services (MEDS), 44
  - Medical device, 14
    - classification, 15
    - vs. medicinal product, 14–15
  - Medical electronics, 1
  - Medical Implant Communication Service (MICS), 44

- Medicinal product, 14
  - Membrane potential
    - cell's interior and exterior regions, 22
    - definition, 22
    - different phases, 22, 23
    - fluids, 22
    - ion concentrations, 22, 24
    - ionic population, 24
    - sodium–potassium exchange pump, 24
    - transference, 22
  - Memory design artifices, 73–76
    - sense amplifiers (*see* Sense amplifiers)
    - soft errors, 76
  - Memory storage
    - computer programs, 47
    - NVM, 47
    - RAM, 47
    - ROM, 48
    - volatile memory, 47
  - MEMS. *See* Microelectromechanical system (MEMS)
  - MEMS technology-enabled microelectrode arrays, 18
  - Metallic biomaterials
    - biodegradable metals, 160
    - cleaning and sterilization, 159
    - CoCrMo alloy, 158
    - corrosion, 158–159
    - metal process, 159
    - stainless steel, 158
    - surface coating, 159
    - surface treatment, 159
    - titanium, 158
  - Microcontroller-based pulse generator
    - active signal shapers, 148
    - amplitude entering function, 147
    - ARM processor, 142
    - DAC, 147
    - digipots, 148
    - digital potentiometers, 147
    - DVS, 143
    - EIA, 145
    - FET-based methods, 148–149
    - frequency division, counters, 145–146
    - in-circuit serial programming, 145
    - internal timer/counter, 145
    - keyboard and display controls, 144
    - output amplifier, 148
    - power consumption, 148
    - RDAC, 147
    - resistive step attenuators, 147
    - RISC architecture, 142
    - RS-232 interface, 145
    - sliding/rotary potentiometer, 147
    - specifications, 143
    - square wave, utilitarian dependability, 145
    - user interfaces, 144
    - voltage amplitude, 147
    - voltage-regulating circuit, 148
    - wave shaping circuits, 148
  - Microelectrode arrays, 379, 387, 398
  - Microelectromechanical systems (MEMS), 20, 429
  - Microphone, 385, 387, 389
  - Microprocessor, 46
    - monolithic chip, 51
  - Micropumps, 427–433
    - active
      - electrochemical principle, 433
      - electrostatic principle, 431
      - MEMS, 429, 430
      - piezoelectric principle, 432, 433
      - thermal principle, 433
    - passive
      - osmotic principle, 427, 428
      - spring-powering principle, 428
  - Microreservoir-based IDDSs
    - actively driven devices, 425, 426
    - passive devices, 424, 425
  - Modulo-8 counter/MOD-8 counter, 145
  - Modulo-256 counter/MOD-256 counter, 146
  - Monophasic defibrillator, 83, 84
  - Monopolar electrode, 81–83
  - Monostable multivibrator, 118
    - flip-flop, 117
    - frequency division, 124
    - initial state, 117
    - missing pulse detection, 124–126
    - timer circuits, 117
    - timer/time delay function, 122–124
    - timing cycle, 117
    - triggered state
      - metastable, 118
      - stable, 118
    - waveforms, 124, 125
  - MOS current mirror, 94, 95
  - Multifarious provincial pain syndrome, 339
  - Multivibrators, 116
    - astable, 118–119
    - bistable, 119–120
    - logic gates, 116–120
    - monostable, 117–118
- N**
- NAND flash memory, 48
  - NAND gate, 58, 59
  - NAND-type memory, 48
  - Nasal method, 410

- Natural and artificial pacemakers
  - AV node, 268
  - blood flows, 269
  - choked/clogged up, 269
  - collar bone, 269
  - epicardium, 269
  - heart muscles, 268
  - SA node, 268
  - ventricles, 268
- Negative-bias temperature instability (NBTI)
  - diffusion phase, 64
  - P-channel MOSFET, 63, 64
  - P-channel transistors, 63
  - R–D model, 64
- Neural amplifier circuits, 237–239
  - biopotential amplifier, 229
  - bio-signal recording system, 229
  - CMOS amplifiers, 229
  - low power consumption, 229
  - zero-drift amplifiers
    - charge injection, 239
    - DC errors, 237
    - decibels (dB), 239
    - flat-band noise, 238
    - higher power dissipation, 238
    - intermodulation distortion, 239
    - nanovolt level, 237
    - thermal drift, 238
- Neuromodulation. *See* Deep brain stimulation (DBS)
- Nitric oxide synthases (NOS), 258
- NMOS transistors, 56
- Noise. *See* CMOSFET noise sources
- Noninvasive device, 16
- Nonresonant coupling, 35
- Non-sinusoidal oscillator, 110
- NOR gate, 58, 59
- NOS. *See* Nitric oxide synthases (NOS)
- NOT gate/inverter, 58
- N- and P-channel devices, 61
- N-well CMOS, 56, 57
- Nyquist rate, 47
  
- O**
- Obesity, 350
- Obsessive–compulsive disorder (OCD), 325–326
- OFC. *See* Orbitofrontal cortex (OFC)
- One-shot multivibrator, 117
- Operational amplifier (OP-AMP), 49, 50
- Operational transconductance amplifier (OTA)
  - CMOS, 240
  - OP-AMP, 240
  - vs. operational amplifier, 242
  - transconductor, 240
- Oral method, 410
- Orbitofrontal cortex (OFC), 349
- Oscillators
  - crystal-based CMOS square wave, 114–116
  - feedback, 110
  - linear and nonlinear, 110
  - non-sinusoidal, 110
  - piezoelectric and inverse piezoelectric effects, 111
  - RC, 112–114
  - register, 110
  - relaxation, 110
- Oscillatory current, 36
- Osmotic pump, 427, 428
- Overactive bladder syndrome, 367
  
- P**
- Pacemaker architecture
  - error-free style, 286
  - hardware variations, 285
  - self-testing routines, 286
  - wireless control, 285
- Pacemaker codes
  - chamber paced and sensed, 278
  - electrophysiology, 279
  - fifth letter* (position V), 280
  - The first letter* (position I), 279
  - fourth letter* (position IV), 280
  - second letter* (position II), 279
  - third letter* (position III), 279, 280
- Pacemaker electronics evolution, 283–285
  - miniaturization
    - building blocks, 284
    - CMOS, 285
    - EMI, 285
    - microns, 284
    - passive components, 284
  - pulse generators
    - heart chamber, 283
    - output circuit, 283
    - power source, 284
    - sensing amplifier, 283
    - telemetry circuit, 284
    - timing circuit, 283, 284
    - timing intervals, 283
- Pacemaker implantation
  - absent pulse, 282
  - electrical pulses, 282
  - pulse generator, 282
  - stimulus, 282
  - thoracotomy, 282

- Pacing leads and connectors, 288
  - construction and design
  - cardiac muscles, 288
  - corticosteroid, 288
  - electrode porous, 288
  - endocardial leads, 288
  - lead components, 288
  - fixation mechanisms, 288
  - materials, 289
- Pacing system, 361–363
- Pallidotomy, 314
- PAM. *See* Pulse amplitude modulation (PAM)
- Parabrachial nucleus (PBN), 349
- Parallel ADCs, 89
- Parasympathetic nervous system, 343
- Paresthesia, 332
- Parkinson's disease (PD)
  - basal ganglia, 311
  - dopamine deficiency, 312
  - dopaminergic neurons, 311
  - levodopa, 312
- Passive charge balancing, 104
  - blocking capacitor, 103–104
  - short-circuiting of electrodes, 104
- Passive implantable devices, 17
  - and active (*see* Active implantable devices)
- Passive phase-shift keying, 201
- Passive telemetry, 192–193
- PBN. *See* Parabrachial nucleus (PBN)
- PEEK. *See* Polyetheretherketone (PEEK)
- Phase-shift keying (PSK), 193, 196, 203–204
- Phase-shift oscillator, 112
- PHM. *See* Pulse harmonic modulation (PHM)
- Photovoltaic effect, 399
- Pierce design, 114
- Piezoelectric and inverse piezoelectric effects, 111
- Piezoelectric pump, 432, 433
- Pink noise, 65
- PMOS transistors, 56
- Poisson noise, 66
- Polyetheretherketone (PEEK), 162
- Polyvinylidene difluoride (PVDF), 162
- Popcorn/burst noise, 67
- Posterior column stimulation, 331
- Power saving, 43
- Power supply, 37
  - DC-to-DC converters, 139
  - electrical noise, 139
  - input conditioning stage, 140
  - output level and polarity control stage, 140
  - sensing circuit, 139
  - signal conditioning, 139
  - stimulus current, 139
  - voltage augmentation and isolation stage, 140
- Power-supply rejection ratio (PSRR), 238
- Programmability & telemetry
  - counters, 286
  - pulse amplitude, 286
  - tachycardia events, 286
- Programmable ROM (PROM), 48
- Progressive supranuclear palsy, 316
- PSK. *See* Phase-shift keying (PSK)
- PSRR. *See* Power-supply rejection ratio (PSRR)
- Pull-down network (PDN), 56, 58
- Pull-up network (PUN), 56, 58
- Pulmonary method, 410, 412
- Pulmonary systems, 19
- Pulse amplitude modulation (PAM), 130, 131
- Pulse generators, 135–138
  - digital/analog techniques, 139
  - electrical pulse and pulse parameters
    - amplitude droop, 138
    - digital pulses, 135
    - double pulse delay, 138
    - ideal pulses, 136
    - jitter, 138
    - linearity, 137, 138
    - overshoot, 138
    - preshoot, 138
    - pulse delay, 138
    - pulse levels, 136
    - pulse period, 136
    - pulse width, 137
    - repeatability, 138
    - ringing, 138
    - stability, 138
    - trigger delay, 137
    - voltage/current, 135
    - wave shapes, 136
    - waveform, 136
  - electronic equipment, 138
  - power supply, 139
  - pulse timing control unit, 139
  - square waves, 138
- Pulse harmonic modulation (PHM), 201–202
- Pulse position modulation, 131–132
- Pulse timing control unit
  - LCD/PC, 140
  - microcontroller-based pulse generator, 140, 141
  - timer IC-based pulse generator, 140, 141
- Pulse-width modulation (PWM), 125–127
- PVDF. *See* Polyvinylidene difluoride (PVDF)
- P-well CMOS, 56, 57
- PWM. *See* Pulse-width modulation (PWM)

**Q**

*Quasi-/soft breakdown*, 62

**R**

R/2R ladder DAC, 86, 88, 89  
 Radio charging, 191  
   safety limits  
     FDTD technique, 191  
     high frequencies, 191  
     numerical/experimental methods, 191  
     power losses, 191  
     RF waves, 191  
     SAR, 191  
   transmission and reception, 190  
 Random access memory (RAM), 47, 48  
 RDAC. *See* Digital pot/digipot/resistive digital-to-analog converter (RDAC)  
 Reaction–diffusion (R–D) model, 64  
 Read circuitry, 73  
 Read-only memory (ROM), 48  
 Rectifier, 37  
 Reduced instruction set computer (RISC), 142  
 Reflectance modulation, 196  
 Reflex sympathetic dystrophy (RSD), 332  
 Refractory epilepsy, 342  
 Relaxation oscillator, 110  
 Resistance–capacitance (RC)  
   inverting amplifier, 112  
   OP-AMP, 113  
   phase-shift oscillator, 112  
   positive feedback, 113  
   square wave generator, 113  
 Resonance charging, 190  
 Resonance frequency, 35  
 Resonant coupling, 35  
   resonance frequency, 35  
   wireless power transmission system, 35  
 Respiration, 356  
 Resting potential, 24  
 Retinal implant  
   epiretinal, 401–405  
   subretinal device, 398–400, 404–405  
 Retinal prosthesis, 394–398  
   alpha IMS retinal implant, 403, 406  
   argus II retinal system, 403  
   implant (*see* Retinal implant)  
   optimal candidates, 406  
   remedial schemes and vision impairment  
     age-related macular degeneration, 397  
     electrical stimulation, 397, 398  
     retinitis pigmentosa, 397  
   restoration, 393

## vision

  amacrine cells, 396  
   bipolar cells, 396  
   cones, 396  
   ganglion cells, 394  
   horizontal cells, 396  
   inverted image construction, 394  
   nerve layer, 394, 395  
   neuroprocessor, 394  
   rods, 396

Retinitis pigmentosa, 397  
 RF communications circuitry, 51  
 Rheumatoid arthritis, 350  
 RISC. *See* Reduced instruction set computer (RISC)  
 RSD. *See* Reflex sympathetic dystrophy (RSD)

**S**

Sacral nerve stimulation (SNS), 373–376  
   bladder control, 367, 370, 371  
   characterization, 371  
   CISC, 371  
   diagnosis and suitability, 372, 373  
   factors, 371  
   implantation procedure  
     components, 373  
     electrical stimulation therapy, 373, 374  
     minimally invasive screening test, 375  
     neurostimulator and thin, 373  
     permanent, 375, 376  
     stages, 376  
   mechanism, 370  
   organs, 369  
   patients, 367  
   pelvic disorder symptoms, 370  
   pelvic floor disorders, 371  
   pulse delivery, 369  
   SNM, 369  
   spinal nerves, 368  
   stimulation parameters, 376  
   types, signals, 368  
   UI, 371  
   urinary dysfunction, 370  
   urinary retention/ischuria, 371  
   urinary system, 370, 371  
   urological practice, 372  
 Sacral neuromodulation (SNM), 369  
 SAR. *See* Specific absorption rate (SAR)  
 SAR ADC, 90, 91  
 SCD. *See* Sudden cardiac death (SCD)  
 SCS. *See* Spinal cord stimulation (SCS)

- Secondary coil, 37
- Self-driven synchronous rectifier (SDSR), 44
- Sense amplifiers
  - analog circuit, 73
  - charge transfer, 76
  - crucial to memory function, 73
  - current-mode, 75–76
  - hazy logic levels, 73
  - memory cell, 73
  - read circuitry, 73
  - voltage-mode, 74, 75
- Sensorineural hearing loss, 381, 382
- Sensors, 253–262
  - accelerometers, 251, 253
  - artificial pancreas concept
    - diabetes, 259, 260
    - infusion pumps, 260
    - metabolite sensors, 259
  - biosensors
    - analyte molecules, 255
    - enzyme stability, 257
    - fine-grained matrix, 256
    - mass transfer, 255
    - oxygen shortfall, 256–257
    - vivo sensor operation, 255
  - blood gas sensors
    - blood clots, 258
    - cardiopulmonary function, 257
    - catheter-type sensor, 257
    - electrochemical and optical techniques, 258
    - endothelial cells, 258
    - Pfizer/biomedical sensors, 258
    - potentiometric devices, 258
    - triggering, 258
    - vasodilator, 258
  - capacitive pressure sensors, 251, 252
  - drift-free, 249
  - glucose biosensor
    - angiogenic layer, 261
    - bioprotective membrane layer, 261
    - O-ring, 261
  - inflammation sensor
    - NO detection, 262
    - PEG, 262
  - piezoresistive pressure sensors, 250
  - SAW sensors
    - diaphragm, 253
    - oscillating circuit, 254
    - RF power converter, 254
    - wireless communication, 255
  - wheatstone bridge circuit, 250
- Short-channel effects
  - CMOSFETs, 77
  - DIBL, 68
  - drain-induced barrier lowering, 70
  - hot carrier effects, 70
  - mobility degradation, 70
  - MOSFETs, 68, 69
  - punchthrough, 70
  - threshold voltage reduction, 70
  - velocity saturation, 70
- Short-circuiting of electrodes, 104
- Shot noise, 66, 67
- Silver vanadium oxide battery, 177
- SNM. *See* Sacral neuromodulation (SNM)
- SNS. *See* Sacral nerve stimulation (SNS)
- Soft errors, 76
- Spatial resolution, 396
- Specific absorption rate (SAR), 191
- Speech processor, 385, 386
- Sphincter muscle, 370
- Spinal cord stimulation (SCS), 334–336
  - adenosine A-1 receptors, 338
  - analgesic method, 331
  - anesthesia, 332–334
  - anti-ischemic and antianginal
    - characteristics, 338
  - antinociceptive (anti-pain) effects, 338
  - back pain, 339
  - chronic pain, 331
  - CRPS, 339
  - DCS, 331, 332
  - dorsal horn, 337
  - epidural space, 332–334
  - FBSS, 339
  - GABA-B, 338
  - gating, 337
  - GCT, 337
  - hardware and electrodes
    - axonal activation, 336
    - cathode, 334
    - cerebrospinal fluid, 335
    - electrical steering, 336
    - electrical stimulation, 334
    - laminotomy/partial laminectomy, 336
    - paresthesia distribution, 336
    - pulse generator, 334
    - Tuohy needles, 336
    - unipolar electrodes, 335
    - values, 334
    - vertebral bone, 335
  - implantable power sources, 336–337
  - indications, 338–339
  - neuromodulation, 332
  - orthodox and surgical treatments, 332
  - paresthesia, 332
  - RSD syndrome, 332

- Static RAM (SRAM), 47, 48
  - Step-up converter, 98
  - Sterilization, 420
  - Stress-induced leakage current (SILC), 62, 63
  - Submicron transistors, 65–67
    - CMOSFET noise sources (*see* CMOSFET noise sources)
    - NBTI, 63, 64
    - quasi-/soft breakdown, 62, 63
    - SILC, 62, 63
  - Subretinal implant
    - advantages, 400
    - limitation, 400
    - microphotodiodes, 398, 400
    - photoreceptor cells, 398
    - silicon photodiode, 399, 400
  - Subthalamic nucleus (STN), 315, 317, 320
  - Subthalamotomy, 314
  - Sudden cardiac death (SCD), 293
  - Surface model/carrier number fluctuation model, 65
  - Switched-biasing amplifier
    - bandwidth, 231
    - charge trapping and de-trapping, 230
    - gate biasing voltage, 230
    - MOS transistor, 231
    - MOSFET, 232
    - off-state operation, 230
    - on-state operation, 230
    - switching/cycling, 230
  - Switched-capacitor-based stimulation, 102
  - Switch-mode power supply (SMPS), 39–41
  - System-on-chip (SoC), 60
- T**
- Teleactuation, 32
  - Telemetry, 31, 32
  - Thalamotomy, 314
  - Thermal/Johnson–Nyquist noise, 65
  - Thoracic diaphragm, 356
  - Thoracotomy, 363
  - Timer circuit, 99
  - Timer IC-based pulse generator, 141–142
  - Timer ICs
    - astable mode, 120, 126–130
    - bistable mode, 120
    - block diagram, 121–122
    - building block approach, 120
    - control and generation of pulses, 120, 121
    - monostable mode, 120 (*see also* Monostable multivibrator)
    - PAM, 130, 131
    - pin diagram, 121, 122
    - pulse position modulation, 131–132
    - PWM, 125, 126
  - Timing circuits. *See* Timer ICs
  - Tined lead, 375
  - Tissue response modifiers (TRMs), 256
  - Tonotopy, 384
  - Transceiver, 36
  - Transconductance amplifier, 94
  - Transdermal method
    - advantages, 412
    - limitations, 413
  - Transference efficiency, 35
  - Transistor models
    - implantable electronics, 71
  - Trapping mechanisms, 65
  - Tremor
    - description, 312
    - propranolol, 313
    - traumatic brain injury, 312
  - TRMs. *See* Tissue response modifiers (TRMs)
  - Twin-tub CMOS, 56, 57
- U**
- Ubiquitous health monitoring (UHM), 222
  - UHM. *See* Ubiquitous health monitoring (UHM)
  - Unipolar and bipolar stimulation
    - anode, 271
    - cathode, 271
    - current threshold, 272
    - pulse generator, 271
    - signal-to-noise ratio, 272
    - voltage threshold, 272
  - Universal Software Radio Peripheral (USRP), 216
  - Urinary incontinence, 371, 372
  - Urinary system
    - bladder filling, 370
    - communication, 371
    - components, 370
    - sphincter muscle, 370
  - USB port, 36
  - USRP. *See* Universal Software Radio Peripheral (USRP)
- V**
- Vagus nerve stimulation (VNS)
    - afferent, 345
    - antidepressant, 348–349
    - brain neurotransmitters, 345
    - cranial nerves, 343, 344
    - depression, 348

- drawbacks, 349
  - effluent, 345
  - electrical signal generator, 346
  - electrodes, 347
  - epileptic seizures, 341–342
  - extracranium, 341
  - heart failure and fibromyalgia (rheumatic condition), 343
  - implantation, 346–348
  - innocuous and effectual subordinate method, 351
  - limbic system, 344
  - magnetic transducer (wand), 347
  - mixed nerve, 345
  - obesity treatment, 350
  - parasympathetic nervous system, 343
  - refractory seizures, 342
  - rheumatoid arthritis, 350, 351
  - thoracic and abdominal viscera, 343
  - visceral organs, 343, 345
  - wandering, 343
  - Voltage multiplier, 96–98
  - Voltage regulator
    - bandgap reference circuit, 38
    - bandgap voltage reference circuit, 40–43
  - EMI, 38
    - linear, 38, 39
    - SMPS, 39–41
  - Voltage source, 92, 93
  - Voltage-controlled current source (VCCS), 94
  - Voltage-controlled stimulation (VCS), 101, 103
  - Voltage-mode sense amplifier, 74, 75
  - Voltage-mode stimulation, 101–102
  - Voltage-to-current converter (VIC), 94–96
- W**
- Wireless charging, 186–188
  - Wireless communications. *See also* Inductive charging
    - percutaneous leads, 186
    - powering implants, 186–188
    - wireless charging, 186–188
  - Wireless power transmission system, 35
- Z**
- Zener-type leakage, 61
  - Zero-order controlled release, 417