

# Index

## A

- AC impedance spectroscopy (IS)
  - CPE2 models, 693
  - ionic conductivity, 694–696
  - program LEVMW, 693
  - temperature, 693
  - VTF equation, 694–695
- 2-acrylamido-2-methylpropane sulfonic acid (AMPS), 653
- Acrylic fatty acid copolymers (AcFAs), 637
- Adhesion
  - corrosion failure, 606
  - definition, 605
  - destructive methods, 611–612
  - enhancement, 609–610
  - factors, 608–609
  - mechanisms, 606–607
  - nondestructive methods
    - assessing and predicting, 612
    - capability, 612
    - infrared spectroscopy, 613, 614
    - JKR theory, 614
    - ultrasonic analysis, 613
    - X-ray radiography and shearography, 614
- Adsorption heat pumps
  - adhesion tests, 673
  - electrochemical performances, 674–676
  - impact test, 674
  - materials and testing, 668–669
  - morphology, 669, 671, 672
  - research and development activity
    - AdHex unit, 663
    - adsorptive cooling cycle, 663
    - AQSOA, 663
    - DDZ70, 662
    - dip-coating methods, 664
    - issues, 665
    - ITAE, 666
    - matrix and pore-filling, 663
    - MOFs, 663
    - multistage cycles, 666
    - optimal adsorption, 662
    - sale-up, 664
    - thermal wave cycles, 665
    - thermogravimetric technique, 663
  - silane-zeolite coatings
    - alkyl chain, 668
    - closed-cycle systems, 667
    - dip-coating methods, 667
    - heat exchanger, 676
    - silane matrix, 667
    - silica-aluminate structure, 667
    - 3D structures, 667
    - thermally driven machines, 660–662
    - wettability tests, 672–673
- Amphiphilic invertible polyesters (AIPes), 403–404
- Amphiphilic invertible polymers (AIPs)
  - AIPes, 403–404
  - AIPUs, 401
  - fibrillar carbon nanostructures, 414
  - hybrid sorbents, 401
  - lipophilic and hydrophilic fragments, 400
  - metal nanoparticles
    - gold, 408
    - hydroxyl moiety, 406
    - nonpolar organic solvents, 405
    - palladium, 409
    - PEG units, 406
    - PEO formation, 405

- Amphiphilic invertible polymers (AIPs) (*cont.*)  
 self-assembly, 410  
 silver, 405, 406, 408  
 XRD technique, 406  
 oxygen atoms, 400  
 semiconductor nanoparticles, 411–414
- Amphiphilic invertible polyurethanes (AIPUs), 401
- Anticorrosion application  
 AFM, 391, 392  
 aspect ratio, 374  
 electrochemical techniques, 392  
 fabrication  
 in situ polymerization, 383  
 melt intercalation, 383  
 solution exfoliation, 383  
 surface modification, 384  
 helium ion microscopy, 392  
 microstructure, 376–377  
 polymer nanocomposite  
 advantages, 385  
 design and synthesis, 384  
 inorganic shells, 386  
 LDH, 388  
 nanocapsules, 386, 388  
 nanovalves, 386  
 polymeric layers, 386  
 polymeric coatings  
 glass transition temperature, 382  
 interfacial region, 382  
 mechanisms, 381  
 polymer matrix, 381  
 porosity and zigzagging, 377  
 SEM, 388  
 TEM, 388
- Antireflective (AR) coatings, 35, 36
- Aptamers  
 gated pores  
 DNA robot, 195  
 molecular actuators and transducers, 191  
 porous anodic aluminum oxide, 192  
 sensing applications, 192  
 target-derived payload delivery, 193  
 hydrogels  
 Boolean logic operations, 191  
 cargo release, 187, 190  
 cross-link polyacrylamide monomers, 187  
 DNA segments, 190  
 rhodamine-labeled liposomes, 187  
 tissue engineering applications, 187  
 microcapsules, 195, 197
- Atom transfer radical polymerization (ATRP)  
 alkyne end-functionalized polymers, 287  
 azide end-functionalized polymers, 286–287  
 chain-end-functionalized polymers, 273  
 covalent bond formation, 276  
 design of, 273  
 diene-/dienophile-functionalized polymers, 287–289  
 encapsulation method, 278  
 ene-containing polymers, 289–290  
 functional groups, 273  
 functional polymers, 272  
 mechanisms, 274  
 microparticle preparation, 585  
 non-covalent bond formation, 274–276  
 semi-encapsulation methods, 277, 278  
 thiol-containing polymers, 289
- ATP-dependent delivery of gold nanoparticles (AuNPs), 187
- Attenuated total reflectance (ATR) spectroscopy, 685
- B**
- Barzic model, 359
- Benzotriazole (BTA), 528
- Bioactive polymers  
 bionanotechnology, 180  
 drug delivery, 181  
 natural polymers  
 anticoagulant activity, 169  
 antidiabetic activity, 171  
 anti-inflammatory activity, 171  
 antimicrobial activity, 171, 172  
 antioxidant activity, 169, 170  
 antitumor activity, 167, 169  
 antiulcer activity, 172  
 biochemicals, 177  
 blending, 179  
 carrageenan, 172  
 demineralization and remineralization, 173  
 drug delivery, 176, 177  
 electric field, 178  
 fucoidan, 173  
 ion response, 179  
 temperature, 177, 178
- Biscrolling technique, 465
- Bottcher model, 359
- Bulk heterojunction (BHJ), 246
- C**
- Capacitors. *See* Energy storage devices
- Chemical warfare agents (CWAs)  
 advantages, 554  
 classification, 555

- conjugated/conductive polymers, 556–558
  - dansyl and nitrobenzofurazan fluorophores, 560
  - development, 554
  - DMMP, 560
  - MIPs, 558
  - nerve agents, 555
  - remote/standoff monitoring, 556
  - sensor array, 559–560
  - Chondroitin sulfate (CS), 171
  - Click chemistry
    - characteristics, 279
    - CuAAC, 282, 284, 587
    - DA reaction, 279, 281
    - mild reaction conditions, 278
  - Conductive inkjet printing, 443–444
  - Conductive textiles
    - biscrolled conductive fibers, 446
    - carbon nanotube fibers, 445
    - dip-dry coating, 443
    - ECPs, 442, 443, 445
    - electroless plating, 441
    - evaporative deposition, 441
    - inkjet printing, 443–444
    - knitting and weaving, 445
    - Nanoink, 443
    - screen printing, 444–445
    - sputtering, 441
    - twisted conductive fibers, 445
    - welded conductive fibers, 446
  - Controlled radical polymerization (CRP), 584
  - Copper catalyzed alkyne–azide cycloaddition (CuAAC), 587
  - Corrosion protection
    - active protection, 418
    - anionic materials
      - AA2024 samples, 422
      - chloride concentration, 421
      - comprehensive model, 421
      - drawbacks, 424
      - hydroxide layers, 421
      - LDH, 421
      - LDHs, 422, 423
      - Mg–Al hydrotalcite conversion, 423
      - MoO<sub>4</sub><sup>2-</sup> ions, 423
    - cationic materials
      - aqueous solution, 425
      - cation-exchange properties, 424
      - intrinsic characteristics, 425
      - montmorillonite, 424
      - salt spray test, 424
      - sol–gel films, 425
      - zeolites, 425
    - intermetallic particles, 418
    - mechanical damage, 419–420
    - mechanisms, 429–432
    - pH changes
      - 2-(benzothiazol-2-ylsulfanyl)-succinic acid, 428
    - feedback coating, 429
    - halloysite, 428
    - healing effect, 429
    - layer-by-layer technique, 427
    - loading capacity, 428, 429
    - metallic oxidation, 426
    - polyelectrolytes, 427
    - storage/release, 429
    - SVET, 427
  - self-healing coatings (*see* Self-healing coatings)
  - sol–gel technology, 418
  - World Corrosion Organization, 418
  - Cover factor, 125
  - Cu (I)-Catalyzed Azide–Alkyne Cycloaddition (CuAAC), 282, 284
  - CWAs. *See* Chemical warfare agents (CWAs)
- D**
- Dess–Martin periodinane method, 641
  - Diels–Alder (DA) reaction, 279, 281
  - Differential expansive bleeding (DEB), 589
  - Differential scanning calorimetry (DSC), 317, 685, 690, 691
- E**
- EAPs. *See* Electroactive polymers (EAPs)
  - Electrically conducting polymers (ECPs)
    - carbon cloth, 459–460
    - challenges, 459
    - CNT, 461, 462
    - conductive textiles, 442, 443, 445
    - discovery, 453
    - external surface area, 453
    - graphene, 460–461
    - PANI, 454–455
    - polypyrrole, 455–458
    - polythiophene, 458
  - Electroactive coatings (EACs), 79–80
  - Electroactive polymers (EAPs)
    - adsorption, 67
    - application, 68
    - artificial muscles, 78
    - bioactivity, 68
    - biomimetic sensors, 72
    - classification, 54, 55

- Electroactive polymers (EAPs) (*cont.*)  
 controllable delivery devices, 69, 70  
 covalent binding, 68  
 dielectric properties, 55, 57  
 doping process, 62, 68  
 electropolymerization process, 60  
 entrapment, 68  
 hydrogels  
   composition, 64  
   drug delivery approaches, 65  
   IPNs, 66  
   performance of, 65  
   transport of ions, 65  
   versatility, 65  
 medical devices, 72  
 nanocomposites, 74–76  
 PANi, 57, 60  
 properties, 67  
 redox reactions  
   chronoamperometry, 64  
   cyclic voltammetry, 63  
   impedance spectroscopy, 64  
   linear sweep voltammetry, 63  
   reduction reversibly, 63  
   swelling/deswelling and  
     electroactivity, 63  
 SMPs, 77  
 water-soluble polymers, 71, 72
- Electrochemical double-layer capacitors  
 (EDLCs), 450, 451
- Electroless plating technique, 441
- Emulsion polymerization, 257, 580, 581, 584,  
 626, 636
- Energy storage devices  
 conventional capacitors, 446–449  
 electrochemical capacitors  
   asymmetric hybrids, 452  
   battery-type hybrids, 452  
   composite electrodes, 451  
   EDLCs, 450, 451  
   pseudocapacitors, 451  
   supercapacitors, 449–450
- E-textiles, 125
- Evaporative deposition techniques, 441
- Explosives (EXs)  
 amplification, 567  
 chemoselective polymers, 566  
 classification, 560  
 conductive polymers  
   fluorescence technique, 562  
   multiphoton excitation, 563  
   pentiptycene, 562  
   polymetallole films, 564  
   polysilanes, 564  
   polythiophenes, 564  
   pyrene, 563  
   rigid structure, 564  
   taggants, detection, 564  
   TNT and RDX, 564  
   trace detection, 564  
 fingerprint residues, 567  
 fluorescence quenching, 567  
 forensic and criminal investigations, 554  
 hydrogen peroxide, 568  
 hyperbranched structures, 567  
 MIPs, 565–566  
 PEG polymer coating, 566–567  
 sensitivity, 568  
 sensor array, 566  
 trace detection, 568  
 vapor detection, 560  
 visual sensing, 567
- F**
- Faradaic and non-Faradaic processes, 451
- Food safety  
 active and smart films, 254, 255  
 antioxidant carbohydrate films  
   characterization, 261, 263  
   food waste reduction, 261  
   lipid oxidation, 261  
   synthetic antioxidants, 261  
 mechanical properties, 259  
 microencapsulation, 265, 266  
 microparticle charge, 260  
 microparticle preparation, 256, 257  
 microparticle size, 260  
 morphological characterization, 258  
 spectroscopy characterization, 258  
 thermal characterization, 259
- TTI  
 film characterization, 265  
 real-time indication, 264  
 water and humidity, 259, 260
- Förster resonance energy transfer (FRET), 623
- Fourier Transformed Infrared Spectroscopy  
 (FTIR), 315
- Freeze drying method, 257
- Fricke model, 358
- G**
- Giordano model, 360
- Gold nanoparticles (GNPs)  
 aptamer hydrogels, 187  
 IPN, 366  
 smart polymers, 17, 18

**H**

High-performance coatings. *See* Waterborne coatings

Hot-dipped galvanized steel, 502–503

**I**

Impedance spectroscopy (IS), 685, 693–695

Interpenetrating polymer networks (IPNs)

electrical active systems, 368

magnetic-active, 368

photosensitive polymers, 367

pH-responsive nanocomposites, 367

thermosensitive nanocomposites, 366–367

**J**

Johnson-Kendall-Roberts (JKR) theory, 614

**K**

Kirkpatrick model, 360

**L**

Layered double hydroxides (LDHs), 388, 421, 527

Lewis–Nielsen model, 358

Lichtenecker model, 360

Linear sweep voltammetry (LSV), 244

Liposome method, 257

Lower critical solution temperature (LCST), 3

**M**

Mamunya model, 361

Maxwell–Eucken model, 358

Maxwell–Wagner model, 361

Melt intercalation method, 383

Mesoporous silica

chemotherapy, 16

classifications, 15

controllable drug delivery system, 17

ill effects, 16

macromolecular dissociation, 17

materials

biomedical devices, 43

drug loading capacity, 39, 41

gene delivery, 41, 42

long-chain hydrocarbon

octadecyltrimethoxysilane, 41

reductive-responsive disulfide, 41

nanogates, 15

nanomedicine, 15

pH-response, 17

surface attachment, 16

Microencapsulation

chemical and physical/mechanical, 580

coacervation/phase separation, 581

co-extrusion process, 583

emulsion polymerization, 580

fluidized bed coating, 583

interfacial polycondensation, 580

layer-by-layer deposition, 583

microspheres, 578

monocored, polycored, and matrix, 579

polymer precipitation, 583

polymeric microparticles, 579

production, 578

shell morphology, 580

smart materials, 578

smart polymers

alkoxyamine's isolation, 586

amphiphilic polymer, 585

ATRP, 585

colloidal stabilizers, 584

CRP, 585

CuAAC reaction, 587

emulsions, 584

nanoparticles, 584

NMP, 586

PEG reaction, 586

RAFT, 585–586

t-butyl groups, 585

solvent evaporation/extraction, 581

spinning disk technique, 584

spray drying, 581, 583

stimuli-responsive polymers

anode and adjoining areas, 597

biologically responsive polymer, 593

controllable alteration/modification, 596

drug carriers, 593

gelling ability, 593

glucose-responsive polymers, 593

intrinsically hydrophobic multilayers, 596

light-sensitive polymers, 596

PCM, 590–593

pharmaceutical and biological  
therapeutics, 593

phase transition, 596

pH changes, 595

pH regions and gradients, 596

pH sensitivity, 597

polybases bearing, 595

self-healing agents

(*see* Self-healing agents)

synthetic materials, 594

thermo-sensitive polymers, 594, 595

- Microencapsulation (*cont.*)  
 supercritical fluid technique, 584  
 suspension cross-linking, 581
- Molecularly imprinted polymers (MIPs), 558, 565–566
- Multifunctional materials  
 biodegradable polymer composite, 349–350  
 biotechnology  
 biocompatibility and biosafety, 347  
 biosensor sensitivity, 347  
 diagnosis, 346  
 drug molecules, 346  
 iron oxide, 346  
 rapid identification, 347  
 superparamagnetism, 345, 346  
 drug and diagnostic agents, 338  
 gold nanostructures, 342–343  
 metallopolymers, 348  
 polymeric micelle, 339–340  
 polymeric microcapsules, 340–342  
 polymer–polyelectrolyte complex, 343–345
- N**
- Nan model, 359
- Natural fiber welding, 446
- Nitroxide-mediated polymerization (NMP)  
 reaction, 156, 157, 586
- N*-methylolacrylamide (NMA), 627, 628, 634
- O**
- Oil industry, 43, 44
- Optical sensors  
 advantages, 539  
 chemical information, 538  
 classes, 538  
 components, 538  
 disadvantages, 540  
 effective strategy, 539  
 performance features, 539  
 principles, 539  
 sol-gel method  
 ammonia and nitrogen dioxide, 546  
 characteristics, 542  
 complementary techniques, 544  
 compound incorporation, 541–542  
 Coumarin 1, 549  
 diversity, 541  
 double layer film, 548  
 encapsulation, 542, 544  
 food industry, 550  
 hydrophobicity, 545  
 indicator-matrix interaction, 545  
 ions, detection, 547  
 O<sub>2</sub> and CO<sub>2</sub>, 549  
 organosilanes bearing, 544  
 ORMOSIL sensing, 546  
 performance evaluation, 544  
 pH indicators, 543, 548  
 pH monitoring, 550  
 process, 540  
 smart coatings, 549  
 textural modification, 545  
 VOCs, 548  
 transducers, 538
- P**
- Phase-change materials (PCM), 590–593
- Piezospectroscopy (PS)  
 alumina  
 carbon nanotubes, 93  
 elastic properties, 96  
 load transfer, 95  
 material configuration, 94  
 multiscale mechanics, 96  
 reinforced composites, 93, 94  
 stress measurement, 94, 95  
 stress sensitivity, 95  
 tribological properties, 93  
 data collection, 100, 101  
 fiber optics, 100  
 open-hole tension testing, 97–99  
 optical emissions, 92
- Polyaniline, 130, 454–455
- Polymer nanocomposites  
 characterization, 356  
 classification, 356–358  
 dielectric constant, 359–360  
 electrical active systems, 368  
 electrical conductivity  
 Kirkpatrick model, 360  
 Mamunya model, 361  
 Maxwell–Wagner model, 361  
 magnetic-active polymers, 368  
 microstructure evaluation  
 electron tomography, 364  
 mechanical tests, 365  
 microscopy, 363–364  
 permeability measurements, 365  
 rheology, 361–362  
 thermal analysis, 366  
 UV-VIS spectrometry, 363  
 X-ray diffraction, 364–365
- PDMA, 367
- photosensitive polymers are, 367

- pH-responsive, 367
  - thermal conductivity
    - Barzic model, 359
    - Fricke model, 358
    - Lewis–Nielsen model, 358
    - Maxwell–Eucken model, 358
    - Nan model, 359
    - Springer–Tsai model, 358
    - Vysotsky model, 359
  - thermosensitive, 366–367
  - Polymer surfaces
    - bio-related applications, 115, 116
    - biosensors, 116
    - immobilization, 106
    - micro- and nanometer-scale topography
      - microcontact printing, 113
      - patterning techniques, 113
      - surface structuring, 112
    - optical sensors, 116
    - phase separation, 106
    - photochemical stimulation, 107
    - pH-sensitive polymers, 106
    - reversible adhesives, 117
    - smart interfaces
      - electroactive polymers, 109
      - graft polymerization/solvent bath, 110
      - multiresponsive surfaces, 111
      - photo-responsive polymers, 109
      - pH-responsive surfaces, 108
      - physisorption, 108
      - surface reorganization, 110
      - temperature-responsive surfaces, 108
    - static electric fields, 108
    - surface wettability control, 114, 115
    - thermoreponsive polymers, 106
    - thermosensitive polymers, 106
    - UCST, 107
  - Poly(oligo(ethylene glycol)-oxalate) (POEGO)
    - ATR spectroscopy, 685
    - attenuated total reflectance, 691, 692
    - DSC, 685, 690, 691
    - Li-POEGO and Li-POEGO–Li-hectorite nanocomposites (*see* AC impedance spectroscopy)
    - lithiation
      - nanocomposites, 684, 685
      - polymer–salt complex, 684
      - sodium hectorite, 684
    - TGA, 685, 688, 690
    - XRD, 685, 686
  - Polypyrrole (PPY), 455–458
  - Polythiophene (PTH), 458
  - Poly(3,4-ethylenedioxythiophene) (PEDOT)
    - absorption peaks, 235
    - active catalysts, 234
    - anticorrosion properties, 232
    - anticonjugated polymers, 232
    - dispersions, 231
    - electrocatalytic properties, 232
    - Goretex membranes, 234, 235
    - light illumination, 235
    - mechanism of, 231
    - recombination reactions, 232
    - thin films, 231
  - Polyurethane (PU)
    - applications, 307, 310
    - chain extenders, 296, 297
    - crystallinity, 294
    - isocyanate, 296
    - polyols, 295, 296
    - shape memory effect
      - chemical/physical cross-links, 299, 300
      - commercial products, 300
      - elastomer, 299
      - petrochemical-based PU, 301, 302
      - phase separations, 297
      - properties, 298
      - renewable resources, 301
      - stimulus types, 299
      - vegetable oil, 303, 307
  - Polyvinylidene fluoride (PVDF)
    - actuators, 325, 326
    - $\beta$ -phase measurement
      - crystalline structures, 318
      - DSC, 317
      - electrical poling, 318
      - FTIR, 315
      - stretching process, 318
      - XRD, 316, 317
    - electric displacement, 321
    - loss in dielectric materials, 323
    - nanogenerators, 326, 328
    - permittivity, 322, 323
    - piezoelectric charge constant, 319, 320
    - piezoelectric properties, 324
    - polarization-electric field, 321
    - polymorphisms, 314
    - sensors, 324, 325
    - voltage response, 320, 321
- R**
- Reversible addition/fragmentation chain transfer (RAFT), 585–586

## S

Scanning electron microscopy (SEM), 388

Self-healing agents

- accelerated crack propagation, 588
- advantage, 589
- aerospace industry, 590
- beneficial features, 589
- bleeding, 589
- cyclic dienes, 588
- cycloaddition reactions, 590
- delicate and brittle polymer, 588
- electrical stimulation, 589
- electrorheological/magnetorheological fluids, 589
- fast and effective execution, 587
- ionic interaction, 590
- magnetic materials, 589
- nanoparticles, 590
- rigidity, 588
- self-repairing composite, 588
- SPM, 588
- stress, 589
- thermal stimuli-responsive material, 588

Self-healing coatings

- definition, 480
- healing agents
  - ceramic pigments, 484
  - microvascular systems, 486
  - nanocontainers, 485
  - nanoparticles, 484
  - sacrificial metal pigments, 484
- inorganic coatings, 481
- layer-by-layer deposition, 486–489
- methods, 490
- organic coatings
  - epoxy resins, 482
  - hybrid coating, 483
  - paints, 483
  - polymers, 482
- repairing agent, 480
- sol-gel process, 489–490

Self-healing polymer

- ATRP
  - alkyne end-functionalized polymers, 287
  - azide end-functionalized polymers, 286–287
  - chain-end-functionalized polymers, 273
  - covalent bond formation, 276
  - design of, 273
  - diene-/dienophile-functionalized polymers, 287–289
  - encapsulation method, 278
  - ene-containing polymers, 289–290
  - functional groups, 273

functional polymers, 272

- mechanisms, 274
- non-covalent bond formation, 274–276
- semi-encapsulation methods, 277, 278
- thiol-containing polymers, 289

click chemistry

- characteristics, 279
- CuAAC, 282, 284
- DA reaction, 279, 281
- mild reaction conditions, 278

conductivity, 515

definition, 512

electrohydrodynamics, 515

hollow fiber embedment, 513

layer-by-layer method, 523–524

mechanical damage

- DA/RDA reactions, 517
- dicyclopentadiene/Grubbs' catalyst, 516
- electronic interactions, 519
- epoxy matrix, 517
- fibrous scaffolds, 519
- microscale scratch, 517
- ureido-4-pyrimidone, 518

microcapsules

- delamination and blistering, 520
- embedment, 513
- emulsions, 520
- interfacial polymerization, 520
- linseed oil, 521
- mechanism, 521
- organic/inorganic reinforcing, 522
- SEM analysis, 520
- water-repelling agents, 521

porous inorganic materials

- bentonite and montmorillonite, 525–526
- cation-exchange resin, 529
- corrosion inhibitors, 524
- cyclodextrins, 529
- halloysite, 527–528
- LDHs, 527
- porous nanoparticles and hollow spheres, 528–529
- zeolites, 526

reversible cross-links

- covalent, 513
- non-covalent, 514–515

Shape memory effect

- chemical/physical cross-links, 299, 300
- commercial products, 300
- elastomer, 299
- petrochemical-based PU, 301, 302
- phase separations, 297
- properties, 298
- renewable resources, 301



- shape memory alloy wires, 515–516
- SMPs fibers, 515–516
- stimulus types, 299
- vegetable oil, 303, 307
- Shape memory polymers (SMPs),  
77, 367
- Silane resin coatings
  - anodic oxidation film, 503–504
  - antibiofouling, 506–507
  - crack formation, 496
  - deterioration
    - concrete, 504–506
    - rocks and conservation, 506
  - history, 495
  - hot-dipped galvanized steel, 502–503
  - organic polymers, 494
  - polysiloxane, 496
  - properties, 497–499
  - silicone and silicate, 495, 496
  - spray coating
    - ceramics and cement, 499, 500
    - corrosion resistance, 499
    - sealing agents, 500–502
    - zinc, aluminum, and magnesium, 499
  - ultraviolet light, 496, 497
- Small angle neutron scattering (SANS), 623
- Smart polymer microparticles (SPM), 588
- Smart polymers
  - actuators, 37, 39
  - applications, 30
  - AR coatings, 35, 36
  - automobiles, aerospace, and textile
    - fabrics, 46
  - biological triggers, 152
  - chemical triggers, 151, 152
  - controlled radical polymerization
    - ATRP reaction, 154, 155
    - click chemistry strategy, 157, 158
    - low termination rate, 153
    - NMP reaction, 156, 157
    - RAFT polymerization, 156
  - corrosion resistance coatings, 37
  - environmental changes, 28
  - food safety (*see* Food safety)
  - gold nanoparticles, 17, 18
  - hydrophilicity/hydrophobicity, 29
  - magnetic nanoparticles
    - dual stimuli-responsive
      - nanospheres, 14
    - heat generation, 13
    - iron oxide nanoparticles, 14
    - macromolecular conformational
      - alterations, 13
    - noninvasive control methods, 12
    - “ON/OFF” magnetic field oscillation
      - periods, 13
      - physicochemical alterations, 14
  - mesoporous silica
    - biomedical devices, 43
    - chemotherapy, 16
    - classifications, 15
    - controllable drug delivery system, 17
    - drug loading capacity, 39, 41
    - gene delivery, 41, 42
    - ill effects, 16
    - long-chain hydrocarbon
      - octadecyltrimethoxysilane, 41
    - macromolecular dissociation, 17
    - nanogates, 15
    - nanomedicine, 15
    - pH-response, 17
    - reductive-responsible disulfide, 41
    - surface attachment, 16
  - nanogels
    - component, 10
    - grafting/blending, 12
    - pH reactive nanogels, 11
    - positive thermosensitive hydrogels, 11
    - techniques, 12
    - temperature-induced changes, 10
    - thermoreversible gels, 11
    - VPTT, 10
  - nonstick- and self-cleaning coatings,  
30–32
  - oil industry, 43, 44
  - physical triggers, 151
  - post/prepolymerization methods, 28
  - self-assembled supramolecular
    - morphologies, 158, 159
  - self-healable materials, 33
  - stimuli-responsive polymers
    - anionic polymers, 7
    - di/triblock copolymers, 3
    - dual-responsive systems, 8
    - evaluation, 6
    - hydrophobicity, 4
    - in vivo application, 5
    - LCST, 3
    - macromolecular chimeras, 9
    - pH-sensitive polymers, 6
    - PNIPAAm-*b*-PSt micelles, 4, 5
    - polyphosphoester block copolymer
      - system, 7
    - rat oral studies, 7
    - solubilization, 6
    - temperature response, 7
    - thermal nanoparticles, 9
    - structure and properties, 150

- Smart textiles
    - carbon-based textiles, 439
    - civil and industrial application, 136, 139
    - construction methods, 132
    - definition, 438
    - design principles, 123, 124, 126
    - electrical conductivity, 438, 439
    - energy applications, 440
    - fabrics, 122
    - materials, 127, 130
    - medical monitoring and guidance, 135, 136
    - metal-based textiles, 439
    - military and aerospace, 134
    - natural and synthetic polymer fibers, 439, 440
    - nonconductive textiles, 440
    - polymer-based textile sensors, 123
    - textile transducers, 122
  - Sol-gel method
    - ammonia and nitrogen dioxide, 546
    - characteristics, 542
    - complementary techniques, 544
    - compound incorporation, 541–542
    - Coumarin 1, 549
    - diversity, 541
    - double layer film, 548
    - encapsulation, 542, 544
    - food industry, 550
    - hydrophobicity, 545
    - indicator-matrix interaction, 545
    - ions, detection, 547
    - O<sub>2</sub> and CO<sub>2</sub>, 549
    - organosilanes bearing, 544
    - ORMOSIL sensing, 546
    - performance evaluation, 544
    - pH indicators, 543, 548
    - pH monitoring, 550
    - process, 540
    - smart coatings, 549
    - textural modification, 545
    - VOCs, 548
  - Solution exfoliation method, 383
  - Split Hopkinson pressure bar (SHPB), 94
  - Spray drying, 256
  - Spray coating
    - ceramics and cement, 499, 500
    - corrosion resistance, 499
    - sealing agents, 500–502
    - zinc, aluminum, and magnesium, 499
  - Springer–Tsai model, 358
  - Superhydrophobicity
    - aesthetic appearance, 218, 219
    - experimental studies, 208
    - industrial applications, 219
    - lotus leaf and rose petal, 206
    - particle concentration, 208, 210, 211
    - particle size, 211–213
    - rhodorsil, 214, 215
    - substrates, 216, 217
  - Surface acoustic wave sensors (SAWs), 559
- T**
- Textile supercapacitors
    - biscrolling technique, 465
    - ECPs
      - carbon cloth, 459–460
      - challenges, 459
      - CNT, 461, 462
      - discovery, 453
      - external surface area, 453
      - graphene, 460–461
      - PANI, 454–455
      - polypyrrole, 455–458
      - polythiophene, 458
    - fabrication process, 464
    - materials, 452
    - nanomaterials, 452
    - p-dodecylbenzenesulfonate, 464
    - plain weave model, 463
    - planar textile devices, 463
    - reduced graphene oxide, 467
    - twist-bundle drawing technique, 467
    - volumetric capacitance, 466
  - Thermogravimetric analysis (TGA), 685, 688, 690
  - Time-temperature indicator (TTI)
    - film characterization, 265
    - real-time indication, 264
- U**
- Ultraviolet-curable coatings
    - antibacterial coatings, 654–656
    - antifog coating
      - AMPS, 653
      - dry silica powder, 652
      - grafting and block, 652
      - hydrophobic and hydrophilic, 651
      - poly (ethylene glycol), 652
      - quaternary ammonium salt, 653
      - water vapor, 651
    - self-cleaning
      - AFM, 651
      - FTIR, 650
      - gas and liquid phase, 648
      - hydrophobic possess, 649
      - inorganic/organic hybrid, 650

- photocatalysis, 649
  - reactive monomer functionality, 650
  - tensiometers, 648
  - Wenzel's equation, 648, 649
  - self-healing coatings, 653–654
  - VOC, 647
  - Upper critical solution temperature (UCST), 107
- V**
- Vapor phase polymerization (VPP)
    - technique, 443
  - Vogel–Tammann–Fulcher (VTF)
    - equation, 694–695
  - Volatile organic compounds (VOCs), 548
  - Vysotsky model, 359
- W**
- Waterborne coatings
    - cross-linking reaction
      - A and A\* blocks, 622
      - acetal, 629
      - acetoacetoxy, 626
      - adhesion energy, 623
      - aldehyde groups, 641
      - carbodiimide, 632
      - confining tube, 622
      - diffusion time, 622
      - epoxy, 630
      - fast-reaction, 622
      - film formation, 640
      - imine formation reaction, 640
      - isocyanate, 630
      - melamine-formaldehyde, 626–628
      - nondimensional parameter, 622
      - nonequilibrium interface, 621
      - polymer diffusion, 625
      - reaction time, 622
      - zinc, 630–631
    - diffusion reaction
      - A and A\* blocks, 622
      - adhesion energy, 623
      - confining tube, 622
      - decay shape, 624
      - diffusion time, 622
      - donor decay curve, 624
      - energy transfer, 625
      - fast-reaction, 622
      - film formation, 624
      - FRET, 623, 624
      - latex film, 624
      - latex films, 625
      - nondimensional parameter, 622
      - nonequilibrium interface, 621
      - reaction time, 622
      - SANS, 623
    - fine balance, 621
    - smart polymer nanoparticles
      - AcFAs, 637
      - alkoxysilane, 637
      - development, 640
      - dispersions, advantages, 634
      - equilibrium dynamics, 633
      - FRET, 637
      - hybrid latex films, 639
      - Menschutkin reaction, 634
      - open time, 639, 640
      - reactive fillers, 636
      - VOC, 620
  - Water-splitting process
    - applications, 226, 227
    - conductivity, 226
    - doping reaction, 226
    - poly(3,4-ethylenedioxythiophene)
      - absorption peaks, 235
      - active catalysts, 234
      - anticorrosion properties, 232
      - conjugated polymers, 232
      - dispersions, 231
      - electrocatalytic properties, 232
      - Goretex membranes, 234, 235
      - light illumination, 235
      - mechanism of, 231
      - recombination reactions, 232
      - thin films, 231
    - polyaniline
      - conventional semiconductors, 240
      - delocalized conjugated structures, 240
      - hydrogen production, 239
      - inert electrode substrate, 242
      - morphology, 241
      - NiMo, 243
      - Ni-ZnO, 240, 241
      - oxidation states, 237
      - PdS–CdS ratio, 240
      - uniform nanocomposite film, 239
    - polypyrrole
      - acidic and neutral solutions, 229
      - chemical oxidant, 227
      - chemical structure, 228
      - features, 229
      - hydrogen evolution, 227
      - Pt/shuttle redox mediators, 227
    - polythiophene
      - BHJ, 246
      - LSV, 244
      - neutral and conductive states, 243

- Water-splitting process (*cont.*)
- OPE-O electrode, 247
  - photocurrent measurements, 244
  - porphyrin dyes, 243
  - standard potential, 244
  - sulfonated Mn-porphyrin monomer, 244
- X**
- X-ray diffraction (XRD), 316, 317, 685, 686
- Y**
- Yamada model, 360