

Index

A

Abrupt junction, 43, 44
Absorption coefficient, 38
Active equalizers, 164
Active high-pass filter, 165
Adaptive analog equalizer, 169
Adaptive equalizers, 164
AGC, 149, 150
AGC-TIA, 150
Alignment, 63
Amplifier, 132, 133
Anti-reflection-coating (ARC), 51
Avalanche multiplication, 54

B

Back-illuminated image sensor, 235
Bandwidth, 105–112, 114–119, 121–125,
127, 128, 130, 131, 133, 134, 136,
137, 140, 142, 143, 145–147, 150,
153–158
Baseline wander, 30
Bayer pattern, 236
BER, 23, 24, 30, 33, 34
Bit error rate tester (BERT), 26

C

Carrier lifetime, 48
Carrier mobilities, 40, 42
Cellphone cameras, 235
CG-TIA, 109–111, 114, 118, 119, 122
Cherry-Hooper amplifier, 194
Circuit, 117, 122, 132, 133, 149

CIS, 235, 239
CMOS, 135, 140
Color filter, 236
Common-base, 119
Common-source, 123, 133
Common-source amplifier, 165
Compression, 136, 139, 150–153
Continuous-time linear equalizer (CTLE),
166, 220
Correlating double sampling (CDS), 235
Correlator, 237
Critical wavelength, 38
CS-TIA, 109, 122, 146
Current, 132–134
Cut-off frequency, 41, 44, 45

D

Data rate, 46
Decision directed mode, 171
Decision feedback equalizer (DFE), 163
Depletion approximation, 43
Depletion region, 42
Deterministic jitter, 30
Differential photodiodes, 218
Diffusion component, 219
Digital micro lens, 236
2D image sensor, 235
Distributed-feedback laser, 199
Drift equation, 42
Drift time, 43
Drift velocities, 43
3D-sensor, 237

Dynamic quantum efficiency, 48
 Dynamic range, 34, 149

E

Edge emitting laser diode, 199
 Einstein relation, 40
 Electron-hole pair, 38
 Excess noise, 54
 External laser modulator, 226
 Extinction ratio, 33
 Extrinsic bandwidth, 47

F

f_T doubler, 218
 Fabry-Perot laser, 199
 Fall time, 46
 Feedback, 118, 122–124, 149, 150
 Feedback resistor, 55
 FET, 133
 Figure of merit (FoM), 224, 233
 Finite states machine, 179
 FIR filter, 175
 Fixed equalizers, 164
 Flicker noise, 27
 Frequency chirping, 202, 214
 Fully integrated optical receiver, 217

G

Gain, 105–107, 110, 112, 117–119, 139, 152, 153
 Gain compression, 32
 Gigabit optical receivers, 224

H

Harmonic distortions, 32
 Hybrid OEICs, 225

I

ICDF-TIA, 122, 123, 230
 III-V photodetector, 225
 Image sensors, 235
 IMD3, 33
 Impurity concentration, 42
 Inductive peaking, 207
 Input capacitance, 56
 Input resistance, 47
 Interleaving active feedback, 194
 Intermodulation distortions, 33
 Intersymbol interference (ISI), 29

Intrinsic bandwidth, 47
 Inv-Cascode-TIA, 146, 147
 Ionization coefficient, 54
 Ionization coefficient ratio, 54
 IP3, 33

L

Lambert-Beer's law, 38
 Laser diode, 199
 Laser modulator driver, 215
 Light emitting diode (LED), 199
 Linear equalizers, 163
 Linearly graded junction, 43
 Load, 133

M

Mach-Zehnder modulator, 214
 Maximum likelihood sequence estimator (MLSE), 163
 Mobility, 42
 Modulator, 215
 Monitoring photodiode, 213
 MOSFET, 133–135, 149
 Multi-shunt-shunt feedback, 167
 Multi-stage inverter TIA, 234
 Multiplication gain, 54

N

N similar TIAs, 234
 NC-TIA, 142–144
 Negative impedance converter, 219
 Noise, 132–134, 140
 $1/f$ noise, 27
 Non-linear equalizers, 163

O

Offset-cancellation network, 220
 Optical absorption, 38
 Optical interconnects, 59
 Optical power, 33, 34
 Optical receiver, 105, 107–109, 127, 140, 142, 150, 157, 158
 Optical refractive index, 37
 Optical transmission coefficient, 53
 Overload, 137, 149

P

Passivation layer, 49
 Passive equalizers, 164

Passive R-C filter, 164
 Penetration depth, 38, 48
 Photo-generation rate, 38
 Photocurrent, 41, 105, 107, 117, 137, 143, 148, 149, 151
 Photodiode, 105, 119, 128, 129, 132, 134, 144–149
 Photon counting, 239
 Photon detection probability, 239
 Photon energy, 38
 Pipeline SAR-ADC, 235
 PN junction, 45
 POF receiver, 220
 Positron-emission tomography (PET), 238
 Post-equalizers, 163
 Power consumption, 117, 119, 122, 124
 Pre-equalizers, 163
 PVT, 166

Q

Quality factor, 24, 150

R

Random jitter, 30
 Recombination, 48
 Reflection, 48
 Reflection coefficient, 52
 Refractive index, 37
 Relative permittivity, 45
 Relaxation oscillation, 202, 205, 214
 Resistor, 132, 133
 Resonant cavity light emitting diode (RC-LED), 199
 RGC-TIA, 109, 117, 119, 121–123
 Rise time, 46

S

Saturation, 33, 34
 Saturation velocity, 43
 Scintillator crystal, 238
 Self-alignment effect, 63
 Sensitivity, 33, 34, 122, 140, 149
 Series resistance, 54, 56
 Shot noise, 26, 54
 Shunt resistor, 55
 SI-POF, 163

Signal, 149, 150
 Silicon photomultiplier, 239
 Single-ended-to-differential converter, 231
 Single-phase clocked latch, 176
 Single-photon avalanche diode (SPAD), 238
 SML photodetector, 218
 Source, 123, 124, 132
 Source degeneration, 170
 Space-charge region (SCR), 40, 42, 46, 48
 Stability, 107, 121, 131, 134–139, 145, 150, 152–154, 159
 Stereo vision, 235
 Subtraction amplifier, 220
 Super-Gm TIA, 220
 Surface recombination, 53
 Symbol error rate (SER), 21, 23

T

Thermal noise, 27
 Third order intercept point, 33
 Third-order intermodulation products, 33
 Time-of-flight (TOF), 150, 237
 Time-to-digital converter (TDC), 239
 Total bandwidth, 47
 Total harmonic distortion (THD), 32
 Training mode, 171
 Transconductance, 119, 133, 135
 Transimpedance, 132
 Transimpedance amplifier (TIA), 33, 34, 105–109, 114, 117–119, 122–124, 129–135, 140, 141, 143, 147, 149–151, 153
 Transimpedance gain, 105, 106, 110, 112, 114, 117, 119, 120, 124, 125, 127, 128, 135–138, 140, 145–148, 151, 154, 158
 Transmission, 49
 Transmission coefficient, 50
 Turn on delay, 202, 214

V

Vacuum wavelenth, 37
 VCSEL, 199
 Velocity of light, 37
 Vertical surface emitting diode, 199
 Viterbi algorithm, 179
 Voltage, 132, 133