

Index

A

Active Queue Management (AQM), 13
Actuator, 3
Adaptive fair allocation, 115
Ad hoc On-Demand Distance Vector, 40, 103, 127
Algorithm responsiveness, 9, 118
Algorithm steady state error, 10
Algorithm time complexity, 44
Application layer, 4
Application layer control system, 4, 29, 45
ATM network, 13
ATM protocol, 5, 25

B

Background traffic, 128
Bottleneck, 16

C

Carrier channel assessment, 43
Closed-loop model, 17
Closed-loop system, 21
Codesign, 44, 46, 117, 121, 129–131
Collision phenomena, 4, 42, 131
Collision probability, 43, 128
Consensus-based algorithms, 5, 7, 121, 127
Consensus-based load balancing law, 72
Consensus error, 39
Content Delivery Networks, 66
Controller, 2
Convergence results, 18
Convergence speed, 39
Convex hull, 34
Cooperative control, 22, 64
Cooperative rate control (CRC), 15, 18, 49

Cooperative sink control, 63

Critical scenario, 116

D

Defibrillator, 106
Delay, 4, 6, 10, 41, 107, 119, 129
DiffServ network, 19
Distributed consensus-based control, 4
Distributed physical process, 3
Dynamic average consensus, 29

E

Electrocardiogram, 104
End-to-End implementation, 10, 25, 49
Energy consumption, 6, 10, 39, 107
EPRCA, 51
ERICA, 51
Explicit Congestion Notification (ECN), 5
Explicit Rate (ER), 5
Extended Laplacian, 15

F

Fairness, 6, 24, 51, 110
Faulty scenario, 116
Feedback control system, 21
Feedback cooperative term, 18, 62
Feedback gains, 22, 64
Feedforward action term, 18, 61
Feedforward gains, 19, 22
Fetal electrocardiogram, 105

H

Healthcare system, 102

HELLO packet, 41, 43, 129
Hop-by-Hop implementation, 10, 25, 55, 66

J

JAIN index, 6, 50
Joint graph, 33

L

Laplacian matrix, 31
Least-Loaded algorithm (LL), 70
Link utilization, 24, 51
Load balancing, 66
Local Area Network (LAN), 100
Lyapunov function, 39

M

MAC protocol, 102
Max–min fair, 19, 61, 110
m-hop relay consensus algorithm, 32
Model, 16
Multi-hop relay dynamic consensus algorithm, 29, 32, 34
Multilayer control system, 3, 45

N

NCPS architecture, 2, 4
Networked Control System (NCS), 1, 30, 37, 99
Networked Cyber-Physical Systems (NCPSs), 1
Networked Monitoring Control Systems (NMCSs), 1, 30, 31
Networked Queue System, 49
Networked Robot System (NRS), 2
Network latency, 42
Network layer, 3
Network layer control system, 4, 13, 45
Network Monitoring Systems (NMSs), 35
Network open loop, 16
NIST simulator, 49
Nominal scenario, 115
NS-2 network simulator, 79

O

On-Demand scenario, 115
Overlay virtual graph, 15, 17

P

Pacemaker, 106

Packet collision, 42
PID, 51
Point of Care (PoC), 100
PRCA, 51
Proportional fairness, 18, 63, 110, 113

Q

Quality of Service (QoS), 19, 99
Queue balancing, 24, 49, 55
Queueing delay, 4
Queue setpoint regulation, 6

R

Rate control, 49, 55
Reliability, 6, 107
Resource Management (RM), 5
Respiration, 104
Response Time (RT), 81
Return ratio transfer function, 21, 36
RM cell, 25
Robot, 3
Robot Autonomous System (RAS), 2
Round Robin algorithm (RR), 70
Round-Trip Time (RTT), 16, 46
Routers, 3
Routing matrix, 16
Routing protocol, 117

S

Scalability, 6, 54, 87, 107
Sensitivity function, 21
Sensor, 3
Servers, 80
Set point regulation, 24
Settling Time, 93, 123, 131
Sink, 8, 63, 100, 112
Spanning tree, 31
Stability, 18, 34, 51
Stability margin, 121, 122
Static average consensus, 31
Supervisor, 8

T

TCP protocol, 5, 26
Time Division Multiple Access (TDMA), 59
TrueTime simulator, 63
Two Random Choices algorithm (2RC), 70

U

Unbalancing Index, 81

V

Vital signs, [103](#)

W

Wide Area Network (WAN), [100](#)

WiFi, [103](#)

Wired networks, [49](#)

Wireless Body Area Network (WBAN), [99](#)

Wireless body area networked system, [99](#)

WirelessHart, [59](#)

Wireless Mesh Network (WMN), [102](#)

Wireless Networked Monitoring Control Systems (WNMCSs), [1](#), [55](#), [57](#)

Wireless networked monitoring systems, [117](#)

Wireless networked robot systems, [126](#)

Wireless networks, [55](#)

Wireless Sensor Actuator Network (WSAN), [2](#)

Z

ZigBee, [40](#), [58](#), [102](#), [127](#)