

# Index

## A

- Abrasion resistance, 189, 264, 462, 464, 468–471, 517, 519–521, 523, 524
- Abrasion test, 463, 468, 469, 471, 472
- Acoustic emission, 139–141, 145, 147, 148, 150, 151, 155, 157, 160, 161
- Acrylonitrile–butadiene–copolymer (ABS), 3, 4, 12, 104
  - blends with thermoplastic polyurethane (TPU/ABS), 3, 4, 5, 12
- Adhesion, 29, 147, 173, 223, 244, 250, 277, 278, 284, 285, 292, 298
- Ageing, 165, 181, 197, 298–307, 351–353, 356–362, 406, 407, 410, 412–416, 423, 431, 435–442
- Arc-shaped specimens, 213–217
- Atomic force microscopy (AFM), 106, 113, 166

## B

- Ball indentation test, 407, 412, 413, 416
- Biaxial deformation, 335, 339
- Biaxial testing, 335, 336, 338
- Biax Test Stand, 336, 338, 348
- Brominated poly(isobutylene-co-isoprene) (BIIR), 498, 500, 501

## C

- Cellulose fibres, 96, 97
- Chain statistics, 500–502
- Cling test, 283, 287, 289, 295
  - instrumented peel cling test, 287, 289
- Compact Tension (CT) specimen, 27, 33, 44–48, 213, 215–218
- Composites
  - conventional, 8, 83, 121, 160, 297, 315
  - nanocomposites, 23–31, 447, 448
- Compression set (CS), 423, 426, 429, 432–434, 437, 439, 440, 442

- Crack deflection, 24, 25, 29–31
- Cracked round bar (CRB) specimen, 33, 36, 44–48, 179, 185, 198, 199
- Crack growth, 39
  - environmental, 33, 36
  - fatigue, 23–25, 27, 30, 41, 42, 351
  - slow, 34, 35, 37, 39, 177–179, 182, 186, 197–199, 204–206, 208, 233, 239, 240
  - stable, 3–5, 7–12, 15–18, 23, 29, 30, 76, 78, 80, 122, 124–126, 129, 132, 205, 214–216, 290, 294, 361
  - Unstable, 15, 17, 30, 74, 87, 261, 264
- Crack initiation, 3–5, 12, 16, 25, 30, 31, 37, 40, 55, 67, 76, 78, 89, 109, 124, 134–136, 160, 165–169, 198, 199, 234, 236, 285, 286, 288, 289, 293–295, 323, 352, 360, 368, 469
- Crack resistance curve (R-curve), 3–10, 16–18, 73, 80, 122, 124, 131–133, 214–216, 219, 224, 286, 289, 290, 292–295
- Crack Round Bar (CRB) Test, 33, 36, 45, 48, 179, 185–187, 198
- Crack speed, 4, 10, 11, 14, 15, 18, 219, 291
- Crack-(tip)-opening displacement (C(T)OD), 4, 5, 10, 18, 148, 205
- Creep testing, 121, 181, 316, 387, 391, 392
- Crosslink density, 248, 249, 463, 465, 471, 475–478, 481, 482, 485, 491, 494, 503, 521
- Crosslinking
  - using radiation or peroxide thermal, 478
- Crystallinity, 57, 73–75, 77, 80, 147, 215, 220, 230, 284, 412
- Crystal modification, 73–75, 191
- C specimens, 213–215, 217

## D

- 3D digital microscopy, 121, 125, 215

- Debonding, 139, 140, 148, 149, 151, 152, 154, 161
- Detergent, 179–182, 184, 187
- Differential Scanning Calorimetry (DSC), 57, 407, 414, 432, 433
- Diffusion, 279, 352, 380, 406, 421–426, 428, 436, 439
- Digital image correlation, 315, 328, 330, 337, 343
- 3D image correlation analysis, 246
- Double-edge-notched tension (DENT) specimens, 258, 259, 464
- 3D reconstruction, 95, 103, 105, 106, 109, 111, 115–117
- Dynamic-mechanical analysis (DMA), 19, 57, 123, 243, 245, 247, 352–354, 378, 379, 381, 432, 437, 519
- Dynamic-thermomechanical analysis, 299, 300, 377, 507, 512, 519
- E**
- Elastic–plastic fracture mechanics (EPPM), 76, 125, 212, 224, 290
- Elastomer
  - chemically crosslinked, 435, 449, 451, 462, 478, 481, 491, 497, 502
  - magnetorheological (MRE), 365, 370–373
  - thermoplastic (TPE), 287, 289, 498, 500–502
- Elastomeric seals, 431–433, 435, 442
- Elastomer-modified polypropylene, 172
- Electron microscopy, 96, 103, 105, 109, 114, 121, 129, 166, 448, 451
- Energy-Dispersive X-ray Spectrometry (EDS), 113
- Energy dissipation, 16, 18, 60, 68, 71, 133, 192, 288, 291, 328–331, 510
- Energy-Filtered Transmission Electron Microscope (EFTEM), 26
- Energy release rate, 74, 86, 154, 263, 271, 274–280, 286, 288–292, 295, 355
- Environmental crack growth, 33, 36
- Environmental Scanning Electron Microscopy (ESEM), 95, 106, 111, 139, 140, 145–147, 149, 150, 152, 153, 160, 161
- Epoxy–clay nanocomposites, 26
- Epoxy nanocomposites
  - with clay as nanofiller, 26
  - with silica as nanofiller, 23, 24, 26
- Epoxy resins
  - modified, 244, 248, 297
  - rubber modified, 244
  - nanocomposites, 23–31
- Epoxy–silica nanocomposites, 26
- Ethylene–propylene–diene rubber (EPDM), 243, 245, 247, 249, 251, 252, 365, 368, 369, 371–374, 437, 498, 500, 501
  - blends with natural rubber, particle filled, 365
- Ethylene-propylene rubber (EPR), 103, 104, 106, 109, 117, 123, 129
- Ethylene vinyl acetate (EVA), 171, 273–280
- Exposure to chemical agents, 266
- F**
- Failure analysis, 165, 166, 173
- Fatigue crack growth, 23–25, 27, 30, 41, 42, 351
- Fatigue crack propagation, 23, 25, 27, 28, 355
- Fatigue loading conditions, 23, 40–42, 197, 223, 330, 331, 335
- Fatigue testing, 316, 323, 326–328, 330, 336, 345, 370, 372
- Fibre fracture, 139–141, 143, 144, 148, 152, 154–157, 161
- Fibre–matrix adhesion, 173, 317, 318
- Fibre orientation, 83, 85, 86, 91, 315, 317, 318, 322–324, 328, 406–411, 416
- Fibre pull-out, 86, 98, 140, 141, 148–157, 161
- Fibre-reinforced thermoplastics, 3, 42, 83, 85, 91, 98, 139–141, 161, 213, 315–317, 319, 325, 378, 406, 407
- Film
  - peel film, 99, 267, 272, 273, 275, 278, 279, 292
  - stretch film, 284–286, 291–295
- Finite element method (FEM), 19, 38, 89, 223, 225, 340, 341, 399, 421, 422, 508
- Fixed-arm peel test, 262, 263, 268, 275, 276
- Fluorescence Adsorption-Contrast Method (3D-FAC), 121, 129, 130, 136
- Fluorescent dye colouring, 125, 127, 129, 130
- Fluorocarbon rubber (FKM), 432, 437
- Fourier transform infrared spectroscopy (FTIR), 102
- Fractography, 95, 106, 152, 165, 166, 171, 173
- Fracture mechanics
  - Elastic–plastic fracture mechanics (EPPM), 76, 125, 212, 224, 290
  - Linear Elastic Fracture Mechanics (LEFM), 36, 39–41, 44, 45, 48, 74, 135, 198
- Fracture mechanics parameters
  - crack-(tip)-opening displacement, 3–5, 10, 18, 148, 205
  - energy release rate, 74, 86, 154, 263, 271, 274–280, 288–292, 295, 355

- J-integral, 4, 6, 9, 15, 16, 121, 122, 135, 340, 346, 413, 416
- stress intensity factor, 15, 23, 24, 27, 36–39, 46, 74, 185, 198, 223, 229, 234–237, 239, 240
- tearing energy, 345–347, 355, 357, 361
- Fracture mechanics specimens
  - arc-shaped specimens, 213–217
  - Compact Tension (CT) specimens, 27, 33, 44–48, 213, 215–218
  - Cracked round bar (CRB) specimens, 33, 44–48, 177, 185, 198, 199
  - C specimens, 213–215, 217
  - Double-edge-notched tension (DENT) specimens, 258, 259, 464
  - pure-shear specimens, 345, 347, 355
  - Single-edge-notched bending (SENB) specimens, 76, 124, 126, 148, 213–221, 225
  - Single-Edge-Notched Tension (SENT) specimens, 205, 213–217, 219, 225, 343, 344
- Fracture (mechanics) tests
  - accelerated Full Notch Creep Test (aFNCT), 177, 179, 181, 182, 184
  - Crack Round Bar Test (CRB), 33, 34, 36, 45, 48, 179, 185–187, 198
  - Full Notch Creep Test (FNCT), 36, 179, 204–206, 208, 212
  - instrumented peel cling test, 287, 289
  - Pennsylvania Edge Notch Tensile Test (PENT), 203–206, 208, 209
  - pipe falling weight test, 192, 193, 196, 199
  - pure-shear test, 345, 347, 355
  - Strain Hardening Test (SHT), 36, 177, 179, 182, 183, 203, 204, 206, 212
- Full Notch Creep Test (FNCT), 36, 179, 204–206, 208, 212
  - accelerated Full Notch Creep Test (aFNCT), 177, 179, 181, 182, 184
- G**
- Gel Permeation Chromatography (GPC), 408, 415, 471
- Glass fibre-reinforced composites, 8, 117, 129, 135, 139, 157, 166, 172, 315, 325, 378, 380, 382, 384
- Glass fibres, 84, 86, 98, 122, 123, 125, 146, 160, 319, 322, 379
- Glass rubber transition, 432–435, 442
- Glass transition temperature, 55, 57, 123, 243, 245, 246, 249, 252, 298, 299, 379, 381, 384, 390, 415, 435, 437, 494, 497, 498
- H**
- Hardness, 113, 147, 155, 215, 220, 231, 245, 264, 267, 369, 406, 407, 412, 413, 416, 437, 439, 440, 442, 463, 468, 469, 490
- High-density polyethylene (PE-HD), 12, 33, 34, 42, 43, 45–48, 139, 147, 157, 183, 204, 205, 207–209, 212, 213, 215, 230, 238, 391
  - reinforced with short-glass fibres, 147, 157–161
- Hooke number, 493–505
- Hygrothermal ageing, 405–407, 409, 411, 416
- Hysteresis, 286, 291, 294, 316, 328, 329, 352, 510, 511
- I**
- Ice traction, 517–519, 521, 523, 524
- Impact-loading conditions, 12, 74, 76, 122, 139, 147, 161, 214, 258
- Infrared spectroscopy, 102, 248, 299
- In situ peel test, 99–101, 106
- In situ tensile test, 96, 99, 100, 106, 139, 145–147, 149, 152, 160
- In situ ultramicrotomy, 103, 106, 111
- Instrumented impact test, 76, 78, 80, 125, 129, 139, 140, 147, 161, 407
  - instrumented puncture impact test, 260, 261, 265
  - instrumented tensile impact test, 258, 259, 264, 464
- Instrumented peel cling test, 283, 287, 289, 295
- J**
- J-integral, 4, 6, 9, 15, 16, 121, 122, 135, 340, 346, 347, 413, 416
- L**
- Leakage rate, 432, 434, 435, 437, 442
- Lifetime estimation, 33, 34, 40, 41, 45, 46, 48, 204, 206, 208, 229, 240, 298, 328, 330, 431, 432
- Light microscopy, 76, 106, 121, 135, 166, 322, 471
- Linear Elastic Fracture Mechanics (LEFM), 33, 36, 39–41, 44, 45, 48, 74, 135, 198
- Linear low-density polyethylene (PE-LLD), 109, 111, 112, 115–117, 216, 273, 275, 277, 278, 284, 286, 287, 292
- Loading conditions
  - fatigue, 23, 40, 42, 197, 223, 330, 331, 335, 355
  - impact, 3, 4, 12, 74, 76, 122, 139, 147, 161, 214, 219, 258

- Loading conditions (*cont.*)  
   quasi-static, 3, 10–12, 139, 161, 166, 212, 214, 216, 219, 261, 316, 335, 353  
   static, 36, 41, 43, 47, 99, 212, 390, 392  
 Loading rate, 60, 61, 62, 69, 152, 214, 218, 220  
 Long-glass fibre-reinforced composites, 83  
 Long-glass fibre-reinforced polypropylene, 83  
 Long-term mechanical performance, 23, 40, 177, 189, 191, 197, 198, 205, 208, 219, 223, 297, 377–379, 387, 389–397, 423  
 Low-density polyethylene (PE-LD), 99, 273–275, 279, 285
- M**
- Macro dispersion index (DI), 470–472  
 Master curve construction, 379, 385–387, 389–391, 393–401, 440, 447, 457, 493–496, 499–501, 503, 505  
 Matrix yielding, 139, 148, 152, 154–157, 161  
 Maximum tangential stress (MTS) criterion, 234  
 Medium-density polyethylene (PE-MD), 207, 216  
 Micro-Bond Test, 86, 87  
 Micro Computer Tomography (micro-CT), 408–411  
 Microindentation test, 211, 215, 220, 225, 232  
 Microscopy  
   3D digital microscopy, 121, 125, 215  
   electron microscopy  
     energy-filtered transmission electron microscopy, 26  
   Environmental Scanning Electron Microscopy (ESEM), 95–103, 106, 111, 139, 140, 145–147, 149, 150, 152, 153, 160, 161, 281, 286  
   Scanning Electron Microscopy (SEM), 29, 77, 79, 80, 95–98, 101, 103, 106, 110, 112, 113, 117, 121, 129, 133, 135, 136, 146, 166, 192, 281, 296, 471  
   transmission electron microscopy (TEM), 103, 114, 279, 448, 451  
   light microscopy  
     3D digital microscopy, 124, 125, 215  
     reflected-light microscopy, 322  
     transmitted-light microscopy, 220  
 Moisture absorption, 122, 123, 406, 412–414, 416, 419  
 Multi-layer pipes, 169–171, 212, 214, 222  
 Multiple-specimen technique, 214
- N**
- Nanocomposites  
   with epoxy as matrix, 23–31  
 Natural rubber (NR)  
   epoxised (ENR), 485, 486  
     with wood flour, 490  
   with carbon black (CB), 368  
   with micron-sized carbonyl iron powder (CIP), 365, 367–369, 371, 373  
   with wood flour, 490  
 Necking, 65, 291  
 Nitrile–butadiene rubber (NBR), 341, 342, 432, 434, 477–479, 498–501  
   hydrogenated (HNBR), 341, 342, 347, 437–441, 477–479  
     with carbon black (CB), 341  
 Notched impact strength, 193  
   notched tensile impact test, 259  
 Nucleation, 191, 194, 352  
 Nucleation agent, 73–75
- O**
- Orientation, 29, 68, 70, 83, 85, 86, 91, 106, 140, 142, 150, 172, 211, 213–215, 217, 218, 220, 224, 225, 315–318, 320, 322, 324–326, 328, 331, 365, 367, 371, 373, 374, 406–411, 416, 490
- P**
- Paris law, 24, 36  
 Particle debonding, 23, 29, 30  
 Peel film, 99, 267, 268, 272, 273, 275, 278, 279, 283, 292  
 Peel system  
   adhesive, 271–273, 275–279, 285  
   cohesive, 271–274, 277–279, 285  
 Peel test, 99, 262, 263, 268, 275–277, 288, 295, 298–300, 304, 306, 307  
   fixed-arm peel test, 262, 263, 268, 275, 276  
   T-peel test, 99, 262, 263, 275, 276, 285, 298–300, 304, 306, 307  
 Pennsylvania Edge Notch tensile (PENT) Test, 36, 179, 203–205, 212, 233  
 Pipe falling weight test, 192, 193, 196, 199  
 Pipes  
   joints, 243  
   plastic pipes, 33, 35, 197, 204, 211–213, 216, 219–221, 224, 259, 389, 391  
   rehabilitation of pipes, 243, 244  
 Plastic deformation, 9, 11, 13, 18, 34, 55, 66–68, 70, 122, 125, 129, 133, 136,

- 141, 147, 149, 150, 156, 157, 166,  
168–170, 199, 222, 223, 225, 286, 291
- Plastic void growth, 24, 29, 30
- Plastic zone size, 23, 24, 30
- Polyamide (PA)  
  high impact, 168  
  polyamide 6 (PA6), 121, 122, 405–407  
  polyamide 66 (PA66), 123, 377, 378, 380,  
  382–384, 414–416  
  polyphthalamide (PPA), 377–387  
  reinforced with short-glass fibres, 377–387,  
  405–416
- Polybutadiene (BR), 3, 463  
  blends with styrene-butadiene rubber, 461,  
  463  
  with silica or glass powder, 461–472
- Polybutene-1 (PB-1), 99, 147, 212, 267, 271,  
  273, 274, 285, 296
- Polycarbonate (PC), 3, 11–16, 19, 42, 55–57,  
  66, 68, 71
- Poly(ethylene terephthalate) (PET), 55–57,  
  59–63, 65–69, 71, 273, 275, 277–279
- Polyethersulfone (PES), 100, 101–104
- Polyethylene (PE)  
  high-density (PE-HD), 12, 33, 34, 42, 43,  
  45–48, 139, 147, 157–161, 183, 204,  
  205, 207–209, 212, 213, 215, 230, 238,  
  391  
  reinforced with short-glass fibres, 147,  
  157–161  
  linear low-density (PE-LLD), 109, 111,  
  112, 115–117, 216, 273, 275, 277, 278,  
  284, 286, 287, 292  
  low-density (PE-LD), 99, 273, 275, 279,  
  285  
  medium-density (PE-MD), 207
- Polyisoprene (IR), 447–449, 451, 453, 455,  
  457–458  
  with carbon black (CB), carbon nanotubes  
  (CNTs) and/or nanographite, 448–458
- Polymer composites, 297, 316
- Poly(methyl methacrylate) (PMMA), 15, 166,  
  167
- Polynorbornene (PNR), 498, 500, 501
- Polyoctenamer (TOR), 498
- Polypropylene (PP)  
  blends, 10, 12  
  with ethylene-propylene rubber, 103,  
  104, 106, 109–118  
  with linear low-density polyethylene  
  (PE-LLD), 109, 111, 112, 115–117  
  elastomer-modified, 122, 172  
  layered-particle reinforced, 213  
  mineral-filled, 172  
  with talc, 103, 104, 172
- neat  
  homopolymer (PPH), 118, 193, 194,  
  196, 198–199  
  random copolymer (PPR), 75, 193, 194,  
  196, 197  
  short-glass fibre-reinforced (PP/GF), 6, 13,  
  150, 160, 315  
  talc-filled, 104, 172
- Poly(styrene-divinylbenzene), 103, 104
- Polyvinylchloride (PVC), 19, 56, 97, 190, 265,  
  266
- Powder X-ray Diffraction, 26, 27
- Polypropylene-talc nanocomposites, 104, 172
- Pure-shear specimen, 345, 347, 355
- Pure-shear test, 345
- Q**
- Quasi-static loading conditions, 3, 10–12, 139,  
  161, 166, 212, 214, 216, 219, 261, 316,  
  335, 353
- R**
- Raman spectroscopy, 298, 299, 304
- Reflected-light microscopy (optical  
  microscopy), 322
- Rolling resistance, 462, 512–515, 517–524
- Rubber  
  acrylonitrile–butadiene–rubber, 341, 342,  
  347, 477  
  with silica, carbon black (CB),  
  organoclay or graphene, 477, 478,  
  482  
  brominated poly(isobutylene-co-isoprene)  
  (BIIR), 498  
  ethylene–propylene–diene rubber (EPDM),  
  243, 245, 247, 249, 251, 252, 365, 368,  
  369, 371–374, 432, 437, 439–441, 498,  
  500, 501  
  blends with natural rubber, particle  
  filled, 352, 353  
  ethylene–propylene–rubber (EPR), 3, 5–8,  
  10–12, 16, 103, 104, 109–117, 123,  
  124, 129, 133–136  
  fluorocarbon rubber (FKM), 432, 435, 437,  
  441  
  natural rubber (NR), 341–343, 345, 351,  
  352, 356, 365–368, 485–487, 489, 491,  
  498  
  epoxised, with wood flour, 490  
  epoxised (ENR), 485, 486  
  with carbon black (CB), 368  
  with wood flour, 490

- Rubber (*cont.*)
- nitrile–butadiene rubber (NBR), 341, 342, 432, 434, 477–479, 498–501
    - hydrogenated (HNBR), 341, 342, 347, 437–441
    - hydrogenated, with carbon black (CB), 341
  - polybutadiene (BR), 352, 353, 463, 517
  - polydimethylsiloxane (PDMS), 498
  - polyisoprene, 447, 449, 458
    - with carbon black (CB), carbon nanotubes (CNTs), 448–458
  - polynorbornene (PNR), 498, 500, 501
  - polyoctamer (TOR), 498
  - styrene–butadiene rubber/polybutadiene blends (SBR/BR), 461, 467, 470, 472, 518, 520
    - with glass powder, 463
    - with silica, 475, 477, 478, 482
  - styrene–butadiene rubber (SBR), 262, 264, 341, 351, 352, 517, 522, 523
    - with carbon black (CB), 262, 264, 341, 352, 356, 495, 497, 504, 505
    - with glass powder, 463
    - with silica, 475, 477, 478, 482
- S**
- Scanning Electron Microscopy (SEM), 27, 29, 77, 79, 95–97, 101, 103, 105, 109, 110, 112, 113, 117, 121, 129, 133, 135, 136, 146, 166, 192, 471
  - Short-glass fibre-reinforced composites, 139, 140, 157, 161, 315, 405, 406
  - Short-glass fibres reinforced high-density polyethylene (PE-HD/GF), 147, 157–160, 161
  - Short-glass fibres reinforced polyamide 6 (PA6/GF), 405–419
  - Short-glass fibres reinforced polyamide 66 (PA66/GF), 378–387
  - Short-glass fibres reinforced polybutene-1 (PB-1/GF), 160
  - Short-glass fibres reinforced polyphthalamide, 380
  - Single-Edge-Notched Bending specimens (SENB), 76, 124, 126, 148, 213–221, 225
  - Single-Edge-Notched Tension specimens (SENT), 205, 213–217, 219, 225, 343, 344
  - Short-glass fibre reinforced polypropylene (PP/GF), 6, 13, 150, 160, 315
  - Short-glass fibre reinforced composites, 139, 140, 157, 161, 315, 405, 406
  - Single-fibre unit cell model, 87, 88
  - Single-specimen method/technique, 4, 5, 214, 290, 292, 293
  - Slow crack growth (SCG), 33–35, 37, 39, 177–179, 182, 186, 189, 197–199, 204–206, 208, 229, 233, 235, 239, 240
  - Specimen geometry, 44, 47, 180, 184, 185, 206, 217, 340, 341, 355
  - Stable crack growth, 12, 17, 24, 29, 166
  - Static loading conditions, 12, 36, 41, 43, 47, 316, 353, 392
  - Stepped Isothermal Method (SIM), 377, 379, 385, 387, 389–401
  - Stiffness, 13, 25, 28, 55, 74, 75, 140, 147, 220, 221, 223, 225, 244, 262, 265, 267, 315, 339, 366, 378, 405, 406, 412, 422, 423, 426, 432, 448, 509, 519, 521
  - Strain field analysis, 331, 340
  - Strain hardening modulus, 183–185
  - Strain hardening test (SHT), 36, 177, 179, 182, 183, 203, 204, 206, 212
  - Stress cracking, 33, 40, 41, 48, 177–187, 208
  - Stress intensity factor, 15, 23, 24, 27, 36–39, 46, 74, 185, 198, 223, 229, 234–237, 239, 240
  - Stress–strain curve, 59, 60, 65, 87–91, 207, 383, 399, 408, 409, 496, 497, 501–503
  - Stretch film, 283–287, 289, 291, 293–295
  - Structural mechanics, 422
  - Styrene–butadiene–butylacrylate mix polymer, 518
  - Styrene–butadiene copolymer, 3, 20
  - Styrene–butadiene rubber (SBR), 262, 341, 342, 351, 352, 356, 497, 517, 522, 523
    - blends with polybutadiene, 463
    - with silica or glass powder, 463
    - with carbon black (CB), 262, 264, 341, 352, 356, 495, 497, 504, 505
    - with silica, 475, 477, 478, 482
    - with silica or glass powder, 463
- T**
- Tearing energy, 345–347, 355, 357, 361
  - Tear resistance, 261, 262, 267, 463, 467–471
  - Tear test, 261, 262, 264–266, 269, 463, 467
  - Tensile lap-shear test, 298–300, 306, 307
  - Tensile test, 67, 98–100, 103, 106, 109–112, 114–117, 123, 124, 139, 140, 145–147, 152, 160, 161, 179, 183, 187, 203–205, 207, 208, 215, 222, 223, 246, 247, 249, 250, 252, 257, 265, 266, 288, 323, 326, 370, 371, 377, 379, 382–384, 387, 407, 463, 467, 477, 487, 497, 501, 504
  - Thermography, 56, 71

- Thermogravimetric Analysis (TGA), 26, 246, 298, 300, 305
- Thermo-mechanical behaviour, 507
- Thermomechanical treatment, 518–523
- Thermoplastic elastomer (TPE), 287, 289, 498, 500–502
- Threshold of crack growth, 23, 28
- Time-temperature superposition principle (TTSP), 389–393, 396–398, 401
- Time to crack initiation, 37
- Time to failure, 37, 180–182, 184, 186, 204, 208, 209, 239, 399
- Toughening, 23–25, 29–31, 121, 135, 194, 195
- Toughening mechanisms
- crack deflection, 23–25, 29–31, 246
  - crack pinning, 24, 29
  - particle debonding, 23, 29, 30
  - plastic void growth, 24, 29, 30
- T-peel test, 99, 262, 263, 275, 276, 285, 298–300, 304, 306, 307
- Transmission Electron Microscopy (TEM), 103, 114, 279, 448, 451
- Transmitted-light microscopy, 220
- Trouser specimen, 261
- Tyre, 517, 518, 521, 523
- V**
- Vulcametry, 461, 472
- W**
- Water absorption, 243, 249, 252, 377–385, 387, 416
- Wavelet analysis, 144, 145, 148, 152, 155, 158, 159
- Welding, 211, 213–215, 219–221, 224, 225, 229–233, 235, 239, 240
- Wet traction, 517–519, 521, 523, 524
- Wöhler curves, 326, 327, 370, 372
- X**
- X-ray computed tomography, 315, 316
- Y**
- Yield point, 56, 59–61, 64–66, 68–71, 170, 171, 207, 222, 299, 503
- Yield temperature, 60–63, 65