

Index

A

Animal experiment, 104
Anticipated challenges, 10
ASK demodulator, 63

B

Bidirectional wireless communication, 58
Biocompatibility, 81–83
Bit error rate, 101
Burr hole, 17

C

Capacitive detuning, 60–62
Clock recovery, 77
Coil design, 33
Coupling coefficient, 29, 30, 32, 33

D

Demodulator, 59, 62–66, 77
Diffusion barrier, 81, 83, 84, 86
Diffusion modelling, 85
Downlink, 16–20

E

EcoG, 2–4
Efficiency, 23, 26, 28–30, 32, 33, 35, 36, 41–43, 45, 48
Epilepsy, 1–5, 7, 8, 10
Epilepsy and surgical treatment, 3
External base station receiver, 74

F

Fast ripple, 7

H

Hermetical sealing, 81, 84

I

IEEG, 2, 4, 7
Implant powering, 23, 26, 30
Inductive link, 23, 26, 28–30, 32–35, 52
In vitro, 89, 102, 103, 106
In vivo, 89, 104, 106

L

Load modulation, 20, 21
Loop antenna, 67, 69–72, 78

M

Magnetic coupling, 23, 26–28, 52
Micro electrode array, 5, 6, 8
Mock CSF, 102, 104
Modulator, 61, 62
Multi-unit activity, 7, 10

N

Neural data acquisition, 7
Neural recording, 1, 4–10

P

Parylene-C, 83–85
Polymer packaging, 84, 85
Power transfer efficiency, 91–94, 98, 101–103
PSRR, 44, 48, 50

Q

Quality factor, 59, 61

R

Receiver, 59, 67, 69, 74, 78
Rectifier, 23, 35, 36, 38, 39, 42–44, 50, 52
Regulator, 23, 35, 36, 39, 43–46, 48–52
Remote powering, 18, 19
Resective surgery, 2
Resonant, 23, 28–30, 32–35, 52
Ripple, 7

S

System characterization, 89

System integration, 89

System level solutions

single frequency approach, 18

two frequency approach, 20

System specifications, 15

T

Tissue absorption, 52

Transmitter, 59, 67–69, 71, 74, 78

U

Uplink, 17, 18, 20, 21

V

Voltage-controlled oscillator (VCO), 67

W

Wireless data communication, 15

Wireless power transfer, 15, 17–21