

# Index

## A

Accuracy, xiii–xvi, 5, 6, 9–11, 13–16, 20, 24, 25, 31, 33–35, 38, 46, 47, 52, 56, 57, 60, 61, 63–65, 68, 73, 75, 79, 80, 82, 83, 85, 87, 88, 91, 92, 95, 97, 99–100, 104–107, 109–111, 113

Active radio frequency identification tags, 3–5

ADC. *See* Analog-to-digital converter (ADC)

*a*-trim, xiv, 56, 69, 79, 87, 95–97, 105

Analog front-end, 23, 37, 59–64, 70, 74, 82–84

Analog-to-digital converter (ADC), xiv–xvi, 9, 13, 15, 16, 19, 23–26, 30, 32–35, 37–54, 57, 59, 60, 62, 64–73, 75, 77, 79–80, 84–85, 87, 93–95, 100, 102–105, 107, 109–112

Auto-zeroing (AZ), 46, 73

## B

Bandgap temperature sensors, 23–25

Bandgap voltage, 19, 21, 22, 82

Bandgap voltage reference, 7, 46, 92, 93

Batch-calibrated, 15, 67, 94

Batch-calibration, 9

Batch-to-batch spread, xv, 78–79, 87

Battery-powered, 2, 5, 107

$\beta$ -compensation, 94

$\beta_F$ -compensation, 61, 74, 98

$\beta_F$ -dependent, 61, 98

Bipolar junction transistors (BJT)-based sensor, xiv–xvi, 11, 16, 55, 57, 87, 91–93, 95, 107, 111, 112

Bipolar junction transistors (BJT)-based temperature sensors, 7, 19–35, 57, 88, 93, 106, 107, 109, 110

Bitstream (bs), 33, 43, 45, 47, 65–67, 71, 103

Bottom-plate sampling, 67

bs. *See* Bitstream (bs)

## C

Calibration, xiii, xv, xvi, 5, 6, 9, 11, 13–15, 25, 31, 34, 52, 54–57, 75–79, 81, 87, 97, 106, 111, 113

Capacitor digital-to-analog converter, 52, 72, 84, 85, 96

CDS. *See* Correlated double-sampling (CDS)

Charge balancing, xv, 23, 33, 34, 45, 51, 52, 65, 87

Charge injection, 74, 75

Charge-pump, 101, 102

Chopping, 33, 46, 62, 67, 74, 83, 99, 100

Clinical temperature range, 24

Coarse conversion, 42–44, 46, 47, 49, 51, 52, 64–66, 70–74, 103

Complementary-to-absolute-temperature (CTAT), xiii, 7, 21, 22, 92, 93, 104, 105, 113

Compound annual growth rate (CAGR), 3

Continuous-time (CT), xvi, 112

Conversion time, xiv, 5, 6, 14, 15, 26, 27, 32–34, 37, 38, 41, 44, 57, 64, 67, 68, 72, 75, 78, 80, 86, 87, 106, 110, 111

Correlated double-sampling (CDS), 67, 74

- Cost-effective, 5, 7  
 CT. *See* Continuous-time (CT)  
 CTAT. *See* Complementary-to-absolute-temperature (CTAT)  
 Current gain  $\beta_F$ , 7, 22, 61–62  
 Current-voltage mirror (CVM), 98, 99, 105  
 Curvature, 55, 57, 60, 67, 75, 104  
 CVM. *See* Current-voltage mirror (CVM)
- D**  
 DAC. *See* Digital-to-analog converter (DAC)  
 Decimation filter, 45, 67, 75, 85, 94, 99, 104  
 $\Delta\Sigma$ -ADC, xiv, 23, 32–34, 37, 38, 44, 46, 48–50, 52, 57, 64, 70, 84, 85, 87, 94, 109–112  
 $\Delta\Sigma$  converters, xiv, 33, 42, 64, 94  
 DEM. *See* Dynamic element matching (DEM)  
 Differential nonlinearity (DNL), 52–54, 80  
 Digital back-end, xiv, 30, 37, 38, 55, 60, 67, 68, 75, 85, 94, 100  
 Digitally assisted, 38, 40  
 Digitally assisted analog, 38  
 Digital-to-analog converter (DAC), 44–46, 52–54, 72, 84, 85, 96, 102, 103, 112  
 DNL. *See* Differential non-linearity (DNL)  
 DTMOSTs. *See* Dynamic threshold MOS transistors (DTMOSTs)  
 Dynamic correction techniques, xiv, 14, 57, 110  
 Dynamic element matching (DEM), 24, 33, 46, 52–54, 63–65, 73, 77, 83, 93, 99, 100, 103, 104, 113  
 Dynamic error correction techniques, 33, 34, 111  
 Dynamic range, xiv, 24, 25, 37, 38, 42, 112  
 Dynamic threshold MOS transistors (DTMOSTs), xiii, xv, xvi, 11–12, 15, 16, 91–100, 105–107, 110, 111, 113
- E**  
 Effective number of bits (ENOB), 25, 34, 41, 46, 48, 49, 51  
 Electro-thermal filter (ETF)-based sensors, 9, 10, 15  
 Energy efficiency, xiii–xvi, 5, 6, 13–16, 19, 26–34, 37, 38, 49, 57, 59, 68–70, 72, 80, 87, 91, 106, 107, 109–112  
 Energy-efficiency gap, xiv, 15, 31–32, 57  
 Energy per conversion, 13, 26, 28, 30, 31, 110  
 ENOB. *See* Effective number of bits (ENOB)  
 Environmental monitoring, 5, 25  
 ETF. *See* Electro-thermal filter (ETF)
- F**  
 Feed-forward, 70, 73, 102, 103  
 Figure of merit (FoM), xiii, xvi, 6, 13–15, 26, 28–34, 37, 38, 68, 69, 80–82, 106, 107, 110–112  
 Fine conversion, xiv, 42, 45, 46, 52, 57, 64–67, 70, 71, 73–75, 79, 80, 87, 100, 103, 110–112  
 1st-order zoom-ADC, 16, 49–54, 59, 64, 65, 68, 69, 95  
 FoM. *See* Figure of merit (FoM)  
 Forward current gain  $\beta_F$ , 22, 61–62  
 Front-end, xiv, 2, 13, 23, 26–33, 37, 54, 59–64, 70, 73, 74, 82–84, 93, 95, 98–100, 103–105, 110  
 Fully differential, 65, 67, 72
- G**  
 General-purpose, xvi, 13, 111  
 Generic bandgap temperature sensor, 23–25, 38  
 Guard-band, 70, 72  
 Guard-band cycle, 65  
 Guard-banding, 46–50, 102
- I**  
 Inaccuracy, xiv, xv, 6, 7, 9, 14, 15, 19, 31, 33, 55–57, 62, 67–69, 74–76, 78–82, 85–87, 91, 92, 94–97, 104–107, 109, 110  
 Incremental analog-to-digital converter, 111  
 Incremental mode, 32, 48  
 INL. *See* Integral nonlinearity (INL)  
 Integral nonlinearity (INL), 52, 111  
 Integrator, xv, 33, 44–46, 49–52, 64–67, 70–74, 84, 102, 103  
 Internet of things (IoT), 3  
 Inverter-based, xv, 100, 102–104, 107  
 Inverter-based OTA, 73, 84, 103
- K**  
 $kT/C$  noise, 67, 95, 112
- L**  
 Lateral NPN, 20  
 Leakage current, xv, 20, 81, 83–85, 94  
 Loop filters, xiv, 45, 46, 48, 49, 51, 52, 57, 70, 87, 110  
 Lot-to-lot spread, 113  
 Low-cost, 1, 6, 15, 16, 34, 79, 80

Low-cost calibration, 76  
 Low-swing, 70, 71, 87  
 Low-swing integrators., 46

## M

MEMS frequency references, 25  
 Military temperature range, 14, 15, 23, 24, 42,  
 72, 75, 87, 91, 92, 94, 110  
 MOSFET-based sensors, 10, 80, 92  
 Multi-bit digital-to-analog converter, 52

## N

Noise bandwidth, 27  
 Nyquist-rate analog-to-digital converter, 32, 33

## O

Offset trim, 56, 57, 76, 95, 96  
 Operating range, xiii, 4, 5  
 Out-of-ranging, 46, 47, 65

## P

Packaging shift, 79  
 Packaging stress, 7, 20, 57  
 Parasitic bipolar junction transistors, 8, 92,  
 107, 110  
 Parasitic vertical PNPs, 7  
 Passive radio frequency identification tags,  
 4–6  
 Phase-domain analog-to-digital converter, 9  
 Plastic packaging, xv, 78–79, 87  
 Proportional-to-absolute-temperature (PTAT),  
 xiii–xv, 7, 19, 21–23, 37–39, 55–57,  
 59–61, 63, 68, 74, 76–79, 82, 87, 92–94,  
 98, 100, 103, 104  
 Pseudo-differential, 72, 102  
 Pseudo-DNL, 53, 54, 80  
 PTAT. *See* Proportional-to-absolute-  
 temperature (PTAT)

## Q

Quantizer, 33, 34, 44, 46, 48, 52, 67, 70, 73,  
 103

## R

Radio frequency identification (RFID), xiii,  
 3–6, 111  
 Redundancy, 46–48  
 Reference sensor, xiii, 5, 54, 76

Residue, 44, 48  
 Resistor-based sensor, 9, 13, 15, 31  
 Resolution, xiv, xv, 6, 13–15, 24–27, 30–32,  
 34, 35, 37, 38, 40–42, 46, 48–50, 57,  
 64, 65, 67–70, 73, 75, 77, 78, 80–82,  
 86, 87, 97, 106, 109–112  
 Resolution figure-of-merit (FoM), 13, 14, 26,  
 31, 68, 69, 80–82, 106, 111  
 RFID tags. *See* Radio frequency identification  
 (RFID)

## S

Sample-and-hold, 52, 64, 72  
 SAR. *See* Successive Approximation (SAR)  
 SAR-ADC, xiv, 32, 34, 42, 43, 57, 64, 70, 94,  
 109, 112  
 SC. *See* Switched-capacitor (SC)  
 2nd-order zoom-ADC, xv, 48, 49, 59, 70, 72,  
 75, 84, 87, 105, 107, 111, 112  
 Self-biased, 74  
 Self-biasing opamp, 98  
 Sensing element, xv, 5–12, 14–15, 19, 91–97,  
 107, 109  
 Shot noise, 27  
 Single-point calibration, 31  
 Smart temperature sensor, xiii, 1, 2, 13, 19, 26,  
 30–32, 53, 60, 94, 110,  
 SM CVM. *See* Symmetrically matched  
 current-voltage mirror (SM CVM)  
 Substrate PNP, xiii, xv, 20, 22, 55, 59, 61, 62,  
 109, 110  
 Sub-threshold, 10–12, 91, 93  
 Successive Approximation (SAR), xiv, 32, 44,  
 64–66, 71, 94, 96, 97, 100, 103, 104,  
 111  
 Switched-capacitor (SC), xiv, xvi, 64, 65, 67,  
 71, 94, 101, 102, 112  
 Symmetrically matched current-voltage mirror  
 (SM CVM), 98, 99, 105  
 System-level chopping, 74, 100

## T

TD. *See* Thermal diffusivity (TD)  
 Temperature-to-digital conversion, 100  
 Thermal calibration, xv, 5, 76–78, 87, 113  
 Thermal diffusivity (TD), xvi, 9, 14, 81, 86,  
 88, 110, 112  
 Thermal equilibrium, 76  
 Thermal noise, 8, 13, 14, 27, 33  
 Thermistors, 1, 80, 81  
 Trimming, xiv, xv, 5, 9, 15, 19, 53–57, 68,  
 75–78, 81, 86, 87, 91, 95, 100, 105, 106

Two-step analog-to-digital converter, 42, 52, 79

Two-step zoom-ADC, xiv, 57, 109

## U

Unary-weighted capacitor digital-to-analog converter, 52

## V

Voltage calibration, xv, xvi, 76–79, 87, 113

## W

Wireless sensor networks (WSNs), xiii, 2, 5

Wireless sensors, 34

Wireless temperature sensing, xiii, 1, 14, 15, 19, 109

WSNs. *See* Wireless sensor networks (WSNs)

## Z

Zoom-ADC, xiv, xv, xvi, 15, 16, 34, 42–54, 57, 59, 60, 62, 64, 65, 68–72, 75, 84, 87, 94–96, 100, 102, 104, 105, 107, 109–112