

Index

A

- Adsorption enhanced CAES, 55
- Advanced adiabatic CAES
 - cooling demand, 57
 - IGDT based risk constrained bidding/offering strategy, 57
 - mathematical modeling, 58
 - schematic diagram, 55
- Agricultural energy hubs, 137–138
- Air-conditioning systems, 103, 104

B

- Battery electric vehicle (BEV)
 - tank-to-wheel assessment, 239
 - well-to-tank assessment, 238–239
- Bi-objective optimization model
 - economic objective function, 427–428
 - electrical model
 - DRP model, 431–432
 - electrical demand, 430
 - electrical, gas and water networks model, 432–433
 - HSS model, 430–431
 - renewable resources model, 430
 - environmental objective function, 428
 - thermal model, 429–430
- Boiler model, 429
- BONMIN solver, 122–126

C

- CAES, *see* Compressed air energy storage system
- CHP, *see* Combined heat and power
- CHP-based district heating systems, 3
- Combined cooling, heat and power (CCHP) system, 31–32, 134
- Combined heat and power (CHP) planning
 - CPLEX, 298
 - district heating scheme, 298
 - in electricity markets, 298
- system
 - boiler gas consumption, 441
 - electrical generation, 440, 441
 - gas consumption, 439, 440
 - model, 429
 - thermal generation, 440
- units
 - boiler, 272
 - dispatch factor, 283, 284, 288, 289, 291, 292
 - MINLP optimization, 272
 - natural gas, 271
 - optimization constraints, 276–277
 - part load ratio, 284, 285, 288, 290–292
- Commercial energy hubs, 135–136
- Compressed air energy storage (CAES) system, 411
 - adsorption enhanced CAES, 55

- Compressed air energy storage (CAES) system
 (*cont.*)
 advanced adiabatic CAES
 cooling demand, 57
 IGD based risk constrained
 bidding/offering strategy, 57
 mathematical modeling, 58
 schematic diagram, 55
 conventional CAES plants
 advantages, 55
 disadvantages, 55
 schematic diagram, 53, 54
 DEED problem
 electrical power generation limits, 60
 forecasted electricity market prices, 63,
 64
 fuel costs and emission productions, 74
 greenhouse gas emission mitigation, 59
 hourly generation schedules, 63, 67–70
 24-h load curve, 63
 nested wind generation intervals, 72
 objectives, 59
 optimal charge and discharge decisions,
 66, 71
 output power of thermal generating
 unit, 73
 Pareto optimal solutions, 63, 70
 power balance criterion, 60
 ramp rates, 60
 technical specification of thermal units,
 63, 64
 transmission loss B -coefficients, 63, 65
 weighing factors, 63, 70
 near-isothermal CAES, 55
 renewable-based hub energy system,
 170–171, 182, 183
 technical characteristics, 63, 66
 underwater CAES, 55–56
 Conditional value-at-risk (CVaR), 223, 224,
 229, 232
 ε -Constraint technique, 433
 Current operation point (COP), 340–341, 343
 CVaR, *see* Conditional value-at-risk
- D**
- Day-ahead optimal chiller dispatching
 problem, 104, 121
 DEED problem, *see* Dynamic economic
 emission dispatch problem
 Demand response program (DRP)
 advantages, 130
 in agricultural energy hubs, 137–138
 in commercial energy hubs, 135–136
 definition, 130
 electrical model, 431–432
 energy hub modeling
 CHP and wind turbine, 147–151
 converters constraints, 141–142
 demand constraints, 140–141
 electricity demand, 154–156
 ESS constraints, 142–143
 heat and natural gas, 145, 151–153,
 156–159
 hourly electricity price, 145, 146
 hourly wind speed, 145, 146
 MILP model, 146
 network constraints, 141
 objective function, 139–140
 optimal energy hub management
 problem, 145, 147
 real-time pricing schedule, 143
 schematic representation, 139
 environmental performance, 427
 hub energy system, 433, 434
 incentive-based program, 132
 in industrial energy hubs, 136–137
 long-term, 131
 MCENs, 392, 400–401
 multi-tariff meters, 131
 objective, 131
 PB program, 132
 photovoltaic powered multi-chiller plants,
 106–107
 renewable-based hub energy system, 171
 in residential energy hubs, 133–135
 short-term, 131
 smart energy hub, 13–16
 wind turbine model, 143–144
 Demand-side management (DSM), 2, 9–11,
 130, 133. *See also* Demand response
 program (DRP)
 DER, *see* Distributed energy resources
 DES, *see* Distributed energy systems
 DGs, *see* Distributed generations
 DHN, *see* District heating network
 Differential cuckoo search algorithm (DCSA),
 104, 121
 Distributed energy resources (DER)
 definition, 25
 multi-generation systems, 2
 optimal scheduling, 25
 PEV (*see* Plug-in electric vehicle)
 RES (*see* Renewable energy sources)
 Distributed energy systems (DES)
 advantages, 365–366
 energy hub approach, 366–367

- multi-energy hub network approach
 - (*see* Multi-energy hub network approach, DES)
- small-scale DES, 366
- Distributed generations (DGs), 297
 - RES, 24–26
 - VSC-WSPM model, 337
 - capacity constraints, 345–346
 - CF, daily variation of, 347, 349
 - DG owner and DSO, perspectives of, 354–359
 - DG owner’s perspective, 352–354
 - dispatchable DG units, characteristics of, 347, 349
- Distribution system operators (DSOs), 337, 350–351, 354–359
- District heating network (DHN)
 - carbon emission reduction and energy saving, 391
 - MCENs
 - continuity of mass flow, 397
 - heat-exchange station, 396
 - heat losses from pipe, 397–398
 - heat production, 396
 - heat sources, 395
 - mass flow rate limit, 398
 - node temperature, 397
 - pressure loss, 398
 - thermal storage, 399
 - water pumps, 396
- DRP, *see* Demand response program
- DSOs, *see* Distribution system operators
- Dynamic economic emission dispatch (DEED)
 - problem
 - electrical power generation limits, 60
 - forecasted electricity market prices, 63, 64
 - fuel costs and emission productions, 74
 - greenhouse gas emission mitigation, 59
 - hourly generation schedules, 63, 67–70
 - 24-h load curve, 63
 - nested wind generation intervals, 72
 - objectives, 59
 - optimal charge and discharge decisions, 66, 71
 - output power of thermal generating unit, 73
- Pareto optimal solutions, 63, 70
 - power balance criterion, 60
 - ramp rates, 60
 - technical specification of thermal units, 63, 64
 - transmission loss B -coefficients, 63, 65
 - weighing factors, 63, 70

E

- Economic chiller dispatching problem, 121
- Electricity and natural gas energy hubs, HSS and DRP
 - bi-objective optimization model
 - economic objective function, 427–428
 - electrical model, 430–433
 - environmental objective function, 428
 - thermal model, 429–430
 - input data
 - energy demands, 434
 - HSS and TSS parameters, 435, 436
 - prices and operation costs, 435, 436
 - thermal generation unit’s parameters, 435, 436
 - upper grid info, 435, 436
 - upper grid power price, 435
 - wind speed, 435
 - wind turbine parameters, 435, 437
 - literature review, 425–426
 - multi-objective problem
 - ε -constraint technique, 433
 - fuzzy satisfying approaches, 433
 - simulation results
 - boiler gas consumption, 441
 - CHP gas consumption, 439, 440
 - electrical generation, CHP system, 440, 441
 - electrical load, 438
 - Pareto front, 437
 - purchased power from upper grid, 438, 439
 - purchase gas from gas network, 438, 439
 - thermal generation, CHP system, 440
- Electric vehicles (EV)
 - arrival pattern, 242
 - BEV, 238–239
 - charging load profiles, 244–245
 - charging standards, 243
 - constant power charging approach, 243
 - constant time charging approach, 243
 - and electric utility interactions, 264–265
 - electric vehicle characteristics, 241, 242
 - vehicle data, 238
 - V2G and G2V (*see* Vehicle-to-grid and grid-to-vehicle)
 - well-to-wheel analysis, 237
- Energy hubs
 - DES, 366–367
 - generic energy hub model, 393

Energy hubs (*cont.*)
 MCENs (*see* Multi-carrier energy networks)
See also Multi-energy hub network approach, DES

Energy Information Administration (EIA), 238

Energy management system (EMS), 8

Energy not supplied (ENS) index, 214, 216–217

Energy storage system (ESS)
 CCHP production system, 31–32
 classification of, 27
 definition, 27
 demand shifting, 29
 in distribution systems, 337, 338
 economic dispatch model, 338
 economic objective, 338
 energy hub, 142–143
 base case, 36, 38–41
 base case+ES, 39–40, 42, 43
 base case+HS, 41, 43, 44
 base case+WT, 42, 44–46
 base case+WT+HS+ES, 44–45, 47
 components installation, 35
 demand, 36, 37
 electricity price, 36, 37
 input data and parameters, 36, 39
 objective functions, 33–35
 schematic representation, 33
 wind speed, 36, 38
 existing literature, 338–339
 information gap decision theory, 338
 multi-objective optimization model, 338
 optimal scheduling, 30–31
 PEV, 30
 RES integration, 28–29
 stochastic planning framework, 338
 system stability, 29
 voltage stability (*see* Voltage stability constrained wind-storage planning model)
 wind power penetration, 338

ESS, *see* Energy storage system

EV, *see* Electric vehicles

EVPI, *see* Expected value of perfect information

Expected value of perfect information (EVPI), 313, 329

F

Forced Outage Rate (FOR), 303

Fossil fuels, 1, 23, 365

Fuzzy decision making (FDM) method, 275

Fuzzy satisfying approaches, 433

G

GAMS SCENRED tool, 214

H

Heat storage, 280
 charging and discharging schedule, 293
 dispatch factor, CHP, 291, 292
 parameters, 282
 part load ratio, CHP, 291, 292
 purchased electricity, 291, 292
 purchased natural gas, 291
 PV curtailment, 273, 294

Home energy management systems, 134–135

HSS, *see* Hydrogen storage system

Hydrogen economy, 412

Hydrogen-enriched natural gas (HENG), 412–414

Hydrogen storage system (HSS)
 electrical model, 430–431
 electrolyzer and fuel cell unit, 426
 hub energy system, 426, 433, 434
 hydrogen molar, 426
 parameters, 435, 436

I

ICE vehicles, *see* Internal combustion engine vehicles

ICT, 7

IEEE 33-bus distribution test system
 charge/discharge cost of ESS, 349
 DG owner and DSO, perspectives of, 354–359
 DG owner's perspective, 352–354
 DGs' CF, daily variation of, 347, 349
 dispatchable DG units, characteristics of, 347, 349
 DSO, perspective of, 350–351
 energy price of ESS, 349
 ESS, characteristics of, 349
 load percentage based on peak load, 347, 348
 MINLP, DICOPT and IPOPT solvers, 347
 simulation parameters, 347, 348
 single line diagram, 347, 348

Incentive-based (IB) programs, 11, 132

Industrial energy hubs, 136–137

Information gap decision theory (IGDT), 57, 195, 338

Integrated demand response (IDR), 15

- Internal combustion engine (ICE) vehicles, 365
 - tank-to-wheel assessment, 240–241
 - vehicle data, 238
 - well-to-tank assessment, 240
 - well-to-wheel analysis, 237, 240

- L**
- Loadability limit point (LLP), 340–341, 344–345
- Loading margin (LM)
 - definition, 340
 - index, 340–341
 - PV curve, system LM, 340–341
- Load management (LM) programs, 9, 130
- Long-term smart grid planning
 - distribution network planning problem, 301
 - economic evaluation, 301–302
 - objective function, 301
 - stochastic planning model (*see* Stochastic planning model)
 - system uncertainties, 299–300
 - target reliability values, 303–304
- Loss of load expectation (LOLE) index, 214
- Loss of load probability (LOLP) index, 214

- M**
- Macro energy hubs
 - centralized control, 4, 5
 - decentralized/distributed control, 4, 5
 - integration and coordinated control, 3
 - MPC method, 4–5
 - OEF problem, 4, 5
 - optimal management, 5
 - two-layer hierarchy problem, 4
- MCENs, *see* Multi-carrier energy networks
- Methanation, 417
- Micro hubs, 3
- Mixed integer linear programming (MILP), 305, 367
- Mixed integer nonlinear programming (MINLP), 222, 272, 305, 347, 367, 404
- Model predictive control (MPC) method, 4–5
- Monte Carlo simulation (MCS) technique, 209, 214, 338
- Multi-agent genetic algorithm (MAGA), 223
- Multi-carrier energy networks (MCENs), 391
 - benefits, 392
 - demand response program, 392, 400–401
 - district heating networks, analysis of
 - continuity of mass flow, 397
 - heat-exchange station, 396
 - heat losses from pipe, 397–398
 - heat production, 396
 - heat sources, 395
 - mass flow rate limit, 398
 - node temperature, 397
 - pressure loss, 398
 - thermal storage, 399
 - water pumps, 396
 - generic energy hub model, 393
 - load flow equations
 - apparent power flow limits for branches, 400
 - exchangeable power limit, 400
 - Kirchhoff's laws, 399
 - voltage limits, 399
 - objective function, 394–395
 - structure, 394
 - three-hub test system
 - active and reactive loads, 401, 403
 - configuration, 401, 402
 - operational constraints, 401, 402
 - simulation results, 404–406
 - structure, 401–403
- Multi-carrier optimal dispatch, 200
- Multi-chiller plants
 - BONMIN solver, 122–126
 - centrifugal chillers, total electrical power, 122
 - chiller data, 122, 123
 - day-ahead optimal chiller dispatching problem, 121
 - DCSA, 121
 - economic chiller dispatching problem, 121
 - partial load ratio, 122
 - See also* Photovoltaic powered multi-chiller plants
- Multi-energy hub network approach, DES, 387
 - direct connections, converters, and storage, 369–370
 - energy storage modeling, 372–373
 - four energy hub system
 - areas of, 379
 - configurations, 384–385
 - economic cost and carbon dioxide emissions, 381–384, 386
 - energy conversion and storage technologies, 380–381
 - scenarios, 380, 385
 - solar energy vector, 380
 - framework development
 - energy hub and network model, 368
 - generic energy hub model,
 - superstructure of, 368–369
 - route map, 367, 368

Multi-energy hub network approach, DES
 (*cont.*)
 generic modeling and analysis framework,
 370–371
 network modeling, 373–374
 three energy hub system
 carbon dioxide emissions, 378, 379
 economic cost, 378–379
 Pareto optimality curve, 379
 technologies and energy vectors, 377
 two energy hub system
 carbon dioxide emissions, 376, 377
 economic cost, 376–377
 scenarios, 375
 technologies and energy vectors, 375
 Multi-energy systems (MES), 2
 Multi-generation system, 2, 3, 23, 392

N

Net present value (NPV), 342

O

Optimization problem, renewable-based
 residential energy hubs
 and components, 279–280
 electrical and heat demand, 282, 283
 gas to power efficiency
 on part load, 280, 281
 and power to heat ratio, 280, 285–288
 heat storage
 addition, 280, 291–294
 parameters, 282
 PHEV
 addition to proposed energy hub, 280,
 287–290
 and heat storage omission, 280,
 282–285
 parameters, 280, 281
 PV, power generation capability, 280, 282
 two-level TOU tariff, 280, 281

P

Petroleum fuels, 415
 PHEV, *see* Plug-in hybrid electrical vehicle
 Photovoltaic (PV) curtailment, 284, 285
 definition, 272
 heat storage system, 273
 power generation capability, 280, 282
 PV panels, 278
 Photovoltaic powered multi-chiller plants
 CCHP system, 104, 105

day-ahead optimal chiller dispatching
 problem, 104
 DCSA, 104
 DR programs, 106–107
 with four chillers
 chiller data, 111, 114
 climatic conditions, 111, 115
 cooling demand, 111, 114, 117
 electricity requirements, 116
 optimum loading points, 114, 116, 117
 power output of photovoltaic panels,
 111, 116
 solar radiations, 111, 115
 total energy cost, 114, 117
 partial load ratio, 105
 power balance criterion, 105
 ripple bee swarm optimization algorithm,
 103
 with six chillers
 ambient temperature variations, 109,
 110
 chiller data, 109, 111
 cooling demand, 108
 economic loading points, 110, 112–113
 hourly electricity rates, 109
 power output of photovoltaic panels,
 109, 110
 PV panel parameters, 109, 110
 SBB solver, 108
 solar irradiance, 109
 total energy cost, 114
 variations of cooling demand, 111
 solar photovoltaic cells, 105–106
 total electricity procurement cost, 107
 Plug-in electric vehicle (PEV), 9, 30, 134
 Plug-in hybrid electrical vehicle (PHEV), 272
 addition to proposed energy hub, 280
 charging and discharging schedule, 288,
 290
 dispatch factor, CHP, 288, 289
 outdoor consumption, 287, 288
 part load ratio, CHP, 288, 290
 purchased electricity, 288, 289
 purchased natural gas, 288, 289
 and heat storage omission, 280
 dispatch factor, CHP, 283, 284
 electricity purchased, 282, 284
 natural gas purchased, 282, 283
 part load ratio, CHP, 284, 285
 PV curtailment, 284, 285
 optimization constraints, 277–278
 parameters, 280, 281
 time scheduling, 273

- Polymer electrolyte membrane (PEM)
 - electrolyzers, 417–418
 - Power rating vs. discharge time of energy storage technologies, 53, 54
 - Power-to-gas energy systems
 - advantages, 411–412
 - alkaline electrolyzers, 417, 418
 - applications, 421–422
 - compressed gas storage, 418
 - hydrogen economy, 412
 - pathways, 419
 - power to hydrogen for zero-emission transportation, 412, 416
 - power to microgrid, 412, 416
 - power to natural gas end-users, 412–414
 - power to power, 412, 415
 - power to renewable content in petroleum fuels, 412, 415
 - power to renewable natural gas to pipeline, 412, 417
 - power to renewable natural gas to seasonal storage, 412, 417
 - power to seasonal energy storage to electricity, 412, 415
 - power to seasonal storage for transportation, 412, 416
 - technical and economic assessment, 418–421
 - PEM electrolyzers, 417–418
 - solid oxide electrolyzer, 417
 - Pressure Swing Adsorption (PSA), 416
 - Price-based (PB) programs, 11, 132
 - Pseudo-sequential Monte Carlo simulation technique, 209
 - PV curtailment, *see* Photovoltaic curtailment
- R**
- Renewable-based hub energy system
 - advantages, 191–192
 - co-and tri-generation, 190
 - components, 192
 - boiler unit, 228
 - CHP units, 227
 - PV system, 226
 - thermal and electrical energy storages, 228–229
 - wind turbine, 225–226
 - configuration of, 224, 225
 - cost function, 222
 - eco-emission performance
 - CAES, 170–171, 182, 183
 - DR program, 171
 - electrical energy demand, 178
 - electrical model, 167–168
 - electrical power generated by CHP unit, 180
 - gas consumption of boiler, 181
 - gas import, 179
 - generated heat by boiler, 181
 - heat generated by CHP unit, 180
 - imported power from upper network, 178
 - objective functions, 165–167
 - Pareto fronts, 176–177
 - thermal model, 168–170
 - used gas by CHP unit, 179
 - water network model, 171
 - electrical and thermal power balance, 229
 - energy demands, 173, 196–197
 - energy scheduling problem
 - conversion technologies, 198
 - direct connections, 198
 - flow diagram, 198, 199
 - hub components modeling, 197
 - input sources modeling, 197
 - mathematical model, 198, 200–201
 - solution algorithm, 201–203
 - storage devices, 198
 - time interval of operation, 197
 - transformers, 198
 - energy storage system, 164
 - environmental effects, 222
 - flow of power, 193
 - generation unit's info, 174
 - input–output relations, 189
 - iterative optimization algorithm, 222
 - MINP model, 222
 - multi-carrier energy system, 163, 164
 - objective function, 224–225
 - operation costs and prices, 175
 - renewable energy conversion systems, 193
 - risk-averse scheduling model, 229
 - risk controlling model, 223–224
 - robust based optimization approach, 163
 - schematic diagram, 172, 191
 - simulations, 230–233
 - solar energy modeling, 195
 - stochastic energy scheduling problem, 190
 - stochastic optimization scheduling
 - backward/forward technique, 214
 - charge and discharge schedule, 215
 - converter constraints, 212–213
 - demand response constraints, 214
 - electricity power shifts up and down, 215, 216
 - energy balance, 207, 211–212
 - ENS, 214, 216–217

- Renewable-based hub energy system (*cont.*)
 - imported (sold) electricity, 214, 215
 - LOLE, 214
 - LOLP, 214
 - network constraints, 212
 - objective function, 207, 210–211
 - overview of, 208
 - probabilistic optimization methods, 208–210
 - storage constraints, 208, 213
 - technical limitations, 207–208
 - total operation cost and reliability assessments, 217
 - uncertainty modeling, 203–206
 - wind power, 211
 - stochastic programming, 164
 - storage systems data, 175
 - upper grid info, 175
 - upper grid power price, 174
 - varying acceleration coefficient-gravitational search algorithm, 163
 - wind energy modeling, 194
 - wind generation info, 175
 - wind hourly speed, 173
 - Renewable energy sources (RES), 24–26
 - Renewable natural gas (RNG), 417–421
 - Residential energy hub system
 - activation time of appliances without solar thermal storage effect, 96
 - battery storage system, 82–84
 - boiler, 82
 - CHP generator, 81, 272, 276–277
 - DR program, 133–135
 - energy balance, 86
 - gas boiler, 278
 - heat storage, 279
 - household appliances, 84
 - household load scheduling problem, 80
 - imported/exported power, 84, 95
 - multi-carrier energy system, 271, 272
 - objective function, 274–275
 - operation cost of equipment, 81
 - optimal energy consumption scheduling, 81
 - optimization problem
 - and components, 279–280
 - electrical and heat demand, 282, 283
 - gas to power efficiency, 280, 281
 - heat storage parameters, 282
 - PV, power generation capability, 280, 282
 - two-level TOU tariff, 280, 281
 - PHEV (*see* Plug-in hybrid electrical vehicle)
 - power and heat flow equations, 275–276
 - PV curtailment, 278
 - definition, 272
 - heat storage system, 273
 - schematic diagram of, 81, 82
 - solar thermal storage, 95
 - activation time of appliances, 97
 - ambient temperature, 90
 - charge/discharge rate of battery storage system, 94, 95
 - earliest starting time of appliances, 89
 - electricity utilization profiles, 88
 - heat demand, 91, 92
 - latest finishing time of appliances, 89
 - market price, 90
 - MIP model, 87
 - output power of boiler, 93
 - output power of CHP, 93
 - power consumption and operation time of appliances, 87
 - solar irradiation, 91
 - state of charge of battery storage system, 94
 - technical constraints, 85, 87, 88
 - total operation cost, 92
 - stochastic programming, 79
 - structure, 273, 274
 - thermal balances, 86
 - total energy cost, 272
 - Ripple bee swarm optimization algorithm, 103
 - Risk-averse scheduling model, 229
 - Robust nonlinear programming (RNLP), 61
- S**
- Smart energy hub (SEH)
 - cloud computing, 15
 - commercial SEH, 14
 - definition, 16
 - dependent demand, 15
 - DR program, 13–16
 - efficiency, 14
 - game theory, 16
 - hydrogen infrastructure, 14
 - integrated management, 16, 17
 - operational optimization, 13
 - residential SEH, 14
 - TOU program, 13
 - Smart grid
 - challenges, 11–12
 - components, 7–11
 - definition, 6–7
 - Smart meter (SM), 7

- Solar thermal storage, 95
 - activation time of appliances, 97
 - ambient temperature, 90
 - charge/discharge rate of battery storage system, 94, 95
 - earliest starting time of appliances, 89
 - electricity utilization profiles, 88
 - heat demand, 91, 92
 - latest finishing time of appliances, 89
 - market price, 90
 - MIP model, 87
 - output power of boiler, 93
 - output power of CHP, 93
 - power consumption and operation time of appliances, 87
 - solar irradiation, 91
 - state of charge of battery storage system, 94
 - technical constraints, 85, 87, 88
 - total operation cost, 92
 - State of charge (SOC), 346–347, 349, 356–358
 - Steam Methane Reforming (SMR), 415, 420–421
 - Stochastic expansion model, 297–298
 - Stochastic planning model
 - multiobjective optimization problem, 305
 - power losses linearization, 305–306
 - proposed methodology, 307
 - average wind and solar power prediction, 316, 317
 - 13-bus distribution network, 314
 - CHP heat and electricity supply, 318
 - cogeneration units, feasibility region, 322, 323
 - controllable DG units and external suppliers, 311
 - district heating, 312, 313, 318, 319
 - energy resource data, 315, 316
 - energy storage systems constraints, 311–312
 - evaluation metrics, 313
 - expected planning cost, 308–309
 - generation curtailment power, 312
 - heat demand data, 318, 322
 - heat resource data, 318, 322
 - initial reliability indexes, 318, 319
 - input data, 306
 - intermittent energy resources and consumers predictions, 315, 316
 - lines thermal limits, 318, 320, 321
 - load and heat demand predictions, 315
 - load demand and consumers prediction, 316, 317
 - network grid constraints, 309–310
 - number of consumers prediction, 315, 316
 - reliability indexes limits, 311
 - scenarios generation, 306
 - scenarios reduction, 306, 308
 - standard deviation, each resource, 315
 - two-stage planning method, 304
 - cost results, 327, 328
 - economic evaluation, 327, 328
 - EVPI and VSS, 329
 - expected SAIDI index, 329, 330
 - expected SAIFI index, 329, 330
 - expected total costs, 328
 - initial costs with and without district heating, 324, 325
 - initial working radial topology considering district heating, 323, 324
 - initial working radial topology without district heating, 323, 324
 - new lines construction, 327
 - peak memory and execution time, 323
 - total costs and monetary benefits, 327, 328
 - Z^{*} radial topology, 325–327
 - System Average Interruption Duration Index (SAIDI), 303–304, 329, 330
 - System Average Interruption Frequency Index (SAIFI), 303–304, 329, 330
- T**
- Time of use (TOU) pricing, 134
 - TSS model, 429–430
 - Two-stage planning method, 304
 - cost results, 327, 328
 - economic evaluation, 327, 328
 - EVPI and VSS, 329
 - expected SAIDI index, 329, 330
 - expected SAIFI index, 329, 330
 - expected total costs, 328
 - initial costs with and without district heating, 324, 325
 - initial working radial topology considering district heating, 323, 324
 - initial working radial topology without district heating, 323, 324
 - new lines construction, 327
 - peak memory and execution time, 323
 - total costs and monetary benefits, 327, 328
 - Z^{*} radial topology, 325–327
 - Two-stochastic model, 297

V

- Value of stochastic solution (VSS), 313, 329
- Varying acceleration coefficient-gravitational search algorithm, 163
- Vehicle-to-grid (V2G) and grid-to-vehicle (G2V)
 - of aggregation, 252–257
 - arrival times, 250, 251
 - charging and discharging
 - constant current (CC) stage, 251–252
 - constant power (CP) charging, 252
 - constant time (CT) charging, 252
 - constant voltage (CV) charging, 252
 - load leveling, 260–263
 - power levels, 251
 - reserve capacity commitment, 257–260
 - energy consumption, 248, 250
 - mobility attributes, 246–248
- Voltage stability constrained wind-storage planning model (VSC-WSPM)
 - charge/discharge costs, 339
 - DG capacity constraints, 345–346
 - DG owner, 339
 - added capacity of DGs, 352
 - added capacity of ESSs, 352
 - total capacity of DGs, 353
 - total capacity of ESSs, 353
 - DG owner and DSO
 - added capacity of DGs, 354, 355
 - added capacity of DGs with and without ESS, 356, 357
 - added capacity of ESSs, 354, 355
 - cash flow, DG owner's profit, 354
 - DG owner profit and power generation cost, 354
 - P-V curves, 358, 359
 - SOC, 356–358

- total capacity of DGs, 355, 356
- total capacity of ESSs, 355, 356
- OF variation vs. interest rate changes, 357, 358
- DSO, 339
 - added capacity of DGs, 350
 - added capacity of ESSs, 350
 - total capacity of DGs, 351
 - total capacity of ESSs, 351
- ESS constraints, 346–347
- loading margin index, 340–341
- objective functions
 - ESS charge/discharge costs minimization, 341–342
 - overall objective function, 342
 - power generation costs minimization, 341
 - profit maximization, wind energy procurement, 342
 - total objective function, 342
 - weighting coefficients, 342
 - wind energy procurement, profit maximization, 342
- power balance constraints at COP, 343
- power balance constraints at LLP, 344–345
- power generation costs, 339
- standard test system, 347–349
- system load growth, 345
- VSS, *see* Value of stochastic solution

W

- Wait-and-see solution (WSS), 313
- Water network model, 171
- Weighting coefficients, 342
- Wind generation uncertainties, 60–62
- Wind turbine model, 143–144