

References

- Bhardwaj, V., & Singh, V. K. (2017). Study of liquid sealed no-core fiber interferometer for sensing applications. *Sensors and Actuators A*, 254, 95–100.
- Bowei, Z. (2004). *High temperature sensors based on hydrogen loaded fiber Bragg gratings*. M. Sc. Thesis. Concordia University, Canada.
- Bowei, Z., & Mojtaba, K. (2005). Characteristics of Fiber Bragg Grating Temperature Sensor at Elevated Temperatures. In *Proceedings of the 2005 International Conference on MEMS, NANO and Smart Systems (ICMENS'05)*.
- Chettouh, S., Akrimi, A. E., Triki, H., & Hamaizi, Y. (2017). Spectral properties of nonlinearly chirped fiber Bragg gratings for optical communications. *Optik*, 147, 163–169.
- Daud, S., & Noorden, A. F. A. (2016). Fibre Bragg grating sensor system for temperature application. *Jurnal Teknologi*, 78(3), 39–42.
- Daud, S., Aziz, M. S., Chaudhary, K. T., Bahadoran, M., & Ali, J. (2016). Sensitivity measurement of fibre Bragg grating sensor. *Jurnal Teknologi*, 78(3), 277–280.
- Daud, S., Jalil, M. A., Najmee, M. S., Saktioto, S., Ali, J., & Yupapin, P. P. (2011). Development of FBG sensing system for outdoor temperature environment. *Procedia Engineering*, 8, 386–392.
- Edmon, C., Chen, C. Y., Stephen, E. S., Stephen, J., & Ralph, P. T. (2004). Characterization of the response of fibre Bragg gratings fabricated in stress and geometrically induced high birefringence fibres to temperature and transverse load. *Institute of Physics Publishing, UK*, 13, 894–895.
- Fasano, A., Woyessa, G., Janting, J., Rasmussen, H. K., & Bang, O. (2017). Solution-mediated annealing of polymer optical fiber Bragg gratings at room temperature. *IEEE Photonics Technology Letters*, 29(8), 687–690.
- Fei, C. Y., Qun, H., & Liu, T. G. (2015). All-fiber optical modulator based on no-core fiber and magnetic fluid as cladding. *China Physics B*, 24(1), 014214.
- Filho, E. S. D. L., Baiad, M. D., Gagné, M., & Kashyap, R. (2014). Fiber Bragg gratings for low-temperature measurement. *Optics Express*, 22(22)
- Georges, T., Delevaque, E., Monerie, M., Lamouler, P., & Bayon, J. F. (1992). Pair induced quenching in erbium doped silicate fibers. *IEEE Optical Amplifiers and Their Applications, Technical Digest*, 17, 71.
- Gouveia, C., Jorge, P. A. S., Baptista, J. M., & Frazoa, O. (2011). Temperature-independent curvature sensor using FBG classing modes based on a core misaligned splice. *IEEE Photonics Technology Letter*, 23(12), 804–806.
- Grattan, K. T. V., & Meggit, B. T. (2000). *Optical fiber sensor: Advanced applications—Bragg gratings and distributed sensors*. Boston: Kluwer Academic Publishers.
- Hill, K. O. (2002). *Fiber optics handbooks—fiber, devices, and systems for optical communication*. McGraw-Hill.

- Hill, K. O., Fujii, Y., Johnson, D. C., & Kawasaki, B. S. (1978). Photosensitivity in optical fiber waveguides: Application to reflection filter fabrication. *Applied Physics Letter*, 32(10), 647–649.
- Hirayama, N., & Sano, Y. (2000). Fiber Bragg grating temperature sensor for practical use. *ISA Transaction*, 39, 169–173.
- Ho, S. P. (2008). *Properties of fabricated fiber Bragg grating for temperature sensing using phase mask technique*. Master Thesis, UTM.
- Ho, S. P., Ali, J., Rahman, R. A., & Saktioto (2008). Growth dynamics and characteristics of fabricated fiber Bragg grating using phase mask method. *Workshop on Recent Advances of Low Dimensional Structures (WRA-LDSD)*.
- Huang, L. S., Lin, G. R., Fu, M. Y., Sheng, H. J., Sun, H. T., & Liu, W. F. (2000). A refractive-index fiber sensor by using no-core fibers (pp. 100–102). IEEE.
- Jeff, H. (2002). *Understanding fiber optics (fourth edition)* (pp. 153–157). London: Prentice Hall.
- Juergens, J. (2005). *Thermal evaluation of fiber Bragg gratings at extreme temperatures*. Canada Technology and Communication Research Center.
- Jung, J. (1999). Fiber Bragg grating temperature sensor with controllable sensitivity. *Applied Optics*, 38(13), 2752–2754.
- Kashyap, R. (1999). *Fiber Bragg gratings* (pp. 185–189). London: Academic Press Inc.
- Kaur, G., Kaler, R. S., & Kwatra, N. (2017). Investigations on highly sensitive fiber Bragg gratings with different grating shapes for far field applications. *Optik*, 131, 483–489.
- Kawasaki, B. S., Hill, K. O., Johnson, D. C., & Fuji, Y. (1978). Narrow-band Bragg reflectors in optical fibers. *Optics Letter*, 3, 66–68.
- Krishna, V., Fan, C. H., & Longtin, J. P. (2000). Real-time precision concentration measurement for flowing liquid solutions. *Revision Science Instrument*, 71, 3864–3868.
- Kumara, J., Prakash, O., Mahakuda, R., Agrawal, A. K., Dixit, S. K., Nakhe, S. V., et al. (2017). Wavelength independent chemical sensing using etched thermally regenerated FBG laser systems engineering. *Sensors and Actuators B*, 244, 54–60.
- Lai, Y. C., Qiu, G. F., Zhang, W., Zhang, L., Bennion, I., & Granttan, K. T. V. (2002). Amplified spontaneous emission-based technique for simultaneous measurement of temperature and strain by combining active fiber with fiber gratings. *Review of Instrument, American Institute of Physics (AIP)*, 73(9).
- Lam, D. K. W., & Garside, B. K. (1981). Characterization of single-mode optical fiber filters. *Applied Optics*, 20, 440–445.
- Li, C., Ning, T., Wen, X., Li, J., Zhang, C., & Zhang, C. B. (2015). Magnetic field and temperature sensor based on nano-core fiber combined with a fiber Bragg grating. *Optics & Laser Technology*, 72, 104–107.
- Li, C., Ning, T., Zhang, C., Li, J., Wen, X., Pei, L., et al. (2016). Liquid level measurement based on a no-core fiber with temperature compensation using a fiber Bragg grating. *Sensors and Actuators A*, 245, 49–53.
- Li, J., Zhang, W., Gao, S., Bai, Z., Wang, L., Liang, H., et al. (2014). Simultaneous force and temperature measurement using S fiber taper in fiber Bragg grating. *IEEE Photonics Technology Letters*, 26(3), 309.
- Li, L., Xia, L., Wuang, Y., Ran, Y., Yang, C., & Liu, D. (2012). Novel NCF-FBG interferometer for simultaneous measurement of refractive index and temperature. *IEEE Photonics Technology Letters*, 24(24), 2268–2271.
- Li, W., Cheng, H., Xia, M., & Yang, K. (2013). An experimental study of pH optical sensor using a section of no-core fiber. *Sensors and Actuators A*, 199, 260–264.
- Lia, S., Li, X., Yang, J., Zhou, L., Che, X., & Binbin, L. (2016). Novel reflection-type optical fiber methane sensor based on a no-core fiber structure. *Materials Today: Proceedings*, 3, 439–442.
- Lin, G. R., Fu, M. Y., Lee, C. L., & Liu, W. F. (2014). Dual-parameter sensor based on a no-core fiber and fiber Bragg grating. *OE Letters*, 53(5), 050502-1-3.

- Liu, H. B., Hiu, H. Y., Peng, G. D., & Chu, P. L. (2013). Strain and temperature sensor using a combination of polymer and silica fibre Bragg gratings. *Optics Communications*, 219, 139–142.
- Liu, Y., & Zhang, J. (2016). Model study of the influence of ambient temperature and installation types on surface temperature measurement by using a fiber Bragg grating sensor. *Sensors*, 16, 975.
- Lopez, J. E. A., Mondragon, J. J. S., LiKamWa, P., & Arrijoja, D. A. M. (2004). Fiber-optic sensor for liquid level measurement. *Optic Letter*, 36(17), 3425–3427.
- Malo, B. (1995). Apodised in fiber Bragg grating reflectors photoimprinted using a phase mask. *Electronic Letters*, 31, 223–225.
- Meltz, G., Morey, W. W., & Glen, W. H. (1989). Formation of Bragg gratings in optical fibre by transverse holographic method. *Optics Letters*, 14(15), 823–825.
- Miao, Y. P., Ma, X., He, Y., Zhang, H., Zhang, H., Song, B., et al. (2016). Low-temperature-sensitive relative humidity sensor based on tapered square no-core fiber coated with SiO₂ nanoparticles. *Optical Fiber Technology*, 29, 59–64.
- Michael, K., Simon, K., Johanne, H., Christian, B., Axel, S. H., Frank, V., et al. (2014). Fabrication and characterization of Bragg gratings in a graded-index perfluorinated polymer optical fiber. *Procedia Technology*, 15, 138–146.
- Morey, W. M., Ball, G. A., & Meltz, G. (1994). Photoinduced Bragg gratings in optical fibers. *Optics and Photonics News*, 8–14.
- Muhs, J. D. (2007). Design and analysis of hybrid solar lighting and full spectrum solar energy system. *Oak Ridge National Laboratory*.
- Mulle, M., Wafai, H., Yudhanto, A., Lubineau, G., Yaldiz, R., Schijve, W., et al. (2016). Process monitoring of glass reinforced polypropylene laminates using fiber Bragg gratings. *Composites Science and Technology*, 123, 143–150.
- Neil, J. G. (1999). Development of temperature compensated fiber optic strain sensors based on fiber Bragg gratings. University of Toronto.
- Othonos, A. (1997). Fiber Bragg gratings. *Review of Scientific Instruments*, 68, 4309–4341.
- Othonos, A., & Kalli, K. (1999). *Fiber Bragg gratings: Fundamentals and applications in telecommunication and sensing*. Boston (USA): Artech House Inc.
- Park, J., Kwon, Y. S., Ko, M. O., & Jeon, M. Y. (2017). Dynamic Fiber bragg grating strain sensor interrogation with real-time measurement. *Optical Fiber Technology*, 38, 147–153.
- Pedersen, J. K. M., Woyessaa, G., Nielsena, K., & Bang, O. (2017). Effects of pre-strain on the intrinsic pressure sensitivity of polymer optical fiber Bragg gratings. In *Proceedings of SPIE*.
- Rahman, R. A., Ikhsan, S., & Supian, H. M. (2000). Fibre optic Bragg grating sensors: A new technology for smart structure monitoring in Malaysia. *IEEE*. 0-7803-6355-8.
- Ramesh, S. K., Kuo, C. W., Righini, G. C., & Najafi, S. I. (1999). Design and fabrication of a Fiber Bragg Grating Temperature Sensor. *International Society for Optical Engineering Proceedings Series*.
- Ran, Y., Xia, L., Han, Y., Li, W., Rohollahnejad, J., Wen, Y., et al. (2015). Vibration fiber sensors based on SM-NC-SM fiber structure. *IEEE Photonics Journal*, 7(2), 6800607.
- Rezayat, A., De Pauw, B., Lamberti, A., El-Kafafy, M., Nassiri, V., Ertveldt, J., et al. (2016). Reconstruction of impacts on a composite plate using Fiber Bragg Gratings (FBG) and inverse methods. *Composite Structures*, 149, 1–10.
- Ronald, S. (2003). Seeing the light. Trade & Industry.
- Shilton, A. N., Powell, N., Mara, D. D., & Craggs, R. (2008). Solar-powered aeration and disinfection, anaerobic co-digestion, biological CO₂ scrubbing and biofuel production: The energy and carbon management opportunities of waste stabilisation ponds. *Water Science Technology*, 58(1), 253–258.
- Simpson, A. G. (2005). Optical fibre sensor and their application. Ph.D. Thesis, Aston University.
- Strasser, T. A., Pedrazzai, J. R., & Andrejio, M. J. (1997). Reflective mode conversion with UV-induced phase grating in two-mode fiber. In *Conference on Optical Fiber Communication (OFC) 1997* (pp. 16–21). Dallas, TX: FRS.

- Snyder, A. W., & Love, J. D. (1983). *Optical waveguide theory*. London: Chapman & Hall.
- Tanaka, T. (2002). 100 GHz Spacing 8-channel light source integrated with gratings and LDs on PLC platform. Technical Report of IEICE.
- Tahir, B. A., Ali, J., & Rahman, R. A. (2005). Strain measurements using fibre Bragg grating sensor. *American Journal of Applied Science (Special Issue)*, 40–48.
- Song, Z. J., Zhong, H. Q., Wei, L. X., Wu, Z. M., & Xia, G. Q. (2015). Experimental investigations on nonlinear dynamics of a semiconductor laser subject to optical injection and fiber Bragg grating feedback. *Optics Communications*, 354, 213–217.
- Su, G., Shi, J., Xu, D., Zhang, H., Xu, W., Wang, Y., Feng, J., & Yao, J. (2016). Simultaneous magnetic field and temperature measurement based on no-core fiber coated with magnetic fluid. *IEEE Sensors*, 1–5.
- Udd, E., Nelson, D., & Lawrence, C. (1997). Multiple axis strain sensing using fibre gratings written onto birefringent single mode optical fibre. *Optical Fibre Sensors*, 354–357.
- Wang, X., Dong, X., Zhou, Y., Ni, K., Cheng, J., & Chen, Z. (2013). Hot-wire anemometer based on silver-coated fiber Bragg grating assisted by no-core fiber. *IEEE Photonics Technology Letters*, 25(24), 2458–2461.
- Wang, Y., & Wen, Y. (2016). Temperature and strain sensing properties of the zinc coated. *Optik*, 127, 6463–6469.
- Woyessa, G., Pedersen, J. K. M., Fasano, A., Nielsen, K., Markos, C., Rasmussen, H. K., & Bang, O. (2017). Simultaneous measurement of temperature and humidity with microstructured polymer optical fiber Bragg gratings. SPIE. 10323. 103234T-1.
- Xia, L., Li, L., Li, W., Kou, T., & Liu, D. (2013). Novel optical fiber humidity sensor based on a no-core Fiber structure. *Sensors and Actuators A*, 190, 1–5.
- Xiaopei, C., Yan, Z., Gang, P., & Jiju, A. (2004). Experimental design in fiber optic development. *International Journal of Productivity and Performance*, 53, 8.
- Xie, J., Li, H., Gao, L., & Liu, M. (2017). Laboratory investigation of rutting performance for multilayer pavement with fiber Bragg gratings. *Construction and Building Materials*, 154, 331–339.
- Yang, H. Z., Ali, M. M., Islam, M. R., Lim, K. S., Gunawardena, D. S., & Ahmad, H. (2015). Cladless few mode fiber grating sensor for simultaneous refractive index and temperature measurement. *Sensors and Actuators A*, 228, 62–68.
- Yao, Q., Meng, H., Wang, W., Xue, H., Xiong, R., Huang, B., et al. (2014). simultaneous measurement of refractive index and temperature based on a core-offset Mach-Zehnder interferometer combined with a fiber Bragg grating. *Sensors and Actuators A*, 209, 73–77.
- Yonghang, S., Jinglei, H., Weizhong, Z., Tong, S., Kenneth, T. V. G., & William, D. N. P. (2004). Fiber-optic sensor system for heat-flux measurement. *Review of Scientific Instruments*.
- Yua, H. C., Fan, Z. Y., Xia, Z. M., Gordone, L. L. M., & Qiang, L. L. (2016). Application of FBG sensors for geotechnical health monitoring, a review of sensor design, implementation methods and packaging techniques. *Sensors and Actuators A*, 244, 184–197.
- Zhang, C., Xu, S., Zhao, J., Li, H., Bai, H., & Miao, C. (2017). Intensity-modulated refractive index sensor with anti-light source fluctuation based on no-core fiber filter. *Optics and Laser Technology*, 97, 358–363.
- Zhang, R., Man, J., Liu, W., Zhou, W., & Yang, Y. (2015). A multi-band access radio-over-fiber link with SSB optical millimeter-wave signals based on optical carrier suppression modulation. *Optical Switching and Networking*, 18, 235–241.
- Zhou, G., Wu, Q., Kumar, R., Ng, W. P., Liu, H., Niu, L. F., et al. (2017). High sensitivity refractometer based on reflective SMF-small diameter no core fiber structure. *Sensors*, 17 (1415), 1–9.
- Zhang, C., Xu, C., Zhao, J., Li, H., Bai, H., & Miao, C. (2017). Intensity-modulated refractive index sensor with anti-light source fluctuation based on no-core fiber filter. *Optics and Laser Technology*, 97, 358–363.

- Zhang, W., Ying, Z., Yuan, S., & Tong, Z. (2015). A fiber laser sensor for liquid level and temperature based on two taper structures and fiber Bragg grating. *Optics Communications*, *342*, 243–246.
- Zhao, J., Wang, J., Zhang, C., Guo, C., Bai, H., Xu, W., et al. (2016). Refractive index fiber laser sensor by using tunable filter based on no-core fiber. *IEEE Photonics Journal*, *8*(5), 6805008.
- Zhou, G., Wu, Q., Kumar, R., Ng, W. P., Liu, H., Niu, L., et al. (2017). High sensitivity refractometer based on reflective SMF-small diameter no core fiber structure. *Sensors*, *17* (1415), 1–9.
- Zibai, M. I., Latifi, H., Karamia, F., Ronaghi, A., Nejad, S. C., & Dargahi, L. (2005). In Vivo brain temperature measurements based on fiber optic Bragg grating. In *Proceedings of SPIE*. 10323. 103234G-1.

Index

B

- Bandwidth, 2, 4, 9, 12, 16, 18–21, 33–35, 38, 39, 41, 42, 45–47, 49, 50, 55, 62, 63, 66–68, 73
- Bragg grating, 6–9, 16, 18, 20–23, 29, 71
- Bragg wavelength, 2, 4, 5, 8–11, 16–20, 22–24, 26, 28, 29, 34–36, 38, 39, 41–45, 47–50, 52, 54–60, 62, 64, 66–70, 73
- Buffer, 32

C

- Center wavelength, 10, 17, 18, 21, 23, 24, 26, 31, 33, 39, 44, 63–67, 73
- Cladding, 3, 10, 13, 15, 16, 30, 32
- Coherent light, 7
- Communication, 2, 3, 12
- Convex lens, 33, 52, 56–58, 60–62, 64
- Coupled-mode theory, 4, 15, 21
- Coupling coefficient, 21

D

- Deviation, 48, 49
- Diameter, 29, 30

E

- Electric field, 22
- Electromagnetic Interference, 3, 11
- Electron, 30
- Engineering, 5
- Environment, 3, 4, 13, 32, 33, 39, 52, 64
- Excimer laser, 11, 30, 31

F

- Fabrication technique, 8, 9, 11, 29–32
- Fibre Bragg grating, 1–3, 5–8, 11, 16, 25, 26, 30, 33, 35, 36, 39, 41, 42, 47–49, 51, 52, 55, 56, 62–66, 73

- Fibre core, 2, 5, 7, 10, 11, 17, 18, 21, 26, 28–30, 32
- Fibre grating, 19, 22, 30
- Fibre optics, 5
- Fibre optic sensor, 2
- Focusing lens, 55, 56
- Full width at half maximum, 44, 45, 71

G

- Graph, 42, 43, 47–49, 55, 57–60, 63, 64, 68–71
- Grating length, 20, 21, 61
- Grating period, 9, 11, 16, 24, 25, 27–29

H

- Hand lens, 33, 52, 56, 58–62, 64
- Height, 35, 55–57, 59, 60, 62–64
- High Birefringent, 10
- Humidity, 11

I

- Incident light, 3, 13, 17, 18, 25
- Instrument, 1
- Interference, 3, 5, 7, 8, 11, 13

L

- Laser, 2, 7, 8, 17, 28, 31, 34, 36
- Light, 2, 3, 5–9, 11–13, 15–18, 20, 26–28, 30–33, 35, 36, 38, 51, 63, 64
- Linear, 3, 10, 11, 15, 42, 55, 64, 68, 70, 73

M

- Magnetic field, 22
- Modal wavevector, 17, 18, 26
- Multi-mode fibre, 32

N

- NCF wavelength, 68
- No-Core Fibre, 1, 3, 5

no-Core Fibre, 13, 32, 36, 65–67, 73
 Nonlinear effects, 2
 Numerical aperture, 29

O

Optical fibre, 2, 3, 5, 8–10, 12, 16, 18, 20, 24, 30, 32, 42, 51
 Optical response, 4, 22–24
 Optical spectrum analyzer, 10, 33

P

Percentage, 17, 18, 25, 30
 Performance, 3, 4, 10, 39, 52
 Photon, 18, 26
 Photosensitivity, 2, 7, 22, 30
 Power dip, 21, 22, 34, 35, 38, 41, 42, 44, 46, 55, 63, 66–68
 Pressure, 4, 22, 32

R

Radiation, 2, 12, 30
 Reflection, 3, 4, 8, 9, 13, 15, 16, 19–22, 25–28, 34–37, 39–41, 52, 53, 55–62, 64, 73
 Reflectivity, 2, 4, 8, 19–22, 27, 29, 31, 33, 34, 41, 42, 44, 46, 47, 49, 50, 55, 62–64
 Refractive index, 2, 5, 9, 11, 12, 16–18, 20, 21, 23–30, 34, 39, 46, 47, 49, 64
 Resonance, 21
 Room temperature, 10, 39, 52, 65

S

Science, 5
 Sensing, 2–5, 8–13, 33, 35, 36, 38, 47, 48, 52, 64–66, 73

Sensitivity, 3, 4, 9–13, 33, 35, 47–49, 55–62, 64, 65, 68, 71
 Sensor, 1–4, 8–13, 16, 17, 30, 33–35, 39, 45, 47–49, 51, 52, 55, 59–62, 64, 65, 68, 70, 73
 Sensor head, 52, 55–57, 59, 61, 64, 73
 Signal, 1, 12, 13, 16, 36
 Single-mode fibre, 3, 5, 13, 15, 16, 35, 51
 Solutions, 15, 34, 36, 42, 46, 47, 49, 66–71
 Spectra, 4, 16, 19, 25, 34, 35, 38, 39, 52, 53, 55, 56, 58, 60, 62, 64–68, 71
 Spectrum, 2, 9, 10, 16, 19, 30, 33, 35–41, 44, 46, 52, 55–57, 59, 63–68, 71
 Splicing technique, 32
 Strain, 3, 4, 8–12, 16, 17, 22–24, 30, 55

T

Telecommunication, 2, 10, 35
 Temperature, 1–4, 9–12, 16–18, 22–24, 30, 33–39, 41–52, 55–61, 63–66, 68–71, 73
 Thermo-expansion coefficient, 18, 42
 Thermo-optic coefficient, 18, 25, 42
 Transmission, 4, 9, 10, 12, 16, 20, 21, 25–27, 32, 34–36, 38–40, 52, 53, 55–62, 64, 66, 73
 Tunable laser source, 33

W

Wavelength, 2–5, 7–10, 12, 13, 16–23, 26–30, 32, 35, 36, 38, 39, 42, 44, 47–49, 55, 62–65, 67, 69–71
 Writing technique, 6–9, 22