

Index

A

- Access point (AP), 32, 101, 231
- Analytical framework, 35, 131, 167, 186, 216, 235
- Applications
 - event detection (ED), 7
 - query-based, 124, 161, 216
 - Spatial process estimation (SPE), 7
- Area throughput, 213, 219
 - aggregation strategy, 220
 - comparing non beacon- and beacon-enabled, 224
 - success probability, 216

B

- Beacon, 10, 76, 138
- Beacon interval, 15, 138, 164, 233
- Beacon order, 15, 164, 233
- Beacon-enabled
 - modelling, 188
 - sensing probability, 189
 - success probability, 195–196
 - transmission
 - probability, 194, 198
- Bimodal behavior, 44
- Binary symmetric channel (BSC), 34, 190
- Bit-flipping, 110
- Bound
 - lower, 56, 236
 - upper, 56
- Boundary
 - single, 106
 - multi, 107

C

- Capacity constraint, 131, 133
- Carrier sense multiple access with collision-avoidance (CSMA/CA), 13, 163
- Channel code
 - BCH, 88
 - error correction capability, 87
 - LDPC, 89
 - repetition, 79
 - systematic block, 80
- Channel model, 126
- Characterization
 - communication-theoretic, 39
 - communication/information-theoretic, 44
- Clustering
 - non-uniform, 37, 237
 - uniform, 35, 237
- Codeword, 83
- Collision-less, 131, 232–233
- Comparing beacon- and non beacon-enabled, 209, 224
- Complexity
 - computational, 118
 - reduced-complexity, 107
- Connectivity, 123, 128, 132, 147, 217
- Contention access period (CAP), 15, 163
- Contention free period (CFP), 15, 164
- Control message, 54

D

- Data gathering, 215, 232
- Decision threshold, 33, 70, 103
- Decoding and fusion
 - joint, 82
 - separate, 81

D (*cont.*)

- Delay, 48, 67, 88, 203
- Distance
 - Hamming, 86
 - quadratic, 112
- Distributed detection, 32, 235

E

- Energy
 - consumption, 60
 - consumption model, 154
 - efficiency, 5, 67
 - infinite battery, 60
 - lifetime, 51
 - limited battery, 63
 - penalty, 61
- Entropy, 45
- Experiments, 50

F

- Fading, 34
- Full function device (FFD), 12, 129
- Fusion
 - algorithm, 101
 - majority-like, 35
 - simplified fusion rule, 102
- Fusion center (FC), 31

G

- Guaranteed time slots (GTSs), 15, 139, 163, 186

I

- IEEE 802.15.4
 - association procedure, 18
 - beacon-enabled, 15, 163, 186
 - data transfer, 16
 - frames, 16
 - MAC layer, 13
 - non beacon-enabled, 13, 162
 - physical layer, 9
 - technology, 9
 - topologies, 10
- Impairments, 232
- Interplay, 79, 231

L

- Link connectivity
 - bounded regions, 147, 152
 - Infinite plane, 129, 132, 147

Loss

- energetic, 42
- percentage, 114
- relative, 114, 242

M

- MicaZ, 50, 76
- Minimum mean square error (MMSE), 102
- Monotonic, 108
- Mote
 - firing, 76
 - mobile, 76
- Multiple observations, 79
- Mutual information, 45

N

- Network connectivity
 - infinite plane, 131
 - multi-hop, bounded regions, 153–154
 - single-hop, bounded regions, 149
- Network cost, 223, 241
- Noisy communication links, 32, 39, 43, 232
- Non beacon-enabled
 - energy consumption, 117
 - modelling, 167
 - sensing probability, 169
 - success probability, 174, 179
 - transmission probability, 174, 179

O

- Observation frequency, 55
- Optimization
 - aggregation strategy, 22
 - locally optimal decision, 69
 - network topology, 242
 - number of level one nodes, 205
 - packet size, 182, 200
 - tree-based topology, 130, 133, 140, 156

P

- Packet capture model, 139
- Packet delivery fraction, 48, 66
- Path loss, 76, 126
- Personal area network (PAN), 8, 137, 161
- Phenomenon
 - common binary, 32
 - spatially constant, 34
 - spatially non-constant, 102
- Poisson point process fields, 128

Probability

- a posteriori, 107
- a priori, 33
- average, 236
- cross-over, 34, 74, 110
- density function (p.d.f.), 105, 150
- fundamental theorem, 52
- mass function (p.m.f.), 128, 215
- maximum a posteriori (MAP), 83
- of being in sensing, 170, 189
- of being in transmission, 174
- of decision error, 36, 235
- of link connection, 127
- of non isolation in bounded regions, 149, 154
- of non isolation in infinite plane, 148
- of success, 168, 174, 179, 186, 195, 216
- total probability theorem, 85, 103

Q

Quality of service (QoS), 43

Quantization

- absence, 102
- binary, 102
- bits, 114
- multi-level, 102

R**Random variable**

- Bernoulli, 237
- binary, 44
- binomial, 83, 236
- exponential, 51
- Gaussian, 33, 84, 126
- Poisson, 127
- Rayleigh, 80

Reclustering

- absence, 52
- cost, 52, 54
- ideal, 52
- protocol, 54

Reduced function device (RFD), 12, 129

Relay, 79

Reliability, 239

Resource allocation, 234

Resource-constrained, 72

Retransmissions, 165, 235

S

Sensor selection, 94

Sensors observations accuracy, 117

Simulation

- IEEE 802.15.4 framework, 137
- Monte Carlo, 72, 88, 112
- Opnet, 48, 65
- results, 41, 140
- run, 113, 140, 197

slope, 71

SNR profile, 70

Statistical analysis

- connectivity, 123
- number of competing nodes, 175
- results, 133
- traffic distribution, 162

Statistics

- lifetime, 56
- traffic generated, 197

Superframe duration, 15, 164, 233

Superframe order, 15, 164, 233

Synchronization, 55

T

Throughput constraint, 233

Time division, 233

Time penalty, 58

TinyOS, 50

Topology

- star, 10, 16, 188, 204
 - tree-based, 130, 133, 139, 201, 204
- Trade-off, 157, 244

W

Waterfall, 88

Weighing, 239

Wireless sensor networks (WSNs)

- applications, 7
- energy efficiency, 5
- fundamentals, 3
- IEEE 802.15.4 Technology, 47
- multi-sink, 3, 124, 129
- research trends, 23

Z**Zigbee**

- end device, 22
- mesh topology, 22
- protocol stack, 19
- router, 22
- topologies, 20
- tree-based topology, 21, 201, 204