

Index

A

- Accelerometers range, 44–46, 64
- Active faults, 33
- Aliasing, 42, 44, 48, 64
- Allowable permanent wall displacements, 121, 133
- Analogue type filters, 49
- Angles of inclination to the horizontal of a critical slip surface behind a wall, 119, 121
- Annual rate of exceedance, 2, 8–9
- Average soil damping ratios, 69–70
- Average transversal wave velocities, 220
- Axial vertical stress at a depth, 161

B

- Background noise, 48, 56
- Base line error, 50
- Bearing capacity, 112–116, 126, 130–132, 140–141, 152–153, 167, 175, 190, 250
- Bench blasting, 36, 253
- Bernoulli's equation, 89–90
- Big Bear earthquake, 191–192
- Bishop method, 117
- Body waves, 29, 39–41, 82, 158, 162, 214, 242
- Boundaries between liquefiable and non-liquefiable (silty) sand, 10
- Boussinesq formula, 161
- Buckling, 139, 207, 223

C

- Central Chile earthquake, 94, 96
- Centrifuge tests, 121–122, 134, 182, 217
- Chaotic behaviour in non-linear dynamics, 18
- Chilean earthquake, 29
- Co-seismic permanent displacements, 5, 83
- Co-seismic sliding, 73, 83, 124, 127, 129
- Cosmetic damage of walls, 235–236
- Cyclic stress ratio, 2, 10–11, 14, 60, 86, 89, 105, 153

- Cyclic stress ratio for slopes, 86, 89, 153
- Cyclic triaxial, 61, 63, 125

D

- Damage in tunnels, 207
- Damping ratio, 2, 11–12, 14, 16, 57, 60–62, 69–71, 153, 203–204, 249, 251–252, 255, 257–258
- Decoupling, 42, 44, 64
- Demolition of structures, 36
- Discrete element model, 155, 159
- Dropping heavy weights, 237, 239
- Duration of flow, 91
- Duration of sliding, 78, 80, 83
- Duzce earthquake, 216, 222–223, 227–229
- Dynamic earth pressure increment, 122, 134

E

- Earthquake intensity, 30–31
- Earthquake magnitude scales, 28
- Edge-cube earthquake, 196
- Environmental sensitivity, 42
- Equivalent frictional angle of a sliding block, 88
- Equivalent number of significant stress cycles, 59, 163
- Equivalent period of structural vibration, 185
- Equivalent sliding block, 87–88
- Equivalent two sliding blocks, 124
- Euler equation, 139
- European Earthquake Data Base, 30
- European-Mediterranean seismic hazard map, 30
- Explosives, 216, 252

F

- Failure modes of pipelines, 207
- Fast Fourier transform, 49

Fault rupture area, 28
 Final factor of safety on sliding, 79–83, 127
 Fixation of transducers, 43, 64
 Fling step, 3–5, 27
 Footfall induced floor vibration, 234
 Fourier amplitude spectrum, 8, 49, 154, 195, 229
 Free vibration of an infinite soil layer, 16
 Frequency range, 35, 42, 45, 64, 158–159

G

Gauss integration points, 241–242
 Geophysical cone, 57–58, 64, 69
 Geophysical cross hole method, 56–57
 Geophysical reflection, 54–55
 Geophysical surveying, 51
 Geotechnical centrifuge, 19–20
 Global seismic hazard map, 30
 Grand Banks earthquake, 106
 Green function, 240
 Gross lateral forces moment equilibrium, 140

H

High speed trains, 35, 238–239
 High-strain dynamic (STATNAMIC), 19
 Horizontal drift over a tunnel height, 210
 Horizontal ground displacement, 5, 162, 210, 217, 222, 225, 227
 Hyogoken-Nanbu earthquake, 121, 125, 159, 171–175, 218, 220

I

Impact hammers, 35, 170, 237, 246–249
 Imperial Valley earthquake, 189, 194
 Inertial interaction, 154, 158, 180, 185, 201, 209
 Initial factor of safety before sliding, 76–77, 79–80, 83, 127
 Inverted pendulum, 158, 166, 185
 Iran, 9
 Izmit (Kocaeli) earthquake, 165

K

Kanagawa-ken Seibu earthquake, 195
 Kinematic interaction, 154, 158, 180, 184–185
 Kinematic soil pile interaction, 17
 Kishiro-Oki earthquake, 97
 Kocaeli earthquake, 228
 Kyoshin Network K-NET, 30

L

Landers earthquake, 192
 Landslides occurrence, 32
 Lateral soil force acting on a retaining wall in seismic condition, 118–119
 Lateral soil forces on a retaining wall in static condition, 119
 Linear vibration source, 241, 249
 Local soil layers effect, 28
 Loma Prieta earthquake, 190
 Longitudinal wave velocity, 15, 41, 62–63, 71
 Love waves, 41
 Low-pass (anti-aliasing) filter, 48–49

M

Magnitude scaling factors, 10
 Maximum amplitude of ground displacement, 27, 224
 Maximum fault surface displacement, 28, 34, 220, 223
 Maximum shear modulus, 15, 69, 240
 Maximum slip, 78
 Maximum velocity and acceleration of sliding, 78–83, 127
 Michoacan earthquake, 187
 Moho surface, 3–5, 28
 Moment magnitude, 2–4, 29, 32, 163, 218, 222, 227
 Mononobe-Okabe method, 118, 127, 131, 144

N

(N_1)₆₀, 28
 The National Geophysical Data Center - NGDC, 30
 Net lateral force moment equilibrium, 140
 Newmark sliding block method, 74, 83, 121, 124, 134, 157
 Nihonkai-Chubu earthquake, 101, 147
 Niigata earthquake, 198–199
 Non-basic errors, 47
 Normal faults, 33–34
 Number of effective acceleration cycles, 163
 Numerical filter, 49
 Nyquist frequency, 48, 50

P

The Pacific Earthquake Engineering Research Center - PEER, 30
 Parnitha earthquake, 145–146
 Particle velocity caused by trains, 35
 Particle velocity due to tunnelling, 239
 Passive lateral soil force in front of a retaining wall in seismic condition, 119

- Peak horizontal ground acceleration, 2, 6, 10, 30, 36, 69–71, 83, 86, 88, 124, 147, 155–156, 163, 183, 191, 207, 211, 222, 241, 251
- Peak horizontal ground displacement, 5, 210, 222
- Peak horizontal ground velocity, 3, 241
- Peloponnesus earthquake, 128, 159
- Petrolia earthquake, 193
- Phase shift, 42, 158
- Pile driving, 21, 35, 42, 58, 64, 170–173, 176, 235, 237, 246–252
- Pile shaft force, 187
- Pile toe force, 246, 249
- Pipeline repair rates, 213, 228
- Planar vibration source, 241
- Point vibration source, 240, 254
- Post-seismic sliding, 83, 124, 127, 129
- Potential of liquefaction of sandy soil, 10
- Predominant period of ground acceleration, 30
- Principal ground strain, 213
- Prismatic vibration source, 241–242, 255
- Punch through type failure, 115
- P-y springs, 181
- R**
- Ratios between the peak horizontal ground acceleration at ground surface and at depths, 211
- Ratio between velocities of the longitudinal and transversal waves, 39
- Rayleigh waves, 9, 29, 40–41, 162, 171
- Residual shear strength, 70
- Resolution, 42, 47–48, 54–55
- Resonance, 36, 60, 166–167, 180, 189, 242–243
- Resonance column, 36, 60, 166–167, 180, 189, 242
- Response spectra, 2, 6–9, 144–147, 156, 163, 184, 189, 191–192, 200
- Return period of earthquakes, 9
- Reverse (thrust) faults, 3–4, 34
- Richter magnitude, 29
- R.m.s. acceleration, 233–234
- Road traffic, 35, 239–240
- Road traffic induced peak particle velocities, 239
- Rotating block model, 157, 176
- Rupture directivity, 3–5, 27, 163
- S**
- Sampling and testing of ground, 51
- San Fernando earthquake, 91
- San Francisco earthquake, 99
- Sectional forces and bending moment in a circular tunnel lining, 209, 217
- Sedimentation time, 91
- Sediment basin edge and depth effects, 3–5, 27
- Seismic gaps, 28
- Seismic moment, 29
- Sensitive equipment, 233
- Sensitivity, 42, 87
- Shaking table, 18–20, 121–122, 154, 181–182
- Shear modulus ratio, 15
- Shear modulus reduction factors, 224
- Shear strength of fine grained soil (fine silt and clay) in cyclic condition, 70
- Shear strength of fine grained soil (fine silt and clay) in static condition, 70
- Simple bearing capacity analogy, 141
- Simple shear test, 13–14, 59–60, 71
- Single degree of freedom oscillator, 7, 12, 203
- Slope failures, 30–33, 70, 72
- Soil dry density, 160
- Soil friction angle, 67, 69, 87–88, 95, 113–114, 116–118, 123, 125, 141
- Soil friction angle in cyclic condition, 69, 87, 123
- Soil liquefaction in static conditions, 86
- Soil permeability of water, 63
- Soil porosity, 63, 68, 160–161
- Soil relative density, 15, 67
- Soil shear modulus, 11, 15–16, 18, 155, 209, 238
- Soil stiffness decrease, 69
- Soil void ratio, 67–68, 160
- Source energy, 44, 249, 258
- Source to site distance, 27, 74, 83, 124, 127, 131, 133
- Specific gravity of soil solids, 160
- Standard penetration test, 10, 15, 57, 67, 69, 71, 86–87, 125, 129, 132, 160, 164, 168, 174, 197–199
- Static stiffness coefficients, 17
- Static stresses in tunnel lining, 224
- Stokes law, 91
- Strains, 41, 51, 58, 179, 182, 208, 227
- Stresses, 39, 41, 51, 59, 63, 65, 68, 86, 113–117, 141–142, 146–147, 163, 180, 182, 208, 212, 224
- Strike-slip faults, 3–4, 34
- Surface rupture length, 28
- Surface waves, 40, 107, 158, 214–215

T

- Transient ground strain, 214
- Transversal forces and bending moments in rectangular tunnels, 210
- Transversal wave velocity, 3–5, 15–16, 18, 41, 60, 71, 86, 144, 146, 154–155, 159, 162, 169, 183, 187, 194, 210–211, 218–220, 223–224, 245, 252, 257
- Truncated cone, 161
- Tsunamis, 29, 33, 35
- Turbidity current, 107
- Turbidity flow, 105
- Two-block sliding method, 74, 76, 134

U

- Ultimate bearing stress in undrained conditions, 115

The United States Geological Survey – USGS, 30

V

- Velocity transducer, 43
- Vertical shafts, 207–229
- Vibrating stone columns, 239
- Vibration from blasting, 249
- Vibration hammers, 246
- Vibration mode, 17, 191–192, 211, 220–221
- Vibrations from blasting, 235
- Vibratory hammers, 247–248, 251
- Vibratory rollers, 36, 238, 242, 245
- Viscous damping coefficients, 17–18
- Void ratio, 15, 67–68, 160

Y

- Yong modulus, 69