

SpringerBriefs in Computer Science

For further volumes:
<http://www.springer.com/series/10028>

Seungyeol Lee

Glazed Panel Construction with Human–Robot Cooperation

Seungyeol Lee
Robotics Research Division
Daegu Gyeongbuk Institute of Science
and Technology
50-1, Sang-Ri, Hyeonpung-Myeon,
Dalseong-Gun, Daegu 711-813
Republic of Korea
suprasy@paran.com

ISSN 2191-5768
ISBN 978-1-4614-1417-9
DOI 10.1007/978-1-4614-1418-6
Springer New York Dordrecht Heidelberg London

e-ISSN 2191-5776
e-ISBN 978-1-4614-1418-6

Library of Congress Control Number: 2011936141

© The Author 2011

All rights reserved. This work may not be translated or copied in whole or in part without the written permission of the publisher (Springer Science+Business Media, LLC, 233 Spring Street, New York, NY 10013, USA), except for brief excerpts in connection with reviews or scholarly analysis. Use in connection with any form of information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed is forbidden.

The use in this publication of trade names, trademarks, service marks, and similar terms, even if they are not identified as such, is not to be taken as an expression of opinion as to whether or not they are subject to proprietary rights.

Cover design: eStudio Calamar, Berlin/Figueres

Printed on acid-free paper

Springer is part of Springer Science+Business Media (www.springer.com)

Preface

Recently, the tendency for buildings and structures is to be ever larger and taller. A new method of construction is, therefore, required to follow the current trend, and construction machinery and equipment are being developed to help in the process at various construction sites. An imbalance in technical manpower supply and demand is a serious problem on construction sites. This labor shortage and the aging of the skilled worker on the construction site cause a lasting increase in wages. These technical service problems have appeared to lower functionality in construction situations. Consequently, the rising labor costs, poorer execution quality, delayed construction period, and increased construction expenses have led to reduced safety and more accidents in construction areas. This problem corresponds to the potential for “automation system and robotics in construction” as one of the solutions. It is possible to substitute an automatic system and robot for technical manpower, which simultaneously increases the working speed and construction quality, improves safety and reduces the cost of construction.

Generally, almost half of construction work is said to be material handling. Materials and equipment used for construction are heavy and bulky for humans. Through the case studies on constructions, to which building material handling robot was applied, however, we could find some factors to be improved. Unlike the automation lines of the general manufacturing industry, construction sites rarely shows repeated operational patterns use to its unstructured processes. That is, construction robots execute orders while operating in a dynamic environment where structures, operators, and equipment are constantly changing. Therefore, a guidance or remote-controlled system is the natural way to implement construction robot manipulators. However, a remote-controlled system has to solve some problems. One of the solutions to address these problems is the technology of human-robot cooperative manipulation.

The purpose of this study is to develop human-robot cooperative manipulation technology to solve all kinds of problems generated by the current installation method, which depends on manpower or a low-quality construction robot for the installation of heavy and bulk building materials at construction sites. The essential technologies of human-robot cooperative manipulation are considered

through the analysis of an existing installation method. The prototype's hardware design and control algorithm development are achieved using the results of this analysis. The developed prototype system is corrected and complemented based on the results of a performance test. To apply human-robot cooperative manipulation at real construction sites, we executed additional work required for application. After application to real construction sites, evaluation on the productivity and safety of the developed system was done by comparing and analyzing with the existing installation methods. Lastly, I would like to acknowledge that this book would not exist without the support of my spouse, SAMSUNG CORPORATION.

Notations

Symbol	Description
$\underline{\mathbf{F}}_h(\underline{\mathbf{T}}_h)$	The force (torque), measured by the operational force sensor which is generated by the interaction between the operator and HRI device
$\underline{\mathbf{F}}_e(\underline{\mathbf{T}}_e)$	The force (torque), measured by the environmental force sensor which is generated by the interaction between the environment and a heavy material
$\mathbf{M}_{pt}(\mathbf{M}_{ot}), \mathbf{B}_{pt}(\mathbf{B}_{ot})$	The impedance parameters, that are related to a desired dynamic behavior, are $\mathbf{M}_{pt}(\mathbf{M}_{ot})$ and $\mathbf{B}_{pt}(\mathbf{B}_{ot})$, (n by n positive definite diagonal inertia and damping matrices), ‘p’ stands for the position and ‘o’ stands for the orientation
λ	The force augmentation ratio of an operator
$\mathbf{M}_{pe}(\mathbf{M}_{oe}), \mathbf{B}_{pe}(\mathbf{B}_{oe}), \mathbf{K}_{pe}(\mathbf{K}_{oe})$	The impedance parameters that determine a dynamic behavior of the end effector for interactions with an environment
$\{D\}$	The desired frame specified by a desired position vector \mathbf{p}_d and a desired rotation matrix \mathbf{R}_d
$\{C\}$	The compliant frame specified by a position vector \mathbf{p}_c and a rotation matrix \mathbf{R}_c
$\mathbf{p}_e, \mathbf{R}_e$	The actual end effector position and orientation
$\underline{\dot{\mathbf{p}}}_e, \omega_e$	The actual end-effector linear velocity and angular velocity
\mathbf{B}_h	The damping coefficient of an operator’s arm
\mathbf{K}_h	The stiffness coefficient of an operator’s arm
$\underline{\ddot{\mathbf{X}}}_d$	Desired acceleration related target dynamics
$\underline{\dot{\mathbf{X}}}_d$	Desired velocity related target dynamics

Contents

1	Introduction	1
1.1	Problems in Construction Industry	1
1.2	Panel Construction Robots	2
1.3	Needs for Human–Robot Cooperative Manipulation	3
	References	5
2	Control Algorithm for Human–Robot Cooperation	7
2.1	Outline	7
2.2	System Modeling	8
2.2.1	Operation in Unconstrained Case	8
2.2.2	Operation in Constrained Case	9
2.3	Control Algorithm	11
2.4	Experimental System	12
2.5	Experiment and Results	13
2.5.1	Influence of Impedance Parameters	15
2.5.2	Influence of Inner Motion Control Loop	17
2.5.3	Influence of Force Augmentation Ratio	18
2.5.4	Influence of an Environmental Stiffness Parameter	21
	References	22
3	Conceptual Design of Human–Robot Cooperative System	23
3.1	Jab Analysis	23
3.2	System Configuration	24
4	Prototype for Glazed Panel Construction Robot	31
4.1	Basic System	31
4.1.1	6DOF Manipulator	31
4.1.2	Mobile Platform	34

4.2	Additional Module.	36
4.2.1	Hardware	36
4.2.2	Software	38
4.3	Experiments and Results	40
	Reference	45
5	Glazed Ceiling Panel Construction Robot	47
5.1	Basic System	47
5.1.1	Multi-DOF Manipulator	48
5.1.2	Aerial Work Platform	49
5.2	Additional Module.	52
5.2.1	Human Robot Interface	52
5.2.2	Deck Design of Aerial Work Platform.	53
5.2.3	Vacuum Suction Device.	53
5.3	Design of Robotized Construction Process	55
5.4	Field Tests and Results	58
	Reference	64
6	Conclusion and Future Works	65
	Index	69